

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Single Window Units

Date: 9-May-07

Code	Single Window Unit																
	Dimensions			Rough Opening			DP Rating			Ventilation		Clear Opening					
	Width	Height		Width	Height		Equal	Cottage	Optional	Daylight	Equal	Cottage	Equal	Cottage			
18210	21	5/8	x	37	22	1/8	x	37	1/2	DP-50	-	-	3.5	1.8	-	-	-
1832	21	5/8	x	41	22	1/8	x	41	1/2	DP-50	-	-	3.9	2.0	-	-	-
18310	21	5/8	x	49	22	1/8	x	49	1/2	DP-50	-	-	4.9	2.5	-	-	-
1842	21	5/8	x	53	22	1/8	x	53	1/2	DP-50	-	-	5.3	2.7	-	-	-
1846	21	5/8	x	57	22	1/8	x	57	1/2	DP-50	-	-	5.8	2.9	-	-	-
1848	21	5/8	x	59	22	1/8	x	59	1/2	DP-50	-	-	6.0	3.1	-	-	-
1852	21	5/8	x	65	22	1/8	x	65	1/2	DP-35	-	DP-50	6.7	3.4	-	-	-
1856	21	5/8	x	69	22	1/8	x	69	1/2	DP-35	-	DP-50	7.2	3.7	-	-	-
1856c	21	5/8	x	69	22	1/8	x	69	1/2	-	DP-50	-	7.2	-	2.9	-	-
1862	21	5/8	x	77	22	1/8	x	77	1/2	DP-35	-	DP-50	8.1	4.1	-	-	-
110210	23	5/8	x	37	24	1/8	x	37	1/2	DP-50	-	-	3.9	2.0	-	-	-
11032	23	5/8	x	41	24	1/8	x	41	1/2	DP-50	-	-	4.4	2.2	-	-	-
110310	23	5/8	x	49	24	1/8	x	49	1/2	DP-50	-	-	5.4	2.8	-	-	-
11042	23	5/8	x	53	24	1/8	x	53	1/2	DP-50	-	-	6.0	3.0	-	-	-
11046	23	5/8	x	57	24	1/8	x	57	1/2	DP-50	-	-	6.5	3.3	-	-	-
11048	23	5/8	x	59	24	1/8	x	59	1/2	DP-50	-	-	6.7	3.4	-	-	-
11052	23	5/8	x	65	24	1/8	x	65	1/2	DP-35	-	DP-50	7.5	3.8	-	-	-
11056	23	5/8	x	69	24	1/8	x	69	1/2	DP-35	-	DP-50	8.1	4.1	-	-	-
11056c	23	5/8	x	69	24	1/8	x	69	1/2	-	DP-50	-	8.1	-	3.3	-	-
11062	23	5/8	x	77	24	1/8	x	77	1/2	DP-35	-	DP-50	9.1	4.6	-	-	-
20210	25	5/8	x	37	26	1/8	x	37	1/2	DP-50	-	-	4.3	2.2	-	-	-
2032	25	5/8	x	41	26	1/8	x	41	1/2	DP-50	-	-	4.9	2.5	-	-	-
20310	25	5/8	x	49	26	1/8	x	49	1/2	DP-50	-	-	6.0	3.0	-	-	-
2042	25	5/8	x	53	26	1/8	x	53	1/2	DP-50	-	-	6.6	3.3	-	-	-
2046	25	5/8	x	57	26	1/8	x	57	1/2	DP-50	-	-	7.2	3.6	-	-	-
2048	25	5/8	x	59	26	1/8	x	59	1/2	DP-50	-	-	7.5	3.8	-	-	-
2052	25	5/8	x	65	26	1/8	x	65	1/2	DP-35	-	DP-50	8.3	4.2	-	-	-
2056	25	5/8	x	69	26	1/8	x	69	1/2	DP-35	-	DP-50	8.9	4.5	-	-	-
2056c	25	5/8	x	69	26	1/8	x	69	1/2	-	DP-50	-	8.9	-	3.6	-	-
2062	25	5/8	x	77	26	1/8	x	77	1/2	DP-35	-	DP-50	10.1	5.1	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area

Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Single Window Units

Date: 9-May-07

Code	Single Window Unit											
	Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
22210	27 5/8	x 37	28 1/8	x 37 1/2	DP-50	-	-	4.7	2.4	-	-	-
2232	27 5/8	x 41	28 1/8	x 41 1/2	DP-50	-	-	5.3	2.7	-	-	-
22310	27 5/8	x 49	28 1/8	x 49 1/2	DP-50	-	-	6.6	3.3	-	-	-
2242	27 5/8	x 53	28 1/8	x 53 1/2	DP-50	-	-	7.2	3.6	-	-	-
2246	27 5/8	x 57	28 1/8	x 57 1/2	DP-50	-	-	7.9	4.0	-	-	-
2248	27 5/8	x 59	28 1/8	x 59 1/2	DP-50	-	-	8.2	4.1	-	-	-
2252	27 5/8	x 65	28 1/8	x 65 1/2	DP-35	-	DP-50	9.1	4.6	-	-	-
2256	27 5/8	x 69	28 1/8	x 69 1/2	DP-35	-	DP-50	9.8	4.9	-	-	-
2256c	27 5/8	x 69	28 1/8	x 69 1/2	-	DP-50	-	9.8	-	4.0	-	-
2262	27 5/8	x 77	28 1/8	x 77 1/2	DP-35	-	DP-50	11.0	5.6	-	-	-
24210	29 5/8	x 37	30 1/8	x 37 1/2	DP-50	-	-	5.1	2.6	-	-	-
2432	29 5/8	x 41	30 1/8	x 41 1/2	DP-50	-	-	5.8	2.9	-	-	-
24310	29 5/8	x 49	30 1/8	x 49 1/2	DP-50	-	-	7.2	3.6	-	-	-
2442	29 5/8	x 53	30 1/8	x 53 1/2	DP-50	-	-	7.9	4.0	-	-	-
2446	29 5/8	x 57	30 1/8	x 57 1/2	DP-50	-	-	8.6	4.3	-	-	-
2448	29 5/8	x 59	30 1/8	x 59 1/2	DP-50	-	-	8.9	4.5	-	-	-
2452	29 5/8	x 65	30 1/8	x 65 1/2	DP-35	-	DP-50	9.9	5.0	-	-	-
2456	29 5/8	x 69	30 1/8	x 69 1/2	DP-35	-	DP-50	10.6	5.4	-	-	-
2456c	29 5/8	x 69	30 1/8	x 69 1/2	-	DP-50	-	10.6	-	4.3	-	-
2462	29 5/8	x 77	30 1/8	x 77 1/2	DP-35	-	DP-50	12.0	6.1	-	Yes	-
26210	31 5/8	x 37	32 1/8	x 37 1/2	DP-50	-	-	5.5	2.8	-	-	-
2632	31 5/8	x 41	32 1/8	x 41 1/2	DP-50	-	-	6.3	3.1	-	-	-
26310	31 5/8	x 49	32 1/8	x 49 1/2	DP-50	-	-	7.8	3.9	-	-	-
2642	31 5/8	x 53	32 1/8	x 53 1/2	DP-50	-	-	8.5	4.3	-	-	-
2646	31 5/8	x 57	32 1/8	x 57 1/2	DP-50	-	-	9.2	4.7	-	-	-
2648	31 5/8	x 59	32 1/8	x 59 1/2	DP-50	-	-	9.6	4.8	-	-	-
2652	31 5/8	x 65	32 1/8	x 65 1/2	DP-35	-	DP-50	10.7	5.4	-	-	-
2656	31 5/8	x 69	32 1/8	x 69 1/2	DP-35	-	DP-50	11.5	5.8	-	Yes	-
2656c	31 5/8	x 69	32 1/8	x 69 1/2	-	DP-50	-	11.5	-	4.7	-	-
2662	31 5/8	x 77	32 1/8	x 77 1/2	DP-35	-	DP-50	13.0	6.5	-	Yes	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Single Window Units

Date: 9-May-07

Code	Single Window Unit																	
	Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening							
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage						
28210	33	5/8	x	37	34	1/8	x	37	1/2	DP-50	-	-	5.9	3.0	-	-	-	-
2832	33	5/8	x	41	34	1/8	x	41	1/2	DP-50	-	-	6.7	3.4	-	-	-	-
28310	33	5/8	x	49	34	1/8	x	49	1/2	DP-50	-	-	8.3	4.2	-	-	-	-
2842	33	5/8	x	53	34	1/8	x	53	1/2	DP-50	-	-	9.1	4.6	-	-	-	-
2846	33	5/8	x	57	34	1/8	x	57	1/2	DP-50	-	-	9.9	5.0	-	-	-	-
2848	33	5/8	x	59	34	1/8	x	59	1/2	DP-50	-	-	10.3	5.2	-	-	-	-
2852	33	5/8	x	65	34	1/8	x	65	1/2	DP-35	-	DP-50	11.5	5.8	-	Yes	-	-
2856	33	5/8	x	69	34	1/8	x	69	1/2	DP-35	-	DP-50	12.3	6.2	-	Yes	-	-
2856c	33	5/8	x	69	34	1/8	x	69	1/2	-	DP-50	-	12.3	-	5.0	-	-	-
2862	33	5/8	x	77	34	1/8	x	77	1/2	DP-35	-	DP-50	13.9	7.0	-	Yes	-	-
210210	35	5/8	x	37	36	1/8	x	37	1/2	DP-50	-	-	6.3	3.2	-	-	-	-
21032	35	5/8	x	41	36	1/8	x	41	1/2	DP-50	-	-	7.2	3.6	-	-	-	-
210310	35	5/8	x	49	36	1/8	x	49	1/2	DP-50	-	-	8.9	4.5	-	-	-	-
21042	35	5/8	x	53	36	1/8	x	53	1/2	DP-50	-	-	9.8	4.9	-	-	-	-
21046	35	5/8	x	57	36	1/8	x	57	1/2	DP-50	-	-	10.6	5.3	-	-	-	-
21048	35	5/8	x	59	36	1/8	x	59	1/2	DP-50	-	-	11.0	5.6	-	-	-	-
21052	35	5/8	x	65	36	1/8	x	65	1/2	DP-35	-	DP-50	12.3	6.2	-	Yes	-	-
21056	35	5/8	x	69	36	1/8	x	69	1/2	DP-35	-	DP-50	13.2	6.6	-	Yes	-	-
21056c	35	5/8	x	69	36	1/8	x	69	1/2	-	DP-50	-	13.2	-	5.3	-	-	-
21062	35	5/8	x	77	36	1/8	x	77	1/2	DP-35	-	-	14.9	7.5	-	Yes	-	-
30210	37	5/8	x	37	38	1/8	x	37	1/2	DP-50	-	-	6.8	3.4	-	-	-	-
3032	37	5/8	x	41	38	1/8	x	41	1/2	DP-50	-	-	7.7	3.8	-	-	-	-
30310	37	5/8	x	49	38	1/8	x	49	1/2	DP-50	-	-	9.5	4.8	-	-	-	-
3042	37	5/8	x	53	38	1/8	x	53	1/2	DP-50	-	-	10.4	5.2	-	-	-	-
3046	37	5/8	x	57	38	1/8	x	57	1/2	DP-50	-	-	11.3	5.7	-	Yes	-	-
3048	37	5/8	x	59	38	1/8	x	59	1/2	DP-50	-	-	11.8	5.9	-	Yes	-	-
3052	37	5/8	x	65	38	1/8	x	65	1/2	DP-35	-	DP-50	13.1	6.6	-	Yes	-	-
3056	37	5/8	x	69	38	1/8	x	69	1/2	DP-35	-	DP-50	14.0	7.1	-	Yes	-	-
3056c	37	5/8	x	69	38	1/8	x	69	1/2	-	DP-50	-	14.0	-	5.7	-	-	Yes
3062	37	5/8	x	77	38	1/8	x	77	1/2	DP-35	-	-	15.9	8.0	-	Yes	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Single Window Units

Date: 9-May-07

Code	Single Window Unit																	
	Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening							
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage						
32210	39	5/8	x	37	40	1/8	x	37	1/2	DP-35	-	DP-50	7.2	3.6	-	-	-	-
3232	39	5/8	x	41	40	1/8	x	41	1/2	DP-35	-	DP-50	8.1	4.1	-	-	-	-
32310	39	5/8	x	49	40	1/8	x	49	1/2	DP-35	-	DP-50	10.1	5.1	-	-	-	-
3242	39	5/8	x	53	40	1/8	x	53	1/2	DP-35	-	DP-50	11.0	5.5	-	-	-	-
3246	39	5/8	x	57	40	1/8	x	57	1/2	DP-35	-	DP-50	12.0	6.0	-	Yes	-	-
3248	39	5/8	x	59	40	1/8	x	59	1/2	DP-35	-	DP-50	12.5	6.3	-	Yes	-	-
3252	39	5/8	x	65	40	1/8	x	65	1/2	DP-35	-	-	13.9	7.0	-	Yes	-	-
3256	39	5/8	x	69	40	1/8	x	69	1/2	DP-35	-	-	14.9	7.5	-	Yes	-	-
3256c	39	5/8	x	69	40	1/8	x	69	1/2	-	NT	-	14.9	-	6.0	-	-	Yes
3262	39	5/8	x	77	40	1/8	x	77	1/2	DP-35	-	-	16.8	8.5	-	Yes	-	-
34210	41	5/8	x	37	42	1/8	x	37	1/2	DP-35	-	DP-50	7.6	3.8	-	-	-	-
3432	41	5/8	x	41	42	1/8	x	41	1/2	DP-35	-	DP-50	8.6	4.3	-	-	-	-
34310	41	5/8	x	49	42	1/8	x	49	1/2	DP-35	-	DP-50	10.6	5.3	-	-	-	-
3442	41	5/8	x	53	42	1/8	x	53	1/2	DP-35	-	DP-50	11.7	5.9	-	-	-	-
3446	41	5/8	x	57	42	1/8	x	57	1/2	DP-35	-	DP-50	12.7	6.4	-	Yes	-	-
3448	41	5/8	x	59	42	1/8	x	59	1/2	DP-35	-	DP-50	13.2	6.6	-	Yes	-	-
3452	41	5/8	x	65	42	1/8	x	65	1/2	DP-35	-	-	14.7	7.4	-	Yes	-	-
3456	41	5/8	x	69	42	1/8	x	69	1/2	DP-35	-	-	15.8	7.9	-	Yes	-	-
3456c	41	5/8	x	69	42	1/8	x	69	1/2	-	NT	-	15.8	-	6.4	-	-	Yes
3462	41	5/8	x	77	42	1/8	x	77	1/2	DP-35	-	-	17.8	9.0	-	Yes	-	-
36210	43	5/8	x	37	44	1/8	x	37	1/2	DP-35	-	-	8.0	4.0	-	-	-	-
3632	43	5/8	x	41	44	1/8	x	41	1/2	DP-35	-	-	9.1	4.5	-	-	-	-
36310	43	5/8	x	49	44	1/8	x	49	1/2	DP-35	-	-	11.2	5.6	-	-	-	-
3642	43	5/8	x	53	44	1/8	x	53	1/2	DP-35	-	-	12.3	6.2	-	-	-	-
3646	43	5/8	x	57	44	1/8	x	57	1/2	DP-35	-	-	13.4	6.7	-	Yes	-	-
3648	43	5/8	x	59	44	1/8	x	59	1/2	DP-35	-	-	13.9	7.0	-	Yes	-	-
3652	43	5/8	x	65	44	1/8	x	65	1/2	DP-35	-	-	15.5	7.8	-	Yes	-	-
3656	43	5/8	x	69	44	1/8	x	69	1/2	DP-35	-	-	16.6	8.3	-	Yes	-	-
3656c	43	5/8	x	69	44	1/8	x	69	1/2	-	NT	-	16.6	-	6.7	-	-	Yes
3662	43	5/8	x	77	44	1/8	x	77	1/2	DP-35	-	-	18.8	9.4	-	Yes	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Single Window Units

Date: 9-May-07

Code	Single Window Unit												
	Dimensions		Rough Opening			DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional	Equal		Cottage	Equal	Cottage	
38210	45 5/8	x 37	46 1/8	x 37 1/2	NT	-	-	8.4	4.2	-	-	-	
3832	45 5/8	x 41	46 1/8	x 41 1/2	NT	-	-	9.5	4.8	-	-	-	
38310	45 5/8	x 49	46 1/8	x 49 1/2	NT	-	-	11.8	5.9	-	-	-	
3842	45 5/8	x 53	46 1/8	x 53 1/2	NT	-	-	12.9	6.5	-	-	-	
3846	45 5/8	x 57	46 1/8	x 57 1/2	NT	-	-	14.1	7.1	-	Yes	-	
3848	45 5/8	x 59	46 1/8	x 59 1/2	NT	-	-	14.6	7.3	-	Yes	-	
3852	45 5/8	x 65	46 1/8	x 65 1/2	NT	-	-	16.3	8.2	-	Yes	-	
3856	45 5/8	x 69	46 1/8	x 69 1/2	NT	-	-	17.5	8.8	-	Yes	-	
3856c	45 5/8	x 69	46 1/8	x 69 1/2	-	NT	-	17.5	-	7.1	-	Yes	
3862	45 5/8	x 77	46 1/8	x 77 1/2	NT	-	-	19.7	9.9	-	Yes	-	
310210	47 5/8	x 37	48 1/8	x 37 1/2	NT	-	-	8.8	4.4	-	-	-	
31032	47 5/8	x 41	48 1/8	x 41 1/2	NT	-	-	10.0	5.0	-	-	-	
310310	47 5/8	x 49	48 1/8	x 49 1/2	NT	-	-	12.4	6.2	-	-	-	
31042	47 5/8	x 53	48 1/8	x 53 1/2	NT	-	-	13.6	6.8	-	-	-	
31046	47 5/8	x 57	48 1/8	x 57 1/2	NT	-	-	14.8	7.4	-	Yes	-	
31048	47 5/8	x 59	48 1/8	x 59 1/2	NT	-	-	15.3	7.7	-	Yes	-	
31052	47 5/8	x 65	48 1/8	x 65 1/2	NT	-	-	17.1	8.6	-	Yes	-	
31056	47 5/8	x 69	48 1/8	x 69 1/2	NT	-	-	18.3	9.2	-	Yes	-	
31056c	47 5/8	x 69	48 1/8	x 69 1/2	-	NT	-	18.3	-	7.4	-	Yes	
31062	47 5/8	x 77	48 1/8	x 77 1/2	NT	-	-	20.7	10.4	-	Yes	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Twin Window Units

Date: 9-May-07

Code	Twin Window Unit																
	Dimensions			Rough Opening			DP Rating			Daylight	Ventilation		Clear Opening				
	Width	Height		Width	Height		Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage			
18210	43	3/4	x	37	44	1/4	x	37	1/2	DP-30	-	DP-50	6.9	3.5	-	-	-
1832	43	3/4	x	41	44	1/4	x	41	1/2	DP-30	-	DP-50	7.9	4.0	-	-	-
18310	43	3/4	x	49	44	1/4	x	49	1/2	DP-30	-	DP-50	9.7	4.9	-	-	-
1842	43	3/4	x	53	44	1/4	x	53	1/2	DP-30	-	DP-50	10.7	5.4	-	-	-
1846	43	3/4	x	57	44	1/4	x	57	1/2	DP-30	-	DP-50	11.6	5.9	-	-	-
1848	43	3/4	x	59	44	1/4	x	59	1/2	DP-30	-	DP-50	12.1	6.1	-	-	-
1852	43	3/4	x	65	44	1/4	x	65	1/2	DP-30	-	DP-50	13.5	6.8	-	-	-
1856	43	3/4	x	69	44	1/4	x	69	1/2	DP-30	-	DP-50	14.4	7.3	-	-	-
1856c	43	3/4	x	69	44	1/4	x	69	1/2	-	DP-40	-	14.4	-	5.9	-	-
1862	43	3/4	x	77	44	1/4	x	77	1/2	DP-30	-	DP-50	16.3	8.3	-	-	-
110210	47	3/4	x	37	48	1/4	x	37	1/2	DP-30	-	DP-50	7.7	3.9	-	-	-
11032	47	3/4	x	41	48	1/4	x	41	1/2	DP-30	-	DP-50	8.8	4.4	-	-	-
110310	47	3/4	x	49	48	1/4	x	49	1/2	DP-30	-	DP-50	10.9	5.5	-	-	-
11042	47	3/4	x	53	48	1/4	x	53	1/2	DP-30	-	DP-50	11.9	6.0	-	-	-
11046	47	3/4	x	57	48	1/4	x	57	1/2	DP-30	-	DP-50	13.0	6.6	-	-	-
11048	47	3/4	x	59	48	1/4	x	59	1/2	DP-30	-	DP-50	13.5	6.8	-	-	-
11052	47	3/4	x	65	48	1/4	x	65	1/2	DP-30	-	DP-50	15.1	7.6	-	-	-
11056	47	3/4	x	69	48	1/4	x	69	1/2	DP-30	-	DP-50	16.1	8.2	-	-	-
11056c	47	3/4	x	69	48	1/4	x	69	1/2	-	DP-40	-	16.1	-	6.6	-	-
11062	47	3/4	x	77	48	1/4	x	77	1/2	DP-30	-	DP-50	18.2	9.2	-	-	-
20210	51	3/4	x	37	52	1/4	x	37	1/2	DP-30	-	DP-50	8.6	4.3	-	-	-
2032	51	3/4	x	41	52	1/4	x	41	1/2	DP-30	-	DP-50	9.7	4.9	-	-	-
20310	51	3/4	x	49	52	1/4	x	49	1/2	DP-30	-	DP-50	12.0	6.1	-	-	-
2042	51	3/4	x	53	52	1/4	x	53	1/2	DP-30	-	DP-50	13.2	6.7	-	-	-
2046	51	3/4	x	57	52	1/4	x	57	1/2	DP-30	-	DP-50	14.3	7.3	-	-	-
2048	51	3/4	x	59	52	1/4	x	59	1/2	DP-30	-	DP-50	14.9	7.5	-	-	-
2052	51	3/4	x	65	52	1/4	x	65	1/2	DP-30	-	DP-50	16.7	8.4	-	-	-
2056	51	3/4	x	69	52	1/4	x	69	1/2	DP-30	-	DP-50	17.8	9.0	-	-	-
2056c	51	3/4	x	69	52	1/4	x	69	1/2	-	DP-40	-	17.8	-	7.3	-	-
2062	51	3/4	x	77	52	1/4	x	77	1/2	DP-30	-	DP-50	20.1	10.2	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area

Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum twin window width for 20" clear opening width – 49 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Twin Window Units

Date: 9-May-07

Code	Twin Window Unit											
	Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
22210	55	3/4 x 37	56	1/4 x 37 1/2	DP-30	-	DP-50	9.4	4.7	-	-	-
2232	55	3/4 x 41	56	1/4 x 41 1/2	DP-30	-	DP-50	10.7	5.4	-	-	-
22310	55	3/4 x 49	56	1/4 x 49 1/2	DP-30	-	DP-50	13.2	6.7	-	-	-
2242	55	3/4 x 53	56	1/4 x 53 1/2	DP-30	-	DP-50	14.5	7.3	-	-	-
2246	55	3/4 x 57	56	1/4 x 57 1/2	DP-30	-	DP-50	15.7	7.9	-	-	-
2248	55	3/4 x 59	56	1/4 x 59 1/2	DP-30	-	DP-50	16.4	8.3	-	-	-
2252	55	3/4 x 65	56	1/4 x 65 1/2	DP-30	-	DP-50	18.3	9.2	-	-	-
2256	55	3/4 x 69	56	1/4 x 69 1/2	DP-30	-	DP-50	19.5	9.9	-	-	-
2256c	55	3/4 x 69	56	1/4 x 69 1/2	-	DP-40	-	19.5	-	7.9	-	-
2262	55	3/4 x 77	56	1/4 x 77 1/2	DP-30	-	DP-50	22.1	11.2	-	-	-
24210	59	3/4 x 37	60	1/4 x 37 1/2	DP-30	-	DP-50	10.2	5.1	-	-	-
2432	59	3/4 x 41	60	1/4 x 41 1/2	DP-30	-	DP-50	11.6	5.8	-	-	-
24310	59	3/4 x 49	60	1/4 x 49 1/2	DP-30	-	DP-50	14.3	7.2	-	-	-
2442	59	3/4 x 53	60	1/4 x 53 1/2	DP-30	-	DP-50	15.7	7.9	-	-	-
2446	59	3/4 x 57	60	1/4 x 57 1/2	DP-30	-	DP-50	17.1	8.6	-	-	-
2448	59	3/4 x 59	60	1/4 x 59 1/2	DP-30	-	DP-50	17.8	9.0	-	-	-
2452	59	3/4 x 65	60	1/4 x 65 1/2	DP-30	-	DP-50	19.9	10.0	-	-	-
2456	59	3/4 x 69	60	1/4 x 69 1/2	DP-30	-	DP-50	21.2	10.7	-	-	-
2456c	59	3/4 x 69	60	1/4 x 69 1/2	-	DP-40	-	21.2	-	8.6	-	-
2462	59	3/4 x 77	60	1/4 x 77 1/2	DP-30	-	DP-50	24.0	12.1	-	Yes	-
26210	63	3/4 x 37	64	1/4 x 37 1/2	DP-30	-	DP-50	11.0	5.5	-	-	-
2632	63	3/4 x 41	64	1/4 x 41 1/2	DP-30	-	DP-50	12.5	6.3	-	-	-
26310	63	3/4 x 49	64	1/4 x 49 1/2	DP-30	-	DP-50	15.5	7.8	-	-	-
2642	63	3/4 x 53	64	1/4 x 53 1/2	DP-30	-	DP-50	17.0	8.6	-	-	-
2646	63	3/4 x 57	64	1/4 x 57 1/2	DP-30	-	DP-50	18.5	9.3	-	-	-
2648	63	3/4 x 59	64	1/4 x 59 1/2	DP-30	-	DP-50	19.2	9.7	-	-	-
2652	63	3/4 x 65	64	1/4 x 65 1/2	DP-30	-	DP-50	21.5	10.8	-	-	-
2656	63	3/4 x 69	64	1/4 x 69 1/2	DP-30	-	DP-50	22.9	11.6	-	Yes	-
2656c	63	3/4 x 69	64	1/4 x 69 1/2	-	DP-40	-	22.9	-	9.3	-	-
2662	63	3/4 x 77	64	1/4 x 77 1/2	DP-30	-	DP-50	25.9	13.1	-	Yes	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum twin window width for 20" clear opening width – 49 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Twin Window Units

Date: 9-May-07

Code	Twin Window Unit												
	Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening		
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage	
28210	67 3/4	x 37	68 1/4	x 37 1/2	DP-30	-	DP-50	11.9	6.0	-	-	-	
2832	67 3/4	x 41	68 1/4	x 41 1/2	DP-30	-	DP-50	13.5	6.8	-	-	-	
28310	67 3/4	x 49	68 1/4	x 49 1/2	DP-30	-	DP-50	16.7	8.4	-	-	-	
2842	67 3/4	x 53	68 1/4	x 53 1/2	DP-30	-	DP-50	18.3	9.2	-	-	-	
2846	67 3/4	x 57	68 1/4	x 57 1/2	DP-30	-	DP-50	19.9	10.0	-	-	-	
2848	67 3/4	x 59	68 1/4	x 59 1/2	DP-30	-	DP-50	20.7	10.4	-	-	-	
2852	67 3/4	x 65	68 1/4	x 65 1/2	DP-30	-	DP-50	23.1	11.6	-	Yes	-	
2856	67 3/4	x 69	68 1/4	x 69 1/2	DP-30	-	DP-50	24.7	12.4	-	Yes	-	
2856c	67 3/4	x 69	68 1/4	x 69 1/2	-	DP-40	DP-50	24.7	-	10.0	-	-	
2862	67 3/4	x 77	68 1/4	x 77 1/2	DP-30	-	DP-50	27.9	14.0	-	Yes	-	
210210	71 3/4	x 37	72 1/4	x 37 1/2	DP-30	-	DP-50	12.7	6.4	-	-	-	
21032	71 3/4	x 41	72 1/4	x 41 1/2	DP-30	-	DP-50	14.4	7.2	-	-	-	
210310	71 3/4	x 49	72 1/4	x 49 1/2	DP-30	-	DP-50	17.8	9.0	-	-	-	
21042	71 3/4	x 53	72 1/4	x 53 1/2	DP-30	-	DP-50	19.5	9.8	-	-	-	
21046	71 3/4	x 57	72 1/4	x 57 1/2	DP-30	-	DP-50	21.2	10.7	-	-	-	
21048	71 3/4	x 59	72 1/4	x 59 1/2	DP-30	-	DP-50	22.1	11.1	-	-	-	
21052	71 3/4	x 65	72 1/4	x 65 1/2	DP-30	-	DP-30	24.7	12.4	-	Yes	-	
21056	71 3/4	x 69	72 1/4	x 69 1/2	DP-30	-	DP-30	26.4	13.3	-	Yes	-	
21056c	71 3/4	x 69	72 1/4	x 69 1/2	-	DP-35	-	26.4	-	10.7	-	-	
21062	71 3/4	x 77	72 1/4	x 77 1/2	DP-30	-	DP-30	29.8	15.0	-	Yes	-	
30210	75 3/4	x 37	76 1/4	x 37 1/2	DP-30	-	DP-50	13.5	6.8	-	-	-	
3032	75 3/4	x 41	76 1/4	x 41 1/2	DP-30	-	DP-50	15.3	7.7	-	-	-	
30310	75 3/4	x 49	76 1/4	x 49 1/2	DP-30	-	DP-50	19.0	9.5	-	-	-	
3042	75 3/4	x 53	76 1/4	x 53 1/2	DP-30	-	DP-50	20.8	10.5	-	-	-	
3046	75 3/4	x 57	76 1/4	x 57 1/2	DP-30	-	DP-50	22.6	11.4	-	Yes	-	
3048	75 3/4	x 59	76 1/4	x 59 1/2	DP-30	-	DP-50	23.5	11.8	-	Yes	-	
3052	75 3/4	x 65	76 1/4	x 65 1/2	DP-30	-	DP-30	26.3	13.2	-	Yes	-	
3056	75 3/4	x 69	76 1/4	x 69 1/2	DP-30	-	DP-30	28.1	14.1	-	Yes	-	
3056c	75 3/4	x 69	76 1/4	x 69 1/2	-	DP-35	-	28.1	-	11.4	-	-	
3062	75 3/4	x 77	76 1/4	x 77 1/2	DP-30	-	DP-30	31.7	16.0	-	Yes	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum twin window width for 20" clear opening width – 49 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Twin Window Units

Date: 9-May-07

Code	Twin Window Unit																	
	Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening							
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage						
32210	79	3/4	x	37	80	1/4	x	37	1/2	NT	-	-	14.3	7.2	-	-	-	-
3232	79	3/4	x	41	80	1/4	x	41	1/2	NT	-	-	16.3	8.2	-	-	-	-
32310	79	3/4	x	49	80	1/4	x	49	1/2	NT	-	-	20.1	10.1	-	-	-	-
3242	79	3/4	x	53	80	1/4	x	53	1/2	NT	-	-	22.1	11.1	-	-	-	-
3246	79	3/4	x	57	80	1/4	x	57	1/2	NT	-	-	24.0	12.1	-	Yes	-	-
3248	79	3/4	x	59	80	1/4	x	59	1/2	NT	-	-	25.0	12.5	-	Yes	-	-
3252	79	3/4	x	65	80	1/4	x	65	1/2	NT	-	-	27.9	14.0	-	Yes	-	-
3256	79	3/4	x	69	80	1/4	x	69	1/2	NT	-	-	29.8	15.0	-	Yes	-	-
3256c	79	3/4	x	69	80	1/4	x	69	1/2	-	NT	-	29.8	-	12.1	-	-	-
3262	79	3/4	x	77	80	1/4	x	77	1/2	NT	-	-	33.7	16.9	-	Yes	-	-
34210	83	3/4	x	37	84	1/4	x	37	1/2	NT	-	-	15.1	7.6	-	-	-	-
3432	83	3/4	x	41	84	1/4	x	41	1/2	NT	-	-	17.2	8.6	-	-	-	-
34310	83	3/4	x	49	84	1/4	x	49	1/2	NT	-	-	21.3	10.7	-	-	-	-
3442	83	3/4	x	53	84	1/4	x	53	1/2	NT	-	-	23.3	11.7	-	-	-	-
3446	83	3/4	x	57	84	1/4	x	57	1/2	NT	-	-	25.4	12.7	-	Yes	-	-
3448	83	3/4	x	59	84	1/4	x	59	1/2	NT	-	-	26.4	13.3	-	Yes	-	-
3452	83	3/4	x	65	84	1/4	x	65	1/2	NT	-	-	29.5	14.8	-	Yes	-	-
3456	83	3/4	x	69	84	1/4	x	69	1/2	NT	-	-	31.5	15.8	-	Yes	-	-
3456c	83	3/4	x	69	84	1/4	x	69	1/2	-	NT	-	31.5	-	12.7	-	-	-
3462	83	3/4	x	77	84	1/4	x	77	1/2	NT	-	-	35.6	17.9	-	Yes	-	-
36210	87	3/4	x	37	88	1/4	x	37	1/2	NT	-	-	16.0	8.0	-	-	-	-
3632	87	3/4	x	41	88	1/4	x	41	1/2	NT	-	-	18.1	9.1	-	-	-	-
36310	87	3/4	x	49	88	1/4	x	49	1/2	NT	-	-	22.4	11.3	-	-	-	-
3642	87	3/4	x	53	88	1/4	x	53	1/2	NT	-	-	24.6	12.3	-	-	-	-
3646	87	3/4	x	57	88	1/4	x	57	1/2	NT	-	-	26.8	13.4	-	Yes	-	-
3648	87	3/4	x	59	88	1/4	x	59	1/2	NT	-	-	27.8	14.0	-	Yes	-	-
3652	87	3/4	x	65	88	1/4	x	65	1/2	NT	-	-	31.1	15.6	-	Yes	-	-
3656	87	3/4	x	69	88	1/4	x	69	1/2	NT	-	-	33.2	16.7	-	Yes	-	-
3656c	87	3/4	x	69	88	1/4	x	69	1/2	-	NT	-	33.2	-	13.4	-	-	-
3662	87	3/4	x	77	88	1/4	x	77	1/2	NT	-	-	37.5	18.9	-	Yes	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum twin window width for 20" clear opening width – 49 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Twin Window Units

Date: 9-May-07

Code	Twin Window Unit											
	Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
38210	91	3/4 x 37	92	1/4 x 37 1/2	NT	-	-	16.8	8.4	-	-	-
3832	91	3/4 x 41	92	1/4 x 41 1/2	NT	-	-	19.1	9.5	-	-	-
38310	91	3/4 x 49	92	1/4 x 49 1/2	NT	-	-	23.6	11.8	-	-	-
3842	91	3/4 x 53	92	1/4 x 53 1/2	NT	-	-	25.9	13.0	-	-	-
3846	91	3/4 x 57	92	1/4 x 57 1/2	NT	-	-	28.1	14.1	-	Yes	-
3848	91	3/4 x 59	92	1/4 x 59 1/2	NT	-	-	29.3	14.7	-	Yes	-
3852	91	3/4 x 65	92	1/4 x 65 1/2	NT	-	-	32.7	16.4	-	Yes	-
3856	91	3/4 x 69	92	1/4 x 69 1/2	NT	-	-	34.9	17.5	-	Yes	-
3856c	91	3/4 x 69	92	1/4 x 69 1/2	-	NT	-	34.9	-	14.1	-	Yes
3862	-	-	-	-	-	-	-	-	-	-	-	-
310210	95	3/4 x 37	96	1/4 x 37 1/2	NT	-	-	17.6	8.8	-	-	-
31032	95	3/4 x 41	96	1/4 x 41 1/2	NT	-	-	20.0	10.0	-	-	-
310310	95	3/4 x 49	96	1/4 x 49 1/2	NT	-	-	24.8	12.4	-	-	-
31042	95	3/4 x 53	96	1/4 x 53 1/2	NT	-	-	27.1	13.6	-	-	-
31046	95	3/4 x 57	96	1/4 x 57 1/2	NT	-	-	29.5	14.8	-	Yes	-
31048	95	3/4 x 59	96	1/4 x 59 1/2	NT	-	-	30.7	15.4	-	Yes	-
31052	95	3/4 x 65	96	1/4 x 65 1/2	NT	-	-	34.3	17.2	-	Yes	-
31056	-	-	-	-	-	-	-	-	-	-	-	-
31056c	-	-	-	-	-	-	-	-	-	-	-	-
31062	-	-	-	-	-	-	-	-	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum twin window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Triple Window Units

Date: 9-May-07

Code	Triple Window Unit															
	Dimensions		Rough Opening			DP Rating		Daylight	Ventilation		Clear Opening					
	Width	Height	Width	Height	Equal	Cottage	Equal		Cottage	Equal	Cottage					
18210	65	7/8	x	37	66	3/8	x	37	1/2	DP-35	-	10.4	5.3	-	-	-
1832	65	7/8	x	41	66	3/8	x	41	1/2	DP-35	-	11.8	6.0	-	-	-
18310	65	7/8	x	49	66	3/8	x	49	1/2	DP-35	-	14.6	7.4	-	-	-
1842	65	7/8	x	53	66	3/8	x	53	1/2	DP-35	-	16.0	8.1	-	-	-
1846	65	7/8	x	57	66	3/8	x	57	1/2	DP-35	-	17.4	8.8	-	-	-
1848	65	7/8	x	59	66	3/8	x	59	1/2	DP-35	-	18.1	9.2	-	-	-
1852	65	7/8	x	65	66	3/8	x	65	1/2	DP-35	-	20.2	10.2	-	-	-
1856	65	7/8	x	69	66	3/8	x	69	1/2	DP-35	-	21.6	11.0	-	-	-
1856c	65	7/8	x	69	66	3/8	x	69	1/2	-	NT	21.6	-	8.8	-	-
1862	65	7/8	x	77	66	3/8	x	77	1/2	DP-35	-	24.4	12.4	-	-	-
110210	71	7/8	x	37	72	3/8	x	37	1/2	DP-35	-	11.6	5.9	-	-	-
11032	71	7/8	x	41	72	3/8	x	41	1/2	DP-35	-	13.2	6.7	-	-	-
110310	71	7/8	x	49	72	3/8	x	49	1/2	DP-35	-	16.3	8.3	-	-	-
11042	71	7/8	x	53	72	3/8	x	53	1/2	DP-35	-	17.9	9.1	-	-	-
11046	71	7/8	x	57	72	3/8	x	57	1/2	DP-35	-	19.5	9.8	-	-	-
11048	71	7/8	x	59	72	3/8	x	59	1/2	DP-35	-	20.2	10.2	-	-	-
11052	71	7/8	x	65	72	3/8	x	65	1/2	DP-35	-	22.6	11.4	-	-	-
11056	71	7/8	x	69	72	3/8	x	69	1/2	DP-35	-	24.2	12.2	-	-	-
11056c	71	7/8	x	69	72	3/8	x	69	1/2	-	NT	24.2	-	9.8	-	-
11062	71	7/8	x	77	72	3/8	x	77	1/2	DP-35	-	27.3	13.8	-	-	-
20210	77	7/8	x	37	78	3/8	x	37	1/2	DP-35	-	12.8	6.5	-	-	-
2032	77	7/8	x	41	78	3/8	x	41	1/2	DP-35	-	14.6	7.4	-	-	-
20310	77	7/8	x	49	78	3/8	x	49	1/2	DP-35	-	18.0	9.1	-	-	-
2042	77	7/8	x	53	78	3/8	x	53	1/2	DP-35	-	19.8	10.0	-	-	-
2046	77	7/8	x	57	78	3/8	x	57	1/2	DP-35	-	21.5	10.9	-	-	-
2048	77	7/8	x	59	78	3/8	x	59	1/2	DP-35	-	22.4	11.3	-	-	-
2052	77	7/8	x	65	78	3/8	x	65	1/2	DP-35	-	25.0	12.6	-	-	-
2056	77	7/8	x	69	78	3/8	x	69	1/2	DP-35	-	26.7	13.5	-	-	-
2056c	77	7/8	x	69	78	3/8	x	69	1/2	-	NT	26.7	-	10.9	-	-
2062	77	7/8	x	77	78	3/8	x	77	1/2	DP-35	-	30.2	15.3	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum triple window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Triple Window Units

Date: 9-May-07

Code	Triple Window Unit																
	Dimensions		Rough Opening		DP Rating		Daylight	Ventilation		Clear Opening							
	Width	Height	Width	Height	Equal	Cottage		Equal	Cottage	Equal	Cottage						
22210	83	7/8	x	37	84	3/8	x	37	1/2	DP-35	-	14.1	7.1	-	-	-	-
2232	83	7/8	x	41	84	3/8	x	41	1/2	DP-35	-	16.0	8.1	-	-	-	-
22310	83	7/8	x	49	84	3/8	x	49	1/2	DP-35	-	19.8	10.0	-	-	-	-
2242	83	7/8	x	53	84	3/8	x	53	1/2	DP-35	-	21.7	10.9	-	-	-	-
2246	83	7/8	x	57	84	3/8	x	57	1/2	DP-35	-	23.6	11.9	-	-	-	-
2248	83	7/8	x	59	84	3/8	x	59	1/2	DP-35	-	24.5	12.4	-	-	-	-
2252	83	7/8	x	65	84	3/8	x	65	1/2	DP-35	-	27.4	13.8	-	-	-	-
2256	83	7/8	x	69	84	3/8	x	69	1/2	DP-35	-	29.3	14.8	-	-	-	-
2256c	83	7/8	x	69	84	3/8	x	69	1/2	-	NT	29.3	-	11.9	-	-	-
2262	83	7/8	x	77	84	3/8	x	77	1/2	DP-35	-	33.1	16.7	-	-	-	-
24210	89	7/8	x	37	90	3/8	x	37	1/2	DP-35	-	15.3	7.7	-	-	-	-
2432	89	7/8	x	41	90	3/8	x	41	1/2	DP-35	-	17.4	8.8	-	-	-	-
24310	89	7/8	x	49	90	3/8	x	49	1/2	DP-35	-	21.5	10.8	-	-	-	-
2442	89	7/8	x	53	90	3/8	x	53	1/2	DP-35	-	23.6	11.9	-	-	-	-
2446	89	7/8	x	57	90	3/8	x	57	1/2	DP-35	-	25.7	12.9	-	-	-	-
2448	89	7/8	x	59	90	3/8	x	59	1/2	DP-35	-	26.7	13.5	-	-	-	-
2452	89	7/8	x	65	90	3/8	x	65	1/2	DP-35	-	29.8	15.0	-	-	-	-
2456	89	7/8	x	69	90	3/8	x	69	1/2	DP-35	-	31.9	16.1	-	-	-	-
2456c	89	7/8	x	69	90	3/8	x	69	1/2	-	NT	31.9	-	12.9	-	-	-
2462	89	7/8	x	77	90	3/8	x	77	1/2	DP-35	-	36.0	18.2	-	Yes	-	-
26210	95	7/8	x	37	96	3/8	x	37	1/2	DP-35	-	16.5	8.3	-	-	-	-
2632	95	7/8	x	41	96	3/8	x	41	1/2	DP-35	-	18.8	9.4	-	-	-	-
26310	95	7/8	x	49	96	3/8	x	49	1/2	DP-35	-	23.3	11.7	-	-	-	-
2642	95	7/8	x	53	96	3/8	x	53	1/2	DP-35	-	25.5	12.8	-	-	-	-
2646	95	7/8	x	57	96	3/8	x	57	1/2	DP-35	-	27.7	14.0	-	-	-	-
2648	95	7/8	x	59	96	3/8	x	59	1/2	DP-35	-	28.8	14.5	-	-	-	-
2652	95	7/8	x	65	96	3/8	x	65	1/2	DP-35	-	32.2	16.2	-	-	-	-
2656	95	7/8	x	69	96	3/8	x	69	1/2	DP-35	-	34.4	17.4	-	Yes	-	-
2656c	95	7/8	x	69	96	3/8	x	69	1/2	-	NT	34.4	-	-	-	-	-
2662	95	7/8	x	77	96	3/8	x	77	1/2	DP-35	-	38.9	19.6	-	Yes	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum triple window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Triple Window Units

Date: 9-May-07

Code	Triple Window Unit											
	Dimensions		Rough Opening		DP Rating		Daylight	Ventilation		Clear Opening		
	Width	Height	Width	Height	Equal	Cottage		Equal	Cottage	Equal	Cottage	
28210	101	7/8 x 37	102	3/8 x 37 1/2	DP-35	-	17.8	8.9	-	-	-	
2832	101	7/8 x 41	102	3/8 x 41 1/2	DP-35	-	20.2	10.1	-	-	-	
28310	101	7/8 x 49	102	3/8 x 49 1/2	DP-35	-	25.0	12.6	-	-	-	
2842	101	7/8 x 53	102	3/8 x 53 1/2	DP-35	-	27.4	13.8	-	-	-	
2846	101	7/8 x 57	102	3/8 x 57 1/2	DP-35	-	29.8	15.0	-	-	-	
2848	101	7/8 x 59	102	3/8 x 59 1/2	DP-35	-	31.0	15.6	-	-	-	
2852	101	7/8 x 65	102	3/8 x 65 1/2	DP-35	-	34.6	17.4	-	Yes	-	
2856	101	7/8 x 69	102	3/8 x 69 1/2	DP-35	-	37.0	18.6	-	Yes	-	
2856c	101	7/8 x 69	102	3/8 x 69 1/2	-	NT	37.0	-	15.0	-	-	
2862	101	7/8 x 77	102	3/8 x 77 1/2	DP-35	-	41.8	21.1	-	Yes	-	
210210	107	7/8 x 37	108	3/8 x 37 1/2	NT	-	19.0	9.5	-	-	-	
21032	107	7/8 x 41	108	3/8 x 41 1/2	NT	-	21.6	10.8	-	-	-	
210310	107	7/8 x 49	108	3/8 x 49 1/2	NT	-	26.7	13.4	-	-	-	
21042	107	7/8 x 53	108	3/8 x 53 1/2	NT	-	29.3	14.7	-	-	-	
21046	107	7/8 x 57	108	3/8 x 57 1/2	NT	-	31.9	16.0	-	-	-	
21048	107	7/8 x 59	108	3/8 x 59 1/2	NT	-	33.1	16.7	-	-	-	
21052	107	7/8 x 65	108	3/8 x 65 1/2	NT	-	37.0	18.6	-	Yes	-	
21056	107	7/8 x 69	108	3/8 x 69 1/2	NT	-	39.6	19.9	-	Yes	-	
21056c	107	7/8 x 69	108	3/8 x 69 1/2	-	NT	39.6	-	16.0	-	-	
21062	107	7/8 x 77	108	3/8 x 77 1/2	NT	-	44.7	22.5	-	Yes	-	
30210	113	7/8 x 37	114	3/8 x 37 1/2	NT	NT	20.3	10.2	-	-	-	
3032	113	7/8 x 41	114	3/8 x 41 1/2	NT	NT	23.0	11.5	-	-	-	
30310	113	7/8 x 49	114	3/8 x 49 1/2	NT	NT	28.5	14.3	-	-	-	
3042	113	7/8 x 53	114	3/8 x 53 1/2	NT	NT	31.2	15.7	-	-	-	
3046	113	7/8 x 57	114	3/8 x 57 1/2	NT	NT	33.9	17.1	-	Yes	-	
3048	-	-	-	-	-	-	-	-	-	-	-	
3052	-	-	-	-	-	-	-	-	-	-	-	
3056	-	-	-	-	-	-	-	-	-	-	-	
3056c	-	-	-	-	-	-	-	-	-	-	Yes	
3062	-	-	-	-	-	-	-	-	-	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum triple window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Triple Window Units

Date: 9-May-07

Code	Triple Window Unit											
	Dimensions		Rough Opening		DP Rating		Daylight	Ventilation		Clear Opening		
	Width	Height	Width	Height	Equal	Cottage		Equal	Cottage	Equal	Cottage	
32210	119	7/8 x 37	120	3/8 x 37 1/2	NT	NT	21.5	10.8	-	-	-	
3232	119	7/8 x 41	120	3/8 x 41 1/2	NT	NT	24.4	12.2	-	-	-	
32310	119	7/8 x 49	120	3/8 x 49 1/2	NT	NT	30.2	15.2	-	-	-	
3242	119	7/8 x 53	120	3/8 x 53 1/2	NT	NT	33.1	16.6	-	-	-	
3246	119	7/8 x 57	120	3/8 x 57 1/2	NT	NT	36.0	18.1	-	Yes	-	
3248	-	-	-	-	-	-	-	-	-	-	-	
3252	-	-	-	-	-	-	-	-	-	-	-	
3256	-	-	-	-	-	-	-	-	-	-	-	
3256c	-	-	-	-	-	-	-	-	-	-	Yes	
3262	-	-	-	-	-	-	-	-	-	-	-	
34210	125	7/8 x 37	126	3/8 x 37 1/2	NT	NT	22.7	11.4	-	-	-	
3432	125	7/8 x 41	126	3/8 x 41 1/2	NT	NT	25.8	12.9	-	-	-	
34310	125	7/8 x 49	126	3/8 x 49 1/2	NT	NT	31.9	16.0	-	-	-	
3442	-	-	-	-	-	-	-	-	-	-	-	
3446	-	-	-	-	-	-	-	-	-	-	-	
3448	-	-	-	-	-	-	-	-	-	-	-	
3452	-	-	-	-	-	-	-	-	-	-	-	
3456	-	-	-	-	-	-	-	-	-	-	-	
3456c	-	-	-	-	-	-	-	-	-	-	Yes	
3462	-	-	-	-	-	-	-	-	-	-	-	
36210	131	7/8 x 37	132	3/8 x 37 1/2	NT	NT	24.0	12.0	-	-	-	
3632	131	7/8 x 41	132	3/8 x 41 1/2	NT	NT	27.2	13.6	-	-	-	
36310	131	7/8 x 49	132	3/8 x 49 1/2	NT	NT	33.7	16.9	-	-	-	
3642	-	-	-	-	-	-	-	-	-	-	-	
3646	-	-	-	-	-	-	-	-	-	-	-	
3648	-	-	-	-	-	-	-	-	-	-	-	
3652	-	-	-	-	-	-	-	-	-	-	-	
3656	-	-	-	-	-	-	-	-	-	-	-	
3656c	-	-	-	-	-	-	-	-	-	-	Yes	
3662	-	-	-	-	-	-	-	-	-	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum triple window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Triple Window Units

Date: 9-May-07

Code	Triple Window Unit												
	Dimensions		Rough Opening				DP Rating		Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Equal	Cottage		Equal	Cottage		
38210	137 7/8	x 37	138 3/8	x 37 1/2	NT	NT	25.2	12.6	-	-	-	-	
3832	137 7/8	x 41	138 3/8	x 41 1/2	NT	NT	28.6	14.3	-	-	-	-	
38310	-	-	-	-	-	-	-	-	-	-	-	-	
3842	-	-	-	-	-	-	-	-	-	-	-	-	
3846	-	-	-	-	-	-	-	-	-	-	-	-	
3848	-	-	-	-	-	-	-	-	-	-	-	-	
3852	-	-	-	-	-	-	-	-	-	-	-	-	
3856	-	-	-	-	-	-	-	-	-	-	-	-	
3856c	-	-	-	-	-	-	-	-	-	-	-	-	
3862	-	-	-	-	-	-	-	-	-	-	-	-	
310210	143 7/8	x 37	144 3/8	x 37 1/2	NT	NT	26.4	13.2	-	-	-	-	
31032	143 7/8	x 41	144 3/8	x 41 1/2	NT	NT	30.0	15.0	-	-	-	-	
310310	-	-	-	-	-	-	-	-	-	-	-	-	
31042	-	-	-	-	-	-	-	-	-	-	-	-	
31046	-	-	-	-	-	-	-	-	-	-	-	-	
31048	-	-	-	-	-	-	-	-	-	-	-	-	
31052	-	-	-	-	-	-	-	-	-	-	-	-	
31056	-	-	-	-	-	-	-	-	-	-	-	-	
31056c	-	-	-	-	-	-	-	-	-	-	-	-	
31062	-	-	-	-	-	-	-	-	-	-	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum triple window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Ventilation, Daylight and Design Pressure

Single Window Units

Window				Width 18 to 28								
Height	Call Out	Unit Dimension		18	110	20	22	24	26	28		
	210	37	Rough Opening	21 5/8	23 5/8	25 5/8	27 5/8	29 5/8	31 5/8	33 5/8		
			37 1/2	22 1/8	24 1/8	26 1/8	28 1/8	30 1/8	32 1/8	34 1/8		
Height	210	37	37 1/2	Ventilation	1.8	2.0	2.2	2.4	2.6	2.8	3.0	
				Daylight	3.5	3.9	4.3	4.7	5.1	5.5	5.9	
					Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
	32	41	41 1/2		Ventilation	2.0	2.2	2.5	2.7	2.9	3.1	3.4
					Daylight	3.9	4.4	4.9	5.3	5.8	6.3	6.7
					Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50
	310	49	49 1/2		Ventilation	2.5	2.8	3.0	3.3	3.6	3.9	4.2
					Daylight	4.9	5.4	6.0	6.6	7.2	7.8	8.3
				Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
42	53	53 1/2		Ventilation	2.7	3.0	3.3	3.6	4.0	4.3	4.6	
				Daylight	5.3	6.0	6.6	7.2	7.9	8.5	9.1	
				Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
46	57	57 1/2		Ventilation	2.9	3.3	3.6	4.0	4.3	4.7	5.0	
				Daylight	5.8	6.5	7.2	7.9	8.6	9.2	9.9	
				Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
48	59	59 1/2		Ventilation	3.1	3.4	3.8	4.1	4.5	4.8	5.2	
				Daylight	6.0	6.7	7.5	8.2	8.9	9.6	10.3	
				Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
52	65	65 1/2		Ventilation	3.4	3.8	4.2	4.6	5.0	5.4	5.8	
				Daylight	6.7	7.5	8.3	9.1	9.9	10.7	11.5	
				Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
56	69	69 1/2		Ventilation	3.7	4.1	4.5	4.9	5.4	5.8	6.2	
				Daylight	7.2	8.1	8.9	9.8	10.6	11.5	12.3	
				Design Presssure	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	
56 Cottage	69	69 1/2		Ventilation	2.9	3.3	3.6	4.0	4.3	4.7	5.0	
				Daylight	7.2	8.1	8.9	9.8	10.7	11.5	12.4	
				Design Presssure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
62	77	77 1/2		Ventilation	4.1	4.6	5.1	5.6	6.1	6.5	7.0	
				Daylight	8.1	9.1	10.1	11.0	12.0	13.0	13.9	
				Design Presssure	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	DP-35/DP-50	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

Note: Daylight and Ventilation calculations are given in square foot of area

44" x 77"	DP-35	37 5/8" x 59"	DP-50
33 7/8" x 65"	DP-50	37 7/8" x 65"	DP-50

Seven D Industries, L.P.
Series 5700 Single Hung

33 7/8" x 77" DP-50

37 5/8" x 71" Cottage DP-50

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Ventilation, Daylight and Design Pressure

Single Window Units

Window		Width 210 to 310									
Height	Call Out	Unit Dimension		210	30	32	34	36	38	310	
	210	37	Rough Opening	35 5/8	37 5/8	39 5/8	41 5/8	43 5/8	45 5/8	47 5/8	
			36 1/8	38 1/8	40 1/8	42 1/8	44 1/8	46 1/8	48 1/8		
210	37	37 1/2	Ventilation	3.2	3.4	3.6	3.8	4.0	4.2	4.4	
			Daylight	6.3	6.8	7.2	7.6	8.0	8.4	8.8	
	32	41	41 1/2	Design Presssure	DP-50	DP-50	DP-35/DP-50	DP-35/DP-50	DP-35	NT	NT
				Ventilation	3.6	3.8	4.1	4.3	4.5	4.8	5.0
	310	49	49 1/2	Daylight	7.2	7.7	8.1	8.6	9.1	9.5	10.0
				Design Presssure	DP-50	DP-50	DP-35/DP-50	DP-35/DP-50	DP-35	NT	NT
	42	53	53 1/2	Ventilation	4.5	4.8	5.1	5.3	5.6	5.9	6.2
				Daylight	8.9	9.5	10.1	10.6	11.2	11.8	12.4
	46	57	57 1/2	Design Presssure	DP-50	DP-50	DP-35/DP-50	DP-35/DP-50	DP-35	NT	NT
				Ventilation	4.9	5.2	5.5	5.9	6.2	6.5	6.8
48	59	59 1/2	Daylight	9.8	10.4	11.0	11.7	12.3	12.9	13.6	
			Design Presssure	DP-50	DP-50	DP-35/DP-50	DP-35/DP-50	DP-35	NT	NT	
52	65	65 1/2	Ventilation	5.3	5.7	6.0	6.4	6.7	7.1	7.4	
			Daylight	10.6	11.3	12.0	12.7	13.4	14.1	14.8	
56	69	69 1/2	Design Presssure	DP-50	DP-50	DP-35/DP-50	DP-35/DP-50	DP-35	NT	NT	
			Ventilation	5.6	5.9	6.3	6.6	7.0	7.3	7.7	
56 Cottage	69	69 1/2	Daylight	11.0	11.8	12.5	13.2	13.9	14.6	15.3	
			Design Presssure	DP-50	DP-50	DP-35/DP-50	DP-35/DP-50	DP-35	NT	NT	
62	77	77 1/2	Ventilation	6.2	6.6	7.0	7.4	7.8	8.2	8.6	
			Daylight	12.3	13.1	13.9	14.7	15.5	16.3	17.1	
62	77	77 1/2	Design Presssure	DP-50	DP-50	DP-35	DP-35	DP-35	NT	NT	
			Ventilation	6.6	7.1	7.5	7.9	8.3	8.8	9.2	
62	77	77 1/2	Daylight	13.2	14.0	14.9	15.8	16.6	17.5	18.3	
			Design Presssure	DP-35/DP-50	DP-35/DP-50	DP-35	DP-35	DP-35	NT	NT	
62	77	77 1/2	Ventilation	5.3	5.7	6.0	6.4	6.7	7.1	7.4	
			Daylight	13.2	14.1	14.9	15.8	16.6	17.5	18.4	
62	77	77 1/2	Design Presssure	DP-50	DP-50	NT	NT	NT	NT	NT	
			Ventilation	7.5	8.0	8.5	9.0	9.4	9.9	10.4	
62	77	77 1/2	Daylight	14.9	15.9	16.8	17.8	18.8	19.7	20.7	
			Design Presssure	DP-35	DP-35	DP-35	DP-35	DP-35	NT	NT	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

44" x 77"	DP-35	37 5/8" x 59"	DP-50
33 7/8" x 65"	DP-50	37 7/8" x 65"	DP-50

Note: Daylight and Ventilation calculations are given in square foot of area

Seven D Industries, L.P.
Series 5700 Single Hung

33 7/8" x 77" DP-50

37 5/8" x 71" Cottage DP-50

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Ventilation, Daylight and Design Pressure

Twin Window Units

Window				Width 18 to 28							
Height	Call Out	Unit Dimension		18	110	20	22	24	26	28	
	210	37	Rough Opening	43 3/4	47 3/4	51 3/4	55 3/4	59 3/4	63 3/4	67 3/4	
			37 1/2	44 1/4	48 1/4	52 1/4	56 1/4	60 1/4	64 1/4	68 1/4	
Height	210	37	37 1/2	Ventilation	3.5	3.9	4.3	4.7	5.1	5.5	6.0
				Daylight	6.9	7.7	8.6	9.4	10.2	11.0	11.9
	32	41	41 1/2	Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50
				Ventilation	4.0	4.4	4.9	5.4	5.8	6.3	6.8
	310	49	49 1/2	Daylight	7.9	8.8	9.7	10.7	11.6	12.5	13.5
				Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50
	42	53	53 1/2	Ventilation	4.9	5.5	6.1	6.7	7.2	7.8	8.4
				Daylight	9.7	10.9	12.0	13.2	14.3	15.5	16.7
	46	57	57 1/2	Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50
				Ventilation	5.4	6.0	6.7	7.3	7.9	8.6	9.2
48	59	59 1/2	Daylight	10.7	11.9	13.2	14.5	15.7	17.0	18.3	
			Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
52	65	65 1/2	Ventilation	5.9	6.5	7.3	7.9	8.6	9.3	10.0	
			Daylight	11.6	13.0	14.3	15.7	17.1	18.5	19.9	
56	69	69 1/2	Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
			Ventilation	6.1	6.8	7.5	8.3	9.0	9.7	10.4	
56 Cottage	69	69 1/2	Daylight	12.1	13.5	14.9	16.4	17.8	19.2	20.7	
			Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
62	77	77 1/2	Ventilation	6.8	7.6	8.4	9.2	10.0	10.8	11.6	
			Daylight	13.5	15.1	16.7	18.3	19.9	21.5	23.1	
62 Cottage	77	77 1/2	Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
			Ventilation	7.3	8.1	9.0	9.9	10.7	11.6	12.4	
62 Cottage	77	77 1/2	Daylight	14.4	16.1	17.8	19.5	21.2	22.9	24.7	
			Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
62 Cottage	77	77 1/2	Ventilation	5.9	6.5	7.3	7.9	8.6	9.3	10.0	
			Daylight	14.5	16.2	17.9	19.6	21.3	23.0	24.7	
62 Cottage	77	77 1/2	Design Presssure	DP-40	DP-40	DP-40	DP-40	DP-40	DP-40	DP-40	
			Ventilation	8.2	9.2	10.2	11.2	12.1	13.1	14.0	
62 Cottage	77	77 1/2	Daylight	16.3	18.2	20.1	22.1	24.0	25.9	27.9	
			Design Presssure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

76" x 77"	DP-30	68" x 77"	DP-50
76" x 59"	DP-50	75 3/4" x 71" Cottage	DP-35

Note: Daylight and Ventilation calculations are given in square foot of area

Seven D Industries, L.P.
Series 5700 Single Hung

68" x 65" DP-50

68 1/4" x 71" Cottage DP-40

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Ventilation, Daylight and Design Pressure

Twin Window Units

Window				Width 210 to 310							
Height	Call Out	Unit Dimension		210	30	32	34	36	38	310	
	210	37	Rough Opening	71 3/4	75 3/4	79 3/4	83 3/4	87 3/4	91 3/4	95 3/4	
			37 1/2	72 1/4	76 1/4	80 1/4	84 1/4	88 1/4	92 1/4	96 1/4	
Height	210	37	37 1/2	Ventilation	6.4	6.8	7.2	7.6	8.0	8.4	8.8
				Daylight	12.7	13.5	14.3	15.1	16.0	16.8	17.6
	32	41	41 1/2	Design Presssure	DP-30/DP-50	DP-30/DP-50	NT	NT	NT	NT	NT
				Ventilation	7.2	7.7	8.2	8.6	9.1	9.5	10.0
	32	41	41 1/2	Daylight	14.4	15.3	16.3	17.2	18.1	19.1	20.0
				Design Presssure	DP-30/DP-50	DP-30/DP-50	NT	NT	NT	NT	NT
	310	49	49 1/2	Ventilation	9.0	9.5	10.1	10.7	11.3	11.8	12.4
				Daylight	17.8	19.0	20.1	21.3	22.4	23.6	24.8
	42	53	53 1/2	Design Presssure	DP-30/DP-50	DP-30/DP-50	NT	NT	NT	NT	NT
				Ventilation	9.8	10.5	11.1	11.7	12.3	13.0	13.6
42	53	53 1/2	Daylight	19.5	20.8	22.1	23.3	24.6	25.9	27.1	
			Design Presssure	DP-30/DP-50	DP-30/DP-50	NT	NT	NT	NT	NT	
46	57	57 1/2	Ventilation	10.7	11.4	12.1	12.7	13.4	14.1	14.8	
			Daylight	21.2	22.6	24.0	25.4	26.8	28.1	29.5	
46	57	57 1/2	Design Presssure	DP-30/DP-50	DP-30/DP-50	NT	NT	NT	NT	NT	
			Ventilation	11.1	11.8	12.5	13.3	14.0	14.7	15.4	
48	59	59 1/2	Daylight	22.1	23.5	25.0	26.4	27.8	29.3	30.7	
			Design Presssure	DP-30/DP-50	DP-30/DP-50	NT	NT	NT	NT	NT	
52	65	65 1/2	Ventilation	12.4	13.2	14.0	14.8	15.6	16.4	17.2	
			Daylight	24.7	26.3	27.9	29.5	31.1	32.7	34.3	
52	65	65 1/2	Design Presssure	DP-30	DP-30	NT	NT	NT	NT	NT	
			Ventilation	13.3	14.1	15.0	15.8	16.7	17.5	-	
56	69	69 1/2	Daylight	26.4	28.1	29.8	31.5	33.2	34.9	-	
			Design Presssure	DP-30	DP-30	NT	NT	NT	NT	-	
56	69	69 1/2	Ventilation	10.7	11.4	12.1	12.7	13.4	14.1	-	
			Daylight	26.4	28.2	29.9	31.6	33.3	35.0	-	
56	69	69 1/2	Design Presssure	DP-35	DP-35	NT	NT	NT	NT	-	
			Ventilation	15.0	16.0	16.9	17.9	18.9	-	-	
62	77	77 1/2	Daylight	29.8	31.7	33.7	35.6	37.5	-	-	
			Design Presssure	DP-30	DP-30	NT	NT	NT	-	-	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

76" x 77" DP-30 68" x 77" DP-50
 76" x 59" DP-50 75 3/4" x 71" Cottage DP-35

Note: Daylight and Ventilation calculations are given in square foot of area

Seven D Industries, L.P.
Series 5700 Single Hung

68" x 65" DP-50

68 1/4" x 71" Cottage DP-40

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Ventilation, Daylight and Design Pressure

Triple Window Units

Window				Width 18 to 28							
Height	Call Out	Unit Dimension		18	110	20	22	24	26	28	
	210	37	Rough Opening	65 7/8	71 7/8	77 7/8	83 7/8	89 7/8	95 7/8	101 7/8	
			37 1/2	66 3/8	72 3/8	78 3/8	84 3/8	90 3/8	96 3/8	102 3/8	
Height	210	37	37 1/2	Ventilation	5.3	5.9	6.5	7.1	7.7	8.3	8.9
				Daylight	10.4	11.6	12.8	14.1	15.3	16.5	17.8
	32	41	41 1/2	Ventilation	6.0	6.7	7.4	8.1	8.8	9.4	10.1
				Daylight	11.8	13.2	14.6	16.0	17.4	18.8	20.2
	310	49	49 1/2	Ventilation	7.4	8.3	9.1	10.0	10.8	11.7	12.6
				Daylight	14.6	16.3	18.0	19.8	21.5	23.3	25.0
	42	53	53 1/2	Ventilation	8.1	9.1	10.0	10.9	11.9	12.8	13.8
				Daylight	16.0	17.9	19.8	21.7	23.6	25.5	27.4
	46	57	57 1/2	Ventilation	8.8	9.8	10.9	11.9	12.9	14.0	15.0
				Daylight	17.4	19.5	21.5	23.6	25.7	27.7	29.8
48	59	59 1/2	Ventilation	9.2	10.2	11.3	12.4	13.5	14.5	15.6	
			Daylight	18.1	20.2	22.4	24.5	26.7	28.8	31.0	
52	65	65 1/2	Ventilation	10.2	11.4	12.6	13.8	15.0	16.2	17.4	
			Daylight	20.2	22.6	25.0	27.4	29.8	32.2	34.6	
56	69	69 1/2	Ventilation	11.0	12.2	13.5	14.8	16.1	17.4	18.6	
			Daylight	21.6	24.2	26.7	29.3	31.9	34.4	37.0	
56 Cottage	69	69 1/2	Ventilation	8.8	9.8	10.9	11.9	12.9	14.0	15.0	
			Daylight	21.7	24.3	26.8	29.4	32.0	34.5	37.1	
62	77	77 1/2	Ventilation	12.4	13.8	15.3	16.7	18.2	19.6	21.1	
			Daylight	24.4	27.3	30.2	33.1	36.0	38.9	41.8	
			Design Presssure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

102 5/8" x 65"

DP-35

102 5/8" x 77"

DP-35

Note: Daylight and Ventilation calculations are given in square foot of area

Seven D Industries, L.P.
Series 5700 Single Hung

Seven D Industries, L.P.

Series 5700 Single Hung

Product Specifications - Ventilation, Daylight and Design Pressure

Triple Window Units

Window		Width 210 to 310									
Height	Call Out	Unit Dimension		210	30	32	34	36	38	310	
	210	37	Rough Opening	107 7/8	113 7/8	119 7/8	125 7/8	131 7/8	137 7/8	143 7/8	
			37 1/2	108 3/8	114 3/8	120 3/8	126 3/8	132 3/8	138 3/8	144 3/8	
210	37	37 1/2	Ventilation	9.5	10.2	10.8	11.4	12.0	12.6	13.2	
			Daylight	19.0	20.3	21.5	22.7	24.0	25.2	26.4	
	32	41	41 1/2	Design Presssure	NT	NT	NT	NT	NT	NT	
				Ventilation	10.8	11.5	12.2	12.9	13.6	14.3	15.0
	310	49	49 1/2	Daylight	21.6	23.0	24.4	25.8	27.2	28.6	30.0
				Design Presssure	NT	NT	NT	NT	NT	NT	NT
	42	53	53 1/2	Ventilation	13.4	14.3	15.2	16.0	16.9	-	-
				Daylight	26.7	28.5	30.2	31.9	33.7	-	-
	46	57	57 1/2	Design Presssure	NT	NT	NT	NT	NT	-	-
				Ventilation	14.7	15.7	16.6	-	-	-	-
48	59	59 1/2	Daylight	29.3	31.2	33.1	-	-	-	-	
			Design Presssure	NT	NT	NT	-	-	-	-	
52	65	65 1/2	Ventilation	16.0	17.1	18.1	-	-	-	-	
			Daylight	31.9	33.9	36.0	-	-	-	-	
56	69	69 1/2	Design Presssure	NT	NT	NT	-	-	-	-	
			Ventilation	16.7	-	-	-	-	-	-	
56 Cottage	69	69 1/2	Daylight	33.1	-	-	-	-	-	-	
			Design Presssure	NT	-	-	-	-	-	-	
62	77	77 1/2	Ventilation	18.6	-	-	-	-	-	-	
			Daylight	37.0	-	-	-	-	-	-	
62	77	77 1/2	Design Presssure	NT	-	-	-	-	-	-	
			Ventilation	19.9	-	-	-	-	-	-	
62	77	77 1/2	Daylight	39.6	-	-	-	-	-	-	
			Design Presssure	NT	-	-	-	-	-	-	
62	77	77 1/2	Ventilation	16.0	-	-	-	-	-	-	
			Daylight	39.7	-	-	-	-	-	-	
62	77	77 1/2	Design Presssure	NT	-	-	-	-	-	-	
			Ventilation	22.5	-	-	-	-	-	-	
62	77	77 1/2	Daylight	44.7	-	-	-	-	-	-	
			Design Presssure	NT	-	-	-	-	-	-	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

102 5/8" x 65"

DP-35

102 5/8" x 77"

DP-35

Note: Daylight and Ventilation calculations are given in square foot of area

Seven D Industries, L.P.
Series 5700 Single Hung

Seven D Industries, L.P.

Series 5700 Single Hung

Screen Dimensions

Code	Unit Dimensions		Screen Dimensions		Code	Unit Dimensions		Screen Dimensions	
	Width	Height	Width	Height		Width	Height	Width	Height
18210	21 5/8	x 37	17 9/16	x 17 7/16	26210	31 5/8	x 37	27 9/16	x 17 7/16
1832	21 5/8	x 41	17 9/16	x 19 7/16	2632	31 5/8	x 41	27 9/16	x 19 7/16
18310	21 5/8	x 49	17 9/16	x 23 7/16	26310	31 5/8	x 49	27 9/16	x 23 7/16
1842	21 5/8	x 53	17 9/16	x 25 7/16	2642	31 5/8	x 53	27 9/16	x 25 7/16
1846	21 5/8	x 57	17 9/16	x 27 7/16	2646	31 5/8	x 57	27 9/16	x 27 7/16
1848	21 5/8	x 59	17 9/16	x 28 7/16	2648	31 5/8	x 59	27 9/16	x 28 7/16
1852	21 5/8	x 65	17 9/16	x 31 7/16	2652	31 5/8	x 65	27 9/16	x 31 7/16
1856	21 5/8	x 69	17 9/16	x 33 7/16	2656	31 5/8	x 69	27 9/16	x 33 7/16
1856c	21 5/8	x 69	17 9/16	x 39 7/16	2656c	31 5/8	x 69	27 9/16	x 39 7/16
1862	21 5/8	x 77	17 9/16	x 37 7/16	2662	31 5/8	x 77	27 9/16	x 37 7/16
110210	23 5/8	x 37	19 9/16	x 17 7/16	28210	33 5/8	x 37	29 9/16	x 17 7/16
11032	23 5/8	x 41	19 9/16	x 19 7/16	2832	33 5/8	x 41	29 9/16	x 19 7/16
110310	23 5/8	x 49	19 9/16	x 23 7/16	28310	33 5/8	x 49	29 9/16	x 23 7/16
11042	23 5/8	x 53	19 9/16	x 25 7/16	2842	33 5/8	x 53	29 9/16	x 25 7/16
11046	23 5/8	x 57	19 9/16	x 27 7/16	2846	33 5/8	x 57	29 9/16	x 27 7/16
11048	23 5/8	x 59	19 9/16	x 28 7/16	2848	33 5/8	x 59	29 9/16	x 28 7/16
11052	23 5/8	x 65	19 9/16	x 31 7/16	2852	33 5/8	x 65	29 9/16	x 31 7/16
11056	23 5/8	x 69	19 9/16	x 33 7/16	2856	33 5/8	x 69	29 9/16	x 33 7/16
11056c	23 5/8	x 69	19 9/16	x 39 7/16	2856c	33 5/8	x 69	29 9/16	x 39 7/16
11062	23 5/8	x 77	19 9/16	x 37 7/16	2862	33 5/8	x 77	29 9/16	x 37 7/16
20210	25 5/8	x 37	21 9/16	x 17 7/16	30210	37 5/8	x 37	33 9/16	x 17 7/16
2032	25 5/8	x 41	21 9/16	x 19 7/16	3032	37 5/8	x 41	33 9/16	x 19 7/16
20310	25 5/8	x 49	21 9/16	x 23 7/16	30310	37 5/8	x 49	33 9/16	x 23 7/16
2042	25 5/8	x 53	21 9/16	x 25 7/16	3042	37 5/8	x 53	33 9/16	x 25 7/16
2046	25 5/8	x 57	21 9/16	x 27 7/16	3046	37 5/8	x 57	33 9/16	x 27 7/16
2048	25 5/8	x 59	21 9/16	x 28 7/16	3048	37 5/8	x 59	33 9/16	x 28 7/16
2052	25 5/8	x 65	21 9/16	x 31 7/16	3052	37 5/8	x 65	33 9/16	x 31 7/16
2056	25 5/8	x 69	21 9/16	x 33 7/16	3056	37 5/8	x 69	33 9/16	x 33 7/16
2056c	25 5/8	x 69	21 9/16	x 39 7/16	3056c	37 5/8	x 69	33 9/16	x 39 7/16
2062	25 5/8	x 77	21 9/16	x 37 7/16	3062	37 5/8	x 77	33 9/16	x 37 7/16
22120	27 5/8	x 35	23 9/16	x 16 7/16	32210	39 5/8	x 37	35 9/16	x 17 7/16
2232	27 5/8	x 41	23 9/16	x 19 7/16	3232	39 5/8	x 41	35 9/16	x 19 7/16
22310	27 5/8	x 49	23 9/16	x 23 7/16	32310	39 5/8	x 49	35 9/16	x 23 7/16
2242	27 5/8	x 53	23 9/16	x 25 7/16	3242	39 5/8	x 53	35 9/16	x 25 7/16
2246	27 5/8	x 57	23 9/16	x 27 7/16	3246	39 5/8	x 57	35 9/16	x 27 7/16
2248	27 5/8	x 59	23 9/16	x 28 7/16	3248	39 5/8	x 59	35 9/16	x 28 7/16
2252	27 5/8	x 65	23 9/16	x 31 7/16	3252	39 5/8	x 65	35 9/16	x 31 7/16
2256	27 5/8	x 69	23 9/16	x 33 7/16	3256	39 5/8	x 69	35 9/16	x 33 7/16
2256c	27 5/8	x 69	23 9/16	x 39 7/16	3256c	39 5/8	x 69	35 9/16	x 39 7/16
2262	27 5/8	x 77	23 9/16	x 37 7/16	3262	39 5/8	x 77	35 9/16	x 37 7/16
24210	29 5/8	x 37	25 9/16	x 17 7/16	34210	41 5/8	x 37	37 9/16	x 17 7/16
2432	29 5/8	x 41	25 9/16	x 19 7/16	3432	41 5/8	x 41	37 9/16	x 19 7/16
24310	29 5/8	x 49	25 9/16	x 23 7/16	34310	41 5/8	x 49	37 9/16	x 23 7/16
2442	29 5/8	x 53	25 9/16	x 25 7/16	3442	41 5/8	x 53	37 9/16	x 25 7/16
2446	29 5/8	x 57	25 9/16	x 27 7/16	3446	41 5/8	x 57	37 9/16	x 27 7/16
2448	29 5/8	x 59	25 9/16	x 28 7/16	3448	41 5/8	x 59	37 9/16	x 28 7/16
2452	29 5/8	x 65	25 9/16	x 31 7/16	3452	41 5/8	x 65	37 9/16	x 31 7/16
2456	29 5/8	x 69	25 9/16	x 33 7/16	3456	41 5/8	x 69	37 9/16	x 33 7/16
2456c	29 5/8	x 69	25 9/16	x 39 7/16	3456c	41 5/8	x 69	37 9/16	x 39 7/16
2462	29 5/8	x 77	25 9/16	x 37 7/16	3462	41 5/8	x 77	37 9/16	x 37 7/16

Seven D Industries, L.P.

Series 5700 Single Hung

Screen Dimensions

Code	Unit Dimensions			Screen Dimensions					
	Width		Height	Width		Height			
36310	43	5/8	x	49	39	9/16	x	23	7/16
3632	43	5/8	x	41	39	9/16	x	19	7/16
36210	43	5/8	x	37	39	9/16	x	17	7/16
3642	43	5/8	x	53	39	9/16	x	25	7/16
3642	43	5/8	x	53	39	9/16	x	25	7/16
3648	43	5/8	x	59	39	9/16	x	28	7/16
3652	43	5/8	x	65	39	9/16	x	31	7/16
3656	43	5/8	x	69	39	9/16	x	33	7/16
3656c	43	5/8	x	69	39	9/16	x	37	7/16
3662	43	5/8	x	77	39	9/16	x	37	7/16
38210	45	5/8	x	37	41	9/16	x	17	7/16
3832	45	5/8	x	41	41	9/16	x	19	7/16
38310	45	5/8	x	49	41	9/16	x	23	7/16
3842	45	5/8	x	53	41	9/16	x	25	7/16
3846	45	5/8	x	57	41	9/16	x	27	7/16
3848	45	5/8	x	59	41	9/16	x	28	7/16
3852	45	5/8	x	65	41	9/16	x	31	7/16
3856	45	5/8	x	69	41	9/16	x	33	7/16
3856c	45	5/8	x	69	41	9/16	x	39	7/16
3862	45	5/8	x	77	41	9/16	x	37	7/16
310210	47	5/8	x	37	43	9/16	x	17	7/16
31032	47	5/8	x	41	43	9/16	x	19	7/16
310310	47	5/8	x	49	43	9/16	x	23	7/16
31042	47	5/8	x	53	43	9/16	x	25	7/16
31046	47	5/8	x	57	43	9/16	x	27	7/16
31048	47	5/8	x	59	43	9/16	x	28	7/16
31052	47	5/8	x	65	43	9/16	x	31	7/16
31056	47	5/8	x	69	43	9/16	x	33	7/16
31056c	47	5/8	x	69	43	9/16	x	39	7/16
31062	47	5/8	x	77	43	9/16	x	37	7/16

Code	Unit Dimensions		Screen Dimensions	
	Width	Height	Width	Height

Seven D Industries, L.P.
Series 5700 Single Hung

Thermal Performance Specifications

SSB Glazing

Glass Type	U-Value	SHGC	VT	w/ Grid	
				SHGC	VT
3/4" IG -Clear/Air/Clear	.48	.63	.65	.56	.58
3/4" IG – Clear/90% Argon/Low-E	.31	.39	.55	.35	.49

DSB Glazing

Glass Type	U-Value	SHGC	VT	w/ Grid	
				SHGC	VT
3/4" IG -Clear/Air/Clear	.48	.61	.65	.55	.58
3/4" IG – Clear/90% Argon/Low-E	.31	.38	.54	.34	.49

Notes: Actual window dimensions have not effect on the Thermal Performance Rating, as the test criteria is based on a per square foot unit.

Seven D Industries, Series 5700 Single Hung windows utilizing Low-E Glass with Argon Fill, meet all requirements for Energy Star compliance.

10/19/2006

Seven D Industries, L.P. **Series 5700 Single Hung**

Ventilation and Daylight Calculation

Single Window Units

Window Width: 36
Window Height: 55.5

Ventilation Area: 5.250 sq ft
Daylight Area: 10.423 sq ft

Clear Opening Width: 31 1/2
Clear Opening Height: 24