

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Single Window Units

Date: 09-May-07

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
1830	19 5/8	x 35 3/4	20 1/8	x 36 1/4	DP-50	-	-	2.7	1.5	-	-	-
1832	19 5/8	x 37 3/4	20 1/8	x 38 1/4	DP-50	-	-	2.9	1.6	-	-	-
1838	19 5/8	x 43 3/4	20 1/8	x 44 1/4	DP-50	-	-	3.5	1.9	-	-	-
1840	19 5/8	x 47 3/4	20 1/8	x 48 1/4	DP-50	-	-	3.9	2.1	-	-	-
1842	19 5/8	x 49 3/4	20 1/8	x 50 1/4	DP-50	-	-	4.1	2.2	-	-	-
1846	19 5/8	x 53 3/4	20 1/8	x 54 1/4	DP-50	-	-	4.5	2.4	-	-	-
1850	19 5/8	x 59 3/4	20 1/8	x 60 1/4	DP-50	-	-	5.0	2.7	-	-	-
1852	19 5/8	x 61 3/4	20 1/8	x 62 1/4	DP-50	-	-	5.2	2.9	-	-	-
1856	19 5/8	x 65 3/4	20 1/8	x 66 1/4	DP-25	-	DP-50	5.6	3.1	-	-	-
1860	19 5/8	x 71 3/4	20 1/8	x 72 1/4	DP-25	-	DP-50	6.2	3.4	-	-	-
1860c	19 5/8	x 71 3/4	20 1/8	x 72 1/4	-	NT	-	6.2	-	2.7	-	-
1860o	19 5/8	x 71 3/4	20 1/8	x 72 1/4	-	NT	-	6.2	-	2.7	-	-
1862	19 5/8	x 73 3/4	20 1/8	x 74 1/4	DP-25	-	DP-50	6.4	3.5	-	-	-
11030	21 5/8	x 35 3/4	22 1/8	x 36 1/4	DP-50	-	-	3.1	1.7	-	-	-
11032	21 5/8	x 37 3/4	22 1/8	x 38 1/4	DP-50	-	-	3.3	1.8	-	-	-
11038	21 5/8	x 43 3/4	22 1/8	x 44 1/4	DP-50	-	-	4.0	2.2	-	-	-
11040	21 5/8	x 47 3/4	22 1/8	x 48 1/4	DP-50	-	-	4.4	2.4	-	-	-
11042	21 5/8	x 49 3/4	22 1/8	x 50 1/4	DP-50	-	-	4.7	2.5	-	-	-
11046	21 5/8	x 53 3/4	22 1/8	x 54 1/4	DP-50	-	-	5.1	2.8	-	-	-
11050	21 5/8	x 59 3/4	22 1/8	x 60 1/4	DP-50	-	-	5.8	3.1	-	-	-
11052	21 5/8	x 61 3/4	22 1/8	x 62 1/4	DP-50	-	-	6.0	3.2	-	-	-
11056	21 5/8	x 65 3/4	22 1/8	x 66 1/4	DP-25	-	DP-50	6.4	3.5	-	-	-
11060	21 5/8	x 71 3/4	22 1/8	x 72 1/4	DP-25	-	DP-50	7.1	3.8	-	-	-
11060c	21 5/8	x 71 3/4	22 1/8	x 72 1/4	-	NT	-	7.1	-	3.1	-	-
11060o	21 5/8	x 71 3/4	22 1/8	x 72 1/4	-	NT	-	7.1	-	3.1	-	-
11062	21 5/8	x 73 3/4	22 1/8	x 74 1/4	DP-25	-	DP-50	7.3	3.9	-	-	-
2030	23 5/8	x 35 3/4	24 1/8	x 36 1/4	DP-50	-	-	3.5	1.9	-	-	-
2032	23 5/8	x 37 3/4	24 1/8	x 38 1/4	DP-50	-	-	3.8	2.0	-	-	-
2038	23 5/8	x 43 3/4	24 1/8	x 44 1/4	DP-50	-	-	4.5	2.4	-	-	-
2040	23 5/8	x 47 3/4	24 1/8	x 48 1/4	DP-50	-	-	5.0	2.7	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Single Window Units

Date: 09-May-07

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
2042	23 5/8	x 49 3/4	24 1/8	x 50 1/4	DP-50	-	-	5.2	2.8	-	-	-
2046	23 5/8	x 53 3/4	24 1/8	x 54 1/4	DP-50	-	-	5.7	3.1	-	-	-
2050	23 5/8	x 59 3/4	24 1/8	x 60 1/4	DP-50	-	-	6.5	3.5	-	-	-
2052	23 5/8	x 61 3/4	24 1/8	x 62 1/4	DP-50	-	-	6.7	3.6	-	-	-
2056	23 5/8	x 65 3/4	24 1/8	x 66 1/4	DP-25	-	DP-50	7.2	3.9	-	-	-
2060	23 5/8	x 71 3/4	24 1/8	x 72 1/4	DP-25	-	DP-50	8.0	4.3	-	-	-
2060c	23 5/8	x 71 3/4	24 1/8	x 72 1/4	-	NT	-	8.0	-	3.5	-	-
2060o	23 5/8	x 71 3/4	24 1/8	x 72 1/4	-	NT	-	8.0	-	3.5	-	-
2062	23 5/8	x 73 3/4	24 1/8	x 74 1/4	DP-25	-	DP-50	8.2	4.4	-	-	-
2230	25 5/8	x 35 3/4	26 1/8	x 36 1/4	DP-50	-	-	3.9	2.1	-	-	-
2232	25 5/8	x 37 3/4	26 1/8	x 38 1/4	DP-50	-	-	4.2	2.2	-	-	-
2238	25 5/8	x 43 3/4	26 1/8	x 44 1/4	DP-50	-	-	5.0	2.7	-	-	-
2240	25 5/8	x 47 3/4	26 1/8	x 48 1/4	DP-50	-	-	5.6	3.0	-	-	-
2242	25 5/8	x 49 3/4	26 1/8	x 50 1/4	DP-50	-	-	5.8	3.1	-	-	-
2246	25 5/8	x 53 3/4	26 1/8	x 54 1/4	DP-50	-	-	6.4	3.4	-	-	-
2250	25 5/8	x 59 3/4	26 1/8	x 60 1/4	DP-50	-	-	7.2	3.8	-	-	-
2252	25 5/8	x 61 3/4	26 1/8	x 62 1/4	DP-50	-	-	7.5	4.0	-	-	-
2256	25 5/8	x 65 3/4	26 1/8	x 66 1/4	DP-25	-	DP-50	8.0	4.3	-	-	-
2260	25 5/8	x 71 3/4	26 1/8	x 72 1/4	DP-25	-	DP-50	8.9	4.7	-	-	-
2260c	25 5/8	x 71 3/4	26 1/8	x 72 1/4	-	NT	-	8.9	-	3.8	-	-
2260o	25 5/8	x 71 3/4	26 1/8	x 72 1/4	-	NT	-	8.9	-	3.8	-	-
2262	25 5/8	x 73 3/4	26 1/8	x 74 1/4	DP-25	-	DP-50	9.1	4.9	-	-	-
2430	27 5/8	x 35 3/4	28 1/8	x 36 1/4	DP-50	-	-	4.3	2.3	-	-	-
2432	27 5/8	x 37 3/4	28 1/8	x 38 1/4	DP-50	-	-	4.6	2.4	-	-	-
2438	27 5/8	x 43 3/4	28 1/8	x 44 1/4	DP-50	-	-	5.5	2.9	-	-	-
2440	27 5/8	x 47 3/4	28 1/8	x 48 1/4	DP-50	-	-	6.1	3.2	-	-	-
2442	27 5/8	x 49 3/4	28 1/8	x 50 1/4	DP-50	-	-	6.4	3.4	-	-	-
2446	27 5/8	x 53 3/4	28 1/8	x 54 1/4	DP-50	-	-	7.0	3.7	-	-	-
2450	27 5/8	x 59 3/4	28 1/8	x 60 1/4	DP-50	-	-	7.9	4.2	-	-	-
2452	27 5/8	x 61 3/4	28 1/8	x 62 1/4	DP-50	-	-	8.2	4.4	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Single Window Units

Date: 09-May-07

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
2456	27 5/8	x 65 3/4	28 1/8	x 66 1/4	DP-25	-	DP-50	8.8	4.7	-	-	-
2460	27 5/8	x 71 3/4	28 1/8	x 72 1/4	DP-25	-	DP-50	9.8	5.2	-	-	-
2460c	27 5/8	x 71 3/4	28 1/8	x 72 1/4	-	NT	-	9.8	-	4.2	-	-
2460o	27 5/8	x 71 3/4	28 1/8	x 72 1/4	-	NT	-	9.8	-	4.2	-	-
2462	27 5/8	x 73 3/4	28 1/8	x 74 1/4	DP-25	-	DP-50	10.1	5.3	-	-	-
2630	29 5/8	x 35 3/4	30 1/8	x 36 1/4	DP-50	-	-	4.7	2.5	-	-	-
2632	29 5/8	x 37 3/4	30 1/8	x 38 1/4	DP-50	-	-	5.0	2.6	-	-	-
2638	29 5/8	x 43 3/4	30 1/8	x 44 1/4	DP-50	-	-	6.0	3.2	-	-	-
2640	29 5/8	x 47 3/4	30 1/8	x 48 1/4	DP-50	-	-	6.7	3.5	-	-	-
2642	29 5/8	x 49 3/4	30 1/8	x 50 1/4	DP-50	-	-	7.0	3.7	-	-	-
2646	29 5/8	x 53 3/4	30 1/8	x 54 1/4	DP-50	-	-	7.7	4.0	-	-	-
2650	29 5/8	x 59 3/4	30 1/8	x 60 1/4	DP-50	-	-	8.7	4.6	-	-	-
2652	29 5/8	x 61 3/4	30 1/8	x 62 1/4	DP-50	-	-	9.0	4.7	-	-	-
2656	29 5/8	x 65 3/4	30 1/8	x 66 1/4	DP-25	-	DP-50	9.7	5.1	-	-	-
2660	29 5/8	x 71 3/4	30 1/8	x 72 1/4	DP-25	-	DP-50	10.7	5.6	-	-	-
2660c	29 5/8	x 71 3/4	30 1/8	x 72 1/4	-	NT	-	10.7	-	4.6	-	-
2660o	29 5/8	x 71 3/4	30 1/8	x 72 1/4	-	NT	-	10.7	-	4.6	-	-
2662	29 5/8	x 73 3/4	30 1/8	x 74 1/4	DP-25	-	DP-50	11.0	5.8	-	Yes	-
2830	31 5/8	x 35 3/4	32 1/8	x 36 1/4	DP-50	-	-	5.1	2.7	-	-	-
2832	31 5/8	x 37 3/4	32 1/8	x 38 1/4	DP-50	-	-	5.4	2.9	-	-	-
2838	31 5/8	x 43 3/4	32 1/8	x 44 1/4	DP-50	-	-	6.5	3.4	-	-	-
2840	31 5/8	x 47 3/4	32 1/8	x 48 1/4	DP-50	-	-	7.2	3.8	-	-	-
2842	31 5/8	x 49 3/4	32 1/8	x 50 1/4	DP-50	-	-	7.6	4.0	-	-	-
2846	31 5/8	x 53 3/4	32 1/8	x 54 1/4	DP-50	-	-	8.3	4.4	-	-	-
2850	31 5/8	x 59 3/4	32 1/8	x 60 1/4	DP-50	-	-	9.4	4.9	-	-	-
2852	31 5/8	x 61 3/4	32 1/8	x 62 1/4	DP-50	-	-	9.7	5.1	-	-	-
2856	31 5/8	x 65 3/4	32 1/8	x 66 1/4	DP-25	-	DP-50	10.5	5.5	-	-	-
2860	31 5/8	x 71 3/4	32 1/8	x 72 1/4	DP-25	-	DP-50	11.5	6.1	-	Yes	-
2860c	31 5/8	x 71 3/4	32 1/8	x 72 1/4	-	NT	-	11.5	-	4.9	-	-
2860o	31 5/8	x 71 3/4	32 1/8	x 72 1/4	-	NT	-	11.5	-	4.9	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Single Window Units

Date: 09-May-07

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
2862	31 5/8	x 73 3/4	32 1/8	x 74 1/4	DP-25	-	DP-50	11.9	6.2	-	Yes	-
21030	33 5/8	x 35 3/4	34 1/8	x 36 1/4	DP-50	-	-	5.5	2.9	-	-	-
21032	33 5/8	x 37 3/4	34 1/8	x 38 1/4	DP-50	-	-	5.9	3.1	-	-	-
21038	33 5/8	x 43 3/4	34 1/8	x 44 1/4	DP-50	-	-	7.0	3.7	-	-	-
21040	33 5/8	x 47 3/4	34 1/8	x 48 1/4	DP-50	-	-	7.8	4.1	-	-	-
21042	33 5/8	x 49 3/4	34 1/8	x 50 1/4	DP-50	-	-	8.2	4.3	-	-	-
21046	33 5/8	x 53 3/4	34 1/8	x 54 1/4	DP-50	-	-	9.0	4.7	-	-	-
21050	33 5/8	x 59 3/4	34 1/8	x 60 1/4	DP-50	-	-	10.1	5.3	-	-	-
21052	33 5/8	x 61 3/4	34 1/8	x 62 1/4	DP-50	-	-	10.5	5.5	-	-	-
21056	33 5/8	x 65 3/4	34 1/8	x 66 1/4	DP-25	-	DP-50	11.3	5.9	-	Yes	-
21060	33 5/8	x 71 3/4	34 1/8	x 72 1/4	DP-25	-	DP-50	12.4	6.5	-	Yes	-
21060c	33 5/8	x 71 3/4	34 1/8	x 72 1/4	-	NT	-	12.4	-	5.3	-	-
21060o	33 5/8	x 71 3/4	34 1/8	x 72 1/4	-	NT	-	12.4	-	5.3	-	-
21062	33 5/8	x 73 3/4	34 1/8	x 74 1/4	DP-25	-	DP-50	12.8	6.7	-	Yes	-
3030	35 5/8	x 35 3/4	36 1/8	x 36 1/4	DP-50	-	-	5.9	3.1	-	-	-
3032	35 5/8	x 37 3/4	36 1/8	x 38 1/4	DP-50	-	-	6.3	3.3	-	-	-
3038	35 5/8	x 43 3/4	36 1/8	x 44 1/4	DP-50	-	-	7.5	3.9	-	-	-
3040	35 5/8	x 47 3/4	36 1/8	x 48 1/4	DP-50	-	-	8.4	4.4	-	-	-
3042	35 5/8	x 49 3/4	36 1/8	x 50 1/4	DP-50	-	-	8.8	4.6	-	-	-
3046	35 5/8	x 53 3/4	36 1/8	x 54 1/4	DP-50	-	-	9.6	5.0	-	-	-
3050	35 5/8	x 59 3/4	36 1/8	x 60 1/4	DP-50	-	-	10.8	5.7	-	-	-
3052	35 5/8	x 61 3/4	36 1/8	x 62 1/4	DP-25	-	DP-50	11.3	5.9	-	Yes	-
3056	35 5/8	x 65 3/4	36 1/8	x 66 1/4	DP-25	-	-	12.1	6.3	-	Yes	-
3060	35 5/8	x 71 3/4	36 1/8	x 72 1/4	DP-25	-	-	13.3	6.9	-	Yes	-
3060c	35 5/8	x 71 3/4	36 1/8	x 72 1/4	-	NT	-	13.3	-	5.7	-	Yes
3060o	35 5/8	x 71 3/4	36 1/8	x 72 1/4	-	NT	-	13.3	-	5.7	-	Yes
3062	35 5/8	x 73 3/4	36 1/8	x 74 1/4	DP-25	-	-	13.7	7.2	-	Yes	-
3230	37 5/8	x 35 3/4	38 1/8	x 36 1/4	DP-50	-	-	6.3	3.3	-	-	-
3232	37 5/8	x 37 3/4	38 1/8	x 38 1/4	DP-50	-	-	6.7	3.5	-	-	-
3238	37 5/8	x 43 3/4	38 1/8	x 44 1/4	DP-50	-	-	8.0	4.2	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Single Window Units

Date: 09-May-07

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
3240	37 5/8	x 47 3/4	38 1/8	x 48 1/4	DP-50	-	-	8.9	4.6	-	-	-
3242	37 5/8	x 49 3/4	38 1/8	x 50 1/4	DP-50	-	-	9.4	4.9	-	-	-
3246	37 5/8	x 53 3/4	38 1/8	x 54 1/4	DP-50	-	-	10.2	5.3	-	-	-
3250	37 5/8	x 59 3/4	38 1/8	x 60 1/4	DP-25	-	DP-50	11.6	6.0	-	Yes	-
3252	37 5/8	x 61 3/4	38 1/8	x 62 1/4	DP-25	-	DP-50	12.0	6.2	-	Yes	-
3256	37 5/8	x 65 3/4	38 1/8	x 66 1/4	DP-25	-	-	12.9	6.7	-	Yes	-
3260	37 5/8	x 71 3/4	38 1/8	x 72 1/4	DP-25	-	-	14.2	7.4	-	Yes	-
3260c	37 5/8	x 71 3/4	38 1/8	x 72 1/4	-	NT	-	14.2	-	6.0	-	Yes
3260o	37 5/8	x 71 3/4	38 1/8	x 72 1/4	-	NT	-	14.2	-	6.0	-	Yes
3262	37 5/8	x 73 3/4	38 1/8	x 74 1/4	DP-25	-	-	14.7	7.6	-	Yes	-
3430	39 5/8	x 35 3/4	40 1/8	x 36 1/4	DP-25	-	DP-50	6.6	3.5	-	-	-
3432	39 5/8	x 37 3/4	40 1/8	x 38 1/4	DP-25	-	DP-50	7.1	3.7	-	-	-
3438	39 5/8	x 43 3/4	40 1/8	x 44 1/4	DP-25	-	DP-50	8.5	4.4	-	-	-
3440	39 5/8	x 47 3/4	40 1/8	x 48 1/4	DP-25	-	DP-50	9.5	4.9	-	-	-
3442	39 5/8	x 49 3/4	40 1/8	x 50 1/4	DP-25	-	DP-50	9.9	5.2	-	-	-
3446	39 5/8	x 53 3/4	40 1/8	x 54 1/4	DP-25	-	DP-50	10.9	5.6	-	-	-
3450	39 5/8	x 59 3/4	40 1/8	x 60 1/4	DP-25	-	-	12.3	6.4	-	Yes	-
3452	39 5/8	x 61 3/4	40 1/8	x 62 1/4	DP-25	-	-	12.8	6.6	-	Yes	-
3456	39 5/8	x 65 3/4	40 1/8	x 66 1/4	DP-25	-	-	13.7	7.1	-	Yes	-
3460	39 5/8	x 71 3/4	40 1/8	x 72 1/4	DP-25	-	-	15.1	7.8	-	Yes	-
3460c	39 5/8	x 71 3/4	40 1/8	x 72 1/4	-	NT	-	15.1	-	6.4	-	Yes
3460o	39 5/8	x 71 3/4	40 1/8	x 72 1/4	-	NT	-	15.1	-	6.4	-	Yes
3462	39 5/8	x 73 3/4	40 1/8	x 74 1/4	DP-25	-	-	15.6	8.1	-	Yes	-
3630	41 5/8	x 35 3/4	42 1/8	x 36 1/4	DP-25	-	DP-50	7.0	3.6	-	-	-
3632	41 5/8	x 37 3/4	42 1/8	x 38 1/4	DP-25	-	DP-50	7.5	3.9	-	-	-
3638	41 5/8	x 43 3/4	42 1/8	x 44 1/4	DP-25	-	DP-50	9.0	4.7	-	-	-
3640	41 5/8	x 47 3/4	42 1/8	x 48 1/4	DP-25	-	DP-50	10.0	5.2	-	-	-
3642	41 5/8	x 49 3/4	42 1/8	x 50 1/4	DP-25	-	DP-50	10.5	5.5	-	-	-
3646	41 5/8	x 53 3/4	42 1/8	x 54 1/4	DP-25	-	DP-50	11.5	6.0	-	-	-
3650	41 5/8	x 59 3/4	42 1/8	x 60 1/4	DP-25	-	-	13.0	6.7	-	Yes	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Single Window Units

Date: 09-May-07

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
3652	41 5/8	x 61 3/4	42 1/8	x 62 1/4	DP-25	-	-	13.5	7.0	-	Yes	-
3656	41 5/8	x 65 3/4	42 1/8	x 66 1/4	DP-25	-	-	14.5	7.5	-	Yes	-
3660	41 5/8	x 71 3/4	42 1/8	x 72 1/4	DP-25	-	-	16.0	8.3	-	Yes	-
3660c	41 5/8	x 71 3/4	42 1/8	x 72 1/4	-	NT	-	16.0	-	6.7	-	Yes
3660o	41 5/8	x 71 3/4	42 1/8	x 72 1/4	-	NT	-	16.0	-	6.7	-	Yes
3662	41 5/8	x 73 3/4	42 1/8	x 74 1/4	DP-25	-	-	16.5	8.5	-	Yes	-
3830	43 5/8	x 35 3/4	44 1/8	x 36 1/4	DP-25	-	-	7.4	3.8	-	-	-
3832	43 5/8	x 37 3/4	44 1/8	x 38 1/4	DP-25	-	-	8.0	4.1	-	-	-
3838	43 5/8	x 43 3/4	44 1/8	x 44 1/4	DP-25	-	-	9.5	4.9	-	-	-
3840	43 5/8	x 47 3/4	44 1/8	x 48 1/4	DP-25	-	-	10.6	5.5	-	-	-
3842	43 5/8	x 49 3/4	44 1/8	x 50 1/4	DP-25	-	-	11.1	5.7	-	-	-
3846	43 5/8	x 53 3/4	44 1/8	x 54 1/4	DP-25	-	-	12.2	6.3	-	-	-
3850	43 5/8	x 59 3/4	44 1/8	x 60 1/4	DP-25	-	-	13.7	7.1	-	Yes	-
3852	43 5/8	x 61 3/4	44 1/8	x 62 1/4	DP-25	-	-	14.3	7.4	-	Yes	-
3856	43 5/8	x 65 3/4	44 1/8	x 66 1/4	DP-25	-	-	15.3	7.9	-	Yes	-
3860	43 5/8	x 71 3/4	44 1/8	x 72 1/4	DP-25	-	-	16.9	8.7	-	Yes	-
3860c	43 5/8	x 71 3/4	44 1/8	x 72 1/4	-	NT	-	16.9	-	7.1	-	Yes
3860o	43 5/8	x 71 3/4	44 1/8	x 72 1/4	-	NT	-	16.9	-	7.1	-	Yes
3862	43 5/8	x 73 3/4	44 1/8	x 74 1/4	DP-25	-	-	17.4	9.0	-	Yes	-
31030	45 5/8	x 35 3/4	46 1/8	x 36 1/4	NT	-	-	7.8	4.0	-	-	-
31032	45 5/8	x 37 3/4	46 1/8	x 38 1/4	NT	-	-	8.4	4.3	-	-	-
31038	45 5/8	x 43 3/4	46 1/8	x 44 1/4	NT	-	-	10.0	5.2	-	-	-
31040	45 5/8	x 47 3/4	46 1/8	x 48 1/4	NT	-	-	11.1	5.8	-	-	-
31042	45 5/8	x 49 3/4	46 1/8	x 50 1/4	NT	-	-	11.7	6.0	-	-	-
31046	45 5/8	x 53 3/4	46 1/8	x 54 1/4	NT	-	-	12.8	6.6	-	-	-
31050	45 5/8	x 59 3/4	46 1/8	x 60 1/4	NT	-	-	14.5	7.5	-	Yes	-
31052	45 5/8	x 61 3/4	46 1/8	x 62 1/4	NT	-	-	15.0	7.8	-	Yes	-
31056	45 5/8	x 65 3/4	46 1/8	x 66 1/4	NT	-	-	16.1	8.3	-	Yes	-
31060	45 5/8	x 71 3/4	46 1/8	x 72 1/4	NT	-	-	17.8	9.2	-	Yes	-
31060c	45 5/8	x 71 3/4	46 1/8	x 72 1/4	-	NT	-	17.8	-	7.5	-	Yes

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Single Window Units

Date: 09-May-07

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
31060o	45 5/8	x 71 3/4	46 1/8	x 72 1/4	-	NT	-	17.8	-	7.5	-	Yes
31062	45 5/8	x 73 3/4	46 1/8	x 74 1/4	NT	-	-	18.3	9.5	-	Yes	-
4030	47 5/8	x 35 3/4	48 1/8	x 36 1/4	NT	-	-	8.2	4.2	-	-	-
4032	47 5/8	x 37 3/4	48 1/8	x 38 1/4	NT	-	-	8.8	4.5	-	-	-
4038	47 5/8	x 43 3/4	48 1/8	x 44 1/4	NT	-	-	10.5	5.4	-	-	-
4040	47 5/8	x 47 3/4	48 1/8	x 48 1/4	NT	-	-	11.7	6.0	-	-	-
4042	47 5/8	x 49 3/4	48 1/8	x 50 1/4	NT	-	-	12.3	6.3	-	-	-
4046	47 5/8	x 53 3/4	48 1/8	x 54 1/4	NT	-	-	13.4	6.9	-	-	-
4050	47 5/8	x 59 3/4	48 1/8	x 60 1/4	NT	-	-	15.2	7.8	-	Yes	-
4052	47 5/8	x 61 3/4	48 1/8	x 62 1/4	NT	-	-	15.8	8.1	-	Yes	-
4056	47 5/8	x 65 3/4	48 1/8	x 66 1/4	NT	-	-	16.9	8.7	-	Yes	-
4060	47 5/8	x 71 3/4	48 1/8	x 72 1/4	NT	-	-	18.7	9.6	-	Yes	-
4060c	47 5/8	x 71 3/4	48 1/8	x 72 1/4	-	NT	-	18.7	-	7.8	-	Yes
4060o	47 5/8	x 71 3/4	48 1/8	x 72 1/4	-	NT	-	18.7	-	7.8	-	Yes
4062	47 5/8	x 73 3/4	48 1/8	x 74 1/4	NT	-	-	19.3	9.9	-	Yes	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Twin Window Units

Date: 09-May-07

Code	Twin Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
1830	39 3/4	x 35 3/4	40 1/4	x 36 1/4	DP-30	-	DP-50	5.4	3.0	-	-	-
1832	39 3/4	x 37 3/4	40 1/4	x 38 1/4	DP-30	-	DP-50	5.8	3.2	-	-	-
1838	39 3/4	x 43 3/4	40 1/4	x 44 1/4	DP-30	-	DP-50	7.0	3.8	-	-	-
1840	39 3/4	x 47 3/4	40 1/4	x 48 1/4	DP-30	-	DP-50	7.8	4.2	-	-	-
1842	39 3/4	x 49 3/4	40 1/4	x 50 1/4	DP-30	-	DP-50	8.1	4.4	-	-	-
1846	39 3/4	x 53 3/4	40 1/4	x 54 1/4	DP-30	-	DP-50	8.9	4.9	-	-	-
1850	39 3/4	x 59 3/4	40 1/4	x 60 1/4	DP-30	-	DP-50	10.1	5.5	-	-	-
1852	39 3/4	x 61 3/4	40 1/4	x 62 1/4	DP-30	-	DP-50	10.5	5.7	-	-	-
1856	39 3/4	x 65 3/4	40 1/4	x 66 1/4	DP-30	-	DP-50	11.2	6.1	-	-	-
1860	39 3/4	x 71 3/4	40 1/4	x 72 1/4	DP-30	-	DP-50	12.4	6.8	-	-	-
1860c	39 3/4	x 71 3/4	40 1/4	x 72 1/4	-	NT	-	12.4	-	5.5	-	-
1860o	39 3/4	x 71 3/4	40 1/4	x 72 1/4	-	NT	-	12.4	-	5.5	-	-
1862	39 3/4	x 73 3/4	40 1/4	x 74 1/4	DP-30	-	DP-50	12.8	7.0	-	-	-
11030	43 3/4	x 35 3/4	44 1/4	x 36 1/4	DP-30	-	DP-50	6.2	3.4	-	-	-
11032	43 3/4	x 37 3/4	44 1/4	x 38 1/4	DP-30	-	DP-50	6.7	3.6	-	-	-
11038	43 3/4	x 43 3/4	44 1/4	x 44 1/4	DP-30	-	DP-50	8.0	4.3	-	-	-
11040	43 3/4	x 47 3/4	44 1/4	x 48 1/4	DP-30	-	DP-50	8.9	4.8	-	-	-
11042	43 3/4	x 49 3/4	44 1/4	x 50 1/4	DP-30	-	DP-50	9.3	5.0	-	-	-
11046	43 3/4	x 53 3/4	44 1/4	x 54 1/4	DP-30	-	DP-50	10.2	5.5	-	-	-
11050	43 3/4	x 59 3/4	44 1/4	x 60 1/4	DP-30	-	DP-50	11.5	6.2	-	-	-
11052	43 3/4	x 61 3/4	44 1/4	x 62 1/4	DP-30	-	DP-50	12.0	6.5	-	-	-
11056	43 3/4	x 65 3/4	44 1/4	x 66 1/4	DP-30	-	DP-50	12.8	6.9	-	-	-
11060	43 3/4	x 71 3/4	44 1/4	x 72 1/4	DP-30	-	DP-50	14.2	7.6	-	-	-
11060c	43 3/4	x 71 3/4	44 1/4	x 72 1/4	-	NT	-	14.2	-	6.2	-	-
11060o	43 3/4	x 71 3/4	44 1/4	x 72 1/4	-	NT	-	14.2	-	6.2	-	-
11062	43 3/4	x 73 3/4	44 1/4	x 74 1/4	DP-30	-	DP-50	14.6	7.9	-	-	-
2030	47 3/4	x 35 3/4	48 1/4	x 36 1/4	DP-30	-	DP-50	7.0	3.8	-	-	-
2032	47 3/4	x 37 3/4	48 1/4	x 38 1/4	DP-30	-	DP-50	7.5	4.0	-	-	-
2038	47 3/4	x 43 3/4	48 1/4	x 44 1/4	DP-30	-	DP-50	9.0	4.8	-	-	-
2040	47 3/4	x 47 3/4	48 1/4	x 48 1/4	DP-30	-	DP-50	10.0	5.4	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Twin Window Units

Date: 09-May-07

Code	Twin Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
2042	47 3/4	x 49 3/4	48 1/4	x 50 1/4	DP-30	-	DP-50	10.5	5.6	-	-	-
2046	47 3/4	x 53 3/4	48 1/4	x 54 1/4	DP-30	-	DP-50	11.5	6.1	-	-	-
2050	47 3/4	x 59 3/4	48 1/4	x 60 1/4	DP-30	-	DP-50	13.0	6.9	-	-	-
2052	47 3/4	x 61 3/4	48 1/4	x 62 1/4	DP-30	-	DP-50	13.5	7.2	-	-	-
2056	47 3/4	x 65 3/4	48 1/4	x 66 1/4	DP-30	-	DP-50	14.5	7.7	-	-	-
2060	47 3/4	x 71 3/4	48 1/4	x 72 1/4	DP-30	-	DP-50	16.0	8.5	-	-	-
2060c	47 3/4	x 71 3/4	48 1/4	x 72 1/4	-	NT	-	16.0	-	6.9	-	-
2060o	47 3/4	x 71 3/4	48 1/4	x 72 1/4	-	NT	-	16.0	-	6.9	-	-
2062	47 3/4	x 73 3/4	48 1/4	x 74 1/4	DP-30	-	DP-50	16.4	8.8	-	-	-
2230	51 3/4	x 35 3/4	52 1/4	x 36 1/4	DP-30	-	DP-50	7.8	4.2	-	-	-
2232	51 3/4	x 37 3/4	52 1/4	x 38 1/4	DP-30	-	DP-50	8.4	4.4	-	-	-
2238	51 3/4	x 43 3/4	52 1/4	x 44 1/4	DP-30	-	DP-50	10.0	5.3	-	-	-
2240	51 3/4	x 47 3/4	52 1/4	x 48 1/4	DP-30	-	DP-50	11.1	5.9	-	-	-
2242	51 3/4	x 49 3/4	52 1/4	x 50 1/4	DP-30	-	DP-50	11.7	6.2	-	-	-
2246	51 3/4	x 53 3/4	52 1/4	x 54 1/4	DP-30	-	DP-50	12.8	6.8	-	-	-
2250	51 3/4	x 59 3/4	52 1/4	x 60 1/4	DP-30	-	DP-50	14.4	7.7	-	-	-
2252	51 3/4	x 61 3/4	52 1/4	x 62 1/4	DP-30	-	DP-50	15.0	8.0	-	-	-
2256	51 3/4	x 65 3/4	52 1/4	x 66 1/4	DP-30	-	DP-50	16.1	8.6	-	-	-
2260	51 3/4	x 71 3/4	52 1/4	x 72 1/4	DP-30	-	DP-50	17.7	9.4	-	-	-
2260c	51 3/4	x 71 3/4	52 1/4	x 72 1/4	-	NT	-	17.7	-	7.7	-	-
2260o	51 3/4	x 71 3/4	52 1/4	x 72 1/4	-	NT	-	17.7	-	7.7	-	-
2262	51 3/4	x 73 3/4	52 1/4	x 74 1/4	DP-30	-	DP-50	18.3	9.7	-	-	-
2430	55 3/4	x 35 3/4	56 1/4	x 36 1/4	DP-30	-	DP-50	8.6	4.5	-	-	-
2432	55 3/4	x 37 3/4	56 1/4	x 38 1/4	DP-30	-	DP-50	9.2	4.9	-	-	-
2438	55 3/4	x 43 3/4	56 1/4	x 44 1/4	DP-30	-	DP-50	11.0	5.8	-	-	-
2440	55 3/4	x 47 3/4	56 1/4	x 48 1/4	DP-30	-	DP-50	12.2	6.5	-	-	-
2442	55 3/4	x 49 3/4	56 1/4	x 50 1/4	DP-30	-	DP-50	12.8	6.8	-	-	-
2446	55 3/4	x 53 3/4	56 1/4	x 54 1/4	DP-30	-	DP-50	14.1	7.4	-	-	-
2450	55 3/4	x 59 3/4	56 1/4	x 60 1/4	DP-30	-	DP-50	15.9	8.4	-	-	-
2452	55 3/4	x 61 3/4	56 1/4	x 62 1/4	DP-30	-	DP-50	16.5	8.7	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Twin Window Units

Date: 09-May-07

Code	Twin Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
2456	55 3/4	x 65 3/4	56 1/4	x 66 1/4	DP-30	-	DP-50	17.7	9.4	-	-	-
2460	55 3/4	x 71 3/4	56 1/4	x 72 1/4	DP-30	-	DP-50	19.5	10.3	-	-	-
2460c	55 3/4	x 71 3/4	56 1/4	x 72 1/4		NT		19.5	-	8.4	-	-
2460o	55 3/4	x 71 3/4	56 1/4	x 72 1/4		NT		19.5	-	8.4	-	-
2462	55 3/4	x 73 3/4	56 1/4	x 74 1/4	DP-30	-	DP-50	20.1	10.6	-	-	-
2630	59 3/4	x 35 3/4	60 1/4	x 36 1/4	DP-30	-	DP-50	9.4	4.9	-	-	-
2632	59 3/4	x 37 3/4	60 1/4	x 38 1/4	DP-30	-	DP-50	10.0	5.3	-	-	-
2638	59 3/4	x 43 3/4	60 1/4	x 44 1/4	DP-30	-	DP-50	12.0	6.3	-	-	-
2640	59 3/4	x 47 3/4	60 1/4	x 48 1/4	DP-30	-	DP-50	13.3	7.0	-	-	-
2642	59 3/4	x 49 3/4	60 1/4	x 50 1/4	DP-30	-	DP-50	14.0	7.4	-	-	-
2646	59 3/4	x 53 3/4	60 1/4	x 54 1/4	DP-30	-	DP-50	15.3	8.1	-	-	-
2650	59 3/4	x 59 3/4	60 1/4	x 60 1/4	DP-30	-	DP-50	17.3	9.1	-	-	-
2652	59 3/4	x 61 3/4	60 1/4	x 62 1/4	DP-30	-	DP-50	18.0	9.5	-	-	-
2656	59 3/4	x 65 3/4	60 1/4	x 66 1/4	DP-30	-	DP-50	19.3	10.2	-	-	-
2660	59 3/4	x 71 3/4	60 1/4	x 72 1/4	DP-30	-	DP-50	21.3	11.2	-	-	-
2660c	59 3/4	x 71 3/4	60 1/4	x 72 1/4	-	NT	-	21.3	-	9.1	-	-
2660o	59 3/4	x 71 3/4	60 1/4	x 72 1/4	-	NT	-	21.3	-	9.1	-	-
2662	59 3/4	x 73 3/4	60 1/4	x 74 1/4	DP-30	-	DP-50	22.0	11.6	-	Yes	-
2830	63 3/4	x 35 3/4	64 1/4	x 36 1/4	DP-30	-	DP-50	10.2	5.3	-	-	-
2832	63 3/4	x 37 3/4	64 1/4	x 38 1/4	DP-30	-	DP-50	10.9	5.7	-	-	-
2838	63 3/4	x 43 3/4	64 1/4	x 44 1/4	DP-30	-	DP-50	13.0	6.8	-	-	-
2840	63 3/4	x 47 3/4	64 1/4	x 48 1/4	DP-30	-	DP-50	14.5	7.6	-	-	-
2842	63 3/4	x 49 3/4	64 1/4	x 50 1/4	DP-30	-	DP-50	15.2	8.0	-	-	-
2846	63 3/4	x 53 3/4	64 1/4	x 54 1/4	DP-30	-	DP-50	16.6	8.7	-	-	-
2850	63 3/4	x 59 3/4	64 1/4	x 60 1/4	DP-30	-	DP-50	18.8	9.9	-	-	-
2852	63 3/4	x 61 3/4	64 1/4	x 62 1/4	DP-30	-	DP-50	19.5	10.2	-	-	-
2856	63 3/4	x 65 3/4	64 1/4	x 66 1/4	DP-30	-	DP-50	20.9	11.0	-	-	-
2860	63 3/4	x 71 3/4	64 1/4	x 72 1/4	DP-30	-	DP-50	23.1	12.1	-	Yes	-
2860c	63 3/4	x 71 3/4	64 1/4	x 72 1/4	-	NT	-	23.1	-	9.8	-	-
2860o	63 3/4	x 71 3/4	64 1/4	x 72 1/4	-	NT	-	23.1	-	9.8	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Twin Window Units

Date: 09-May-07

Code	Twin Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
2862	63 3/4	x 73 3/4	64 1/4	x 74 1/4	DP-30	-	DP-50	23.8	12.5	-	Yes	-
21030	67 3/4	x 35 3/4	68 1/4	x 36 1/4	DP-30	-	DP-50	10.9	5.7	-	-	-
21032	67 3/4	x 37 3/4	68 1/4	x 38 1/4	DP-30	-	DP-50	11.7	6.1	-	-	-
21038	67 3/4	x 43 3/4	68 1/4	x 44 1/4	DP-30	-	DP-50	14.0	7.3	-	-	-
21040	67 3/4	x 47 3/4	68 1/4	x 48 1/4	DP-30	-	DP-50	15.6	8.2	-	-	-
21042	67 3/4	x 49 3/4	68 1/4	x 50 1/4	DP-30	-	DP-50	16.4	8.6	-	-	-
21046	67 3/4	x 53 3/4	68 1/4	x 54 1/4	DP-30	-	DP-50	17.9	9.4	-	-	-
21050	67 3/4	x 59 3/4	68 1/4	x 60 1/4	DP-30	-	DP-50	20.2	10.6	-	-	-
21052	67 3/4	x 61 3/4	68 1/4	x 62 1/4	DP-30	-	DP-50	21.0	11.0	-	-	-
21056	67 3/4	x 65 3/4	68 1/4	x 66 1/4	DP-30	-	DP-50	22.6	11.8	-	Yes	-
21060	67 3/4	x 71 3/4	68 1/4	x 72 1/4	DP-30	-	DP-50	24.9	13.0	-	Yes	-
21060c	67 3/4	x 71 3/4	68 1/4	x 72 1/4	-	NT	-	24.9	-	10.6	-	-
21060o	67 3/4	x 71 3/4	68 1/4	x 72 1/4	-	NT	-	24.9	-	10.6	-	-
21062	67 3/4	x 73 3/4	68 1/4	x 74 1/4	DP-30	-	DP-50	25.6	13.4	-	Yes	-
3030	71 3/4	x 35 3/4	72 1/4	x 36 1/4	DP-30	-	DP-50	11.7	6.1	-	-	-
3032	71 3/4	x 37 3/4	72 1/4	x 38 1/4	DP-30	-	DP-50	12.6	6.5	-	-	-
3038	71 3/4	x 43 3/4	72 1/4	x 44 1/4	DP-30	-	DP-50	15.0	7.8	-	-	-
3040	71 3/4	x 47 3/4	72 1/4	x 48 1/4	DP-30	-	DP-50	16.7	8.7	-	-	-
3042	71 3/4	x 49 3/4	72 1/4	x 50 1/4	DP-30	-	DP-50	17.5	9.1	-	-	-
3046	71 3/4	x 53 3/4	72 1/4	x 54 1/4	DP-30	-	DP-50	19.2	10.0	-	-	-
3050	71 3/4	x 59 3/4	72 1/4	x 60 1/4	DP-30	-	-	21.7	11.3	-	-	-
3052	71 3/4	x 61 3/4	72 1/4	x 62 1/4	DP-30	-	-	22.5	11.7	-	Yes	-
3056	71 3/4	x 65 3/4	72 1/4	x 66 1/4	DP-30	-	-	24.2	12.6	-	Yes	-
3060	71 3/4	x 71 3/4	72 1/4	x 72 1/4	DP-30	-	-	26.7	13.9	-	Yes	-
3060c	71 3/4	x 71 3/4	72 1/4	x 72 1/4	-	NT	-	26.7	-	11.3	-	Yes
3060o	71 3/4	x 71 3/4	72 1/4	x 72 1/4	-	NT	-	26.7	-	11.3	-	Yes
3062	71 3/4	x 73 3/4	72 1/4	x 74 1/4	DP-30	-	-	27.5	14.3	-	Yes	-
3230	75 3/4	x 35 3/4	76 1/4	x 36 1/4	DP-30	-	-	12.5	6.5	-	-	-
3232	75 3/4	x 37 3/4	76 1/4	x 38 1/4	DP-30	-	-	13.4	7.0	-	-	-
3238	75 3/4	x 43 3/4	76 1/4	x 44 1/4	DP-30	-	-	16.0	8.4	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Twin Window Units

Date: 09-May-07

Code	Twin Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
3240	75 3/4	x 47 3/4	76 1/4	x 48 1/4	DP-30	-	-	17.8	9.3	-	-	-
3242	75 3/4	x 49 3/4	76 1/4	x 50 1/4	DP-30	-	-	18.7	9.7	-	-	-
3246	75 3/4	x 53 3/4	76 1/4	x 54 1/4	DP-30	-	-	20.5	10.7	-	-	-
3250	75 3/4	x 59 3/4	76 1/4	x 60 1/4	DP-30	-	-	23.1	12.0	-	Yes	-
3252	75 3/4	x 61 3/4	76 1/4	x 62 1/4	DP-30	-	-	24.0	12.5	-	Yes	-
3256	75 3/4	x 65 3/4	76 1/4	x 66 1/4	DP-30	-	-	25.8	13.4	-	Yes	-
3260	75 3/4	x 71 3/4	76 1/4	x 72 1/4	DP-30	-	-	28.4	14.8	-	Yes	-
3260c	75 3/4	x 71 3/4	76 1/4	x 72 1/4	-	NT	-	28.4	-	12.0	-	Yes
3260o	75 3/4	x 71 3/4	76 1/4	x 72 1/4	-	NT	-	28.4	-	12.0	-	Yes
3262	75 3/4	x 73 3/4	76 1/4	x 74 1/4	DP-30	-	-	29.3	15.3	-	Yes	-
3430	79 3/4	x 35 3/4	80 1/4	x 36 1/4	NT	-	-	13.3	6.9	-	-	-
3432	79 3/4	x 37 3/4	80 1/4	x 38 1/4	NT	-	-	14.2	7.4	-	-	-
3438	79 3/4	x 43 3/4	80 1/4	x 44 1/4	NT	-	-	17.1	8.9	-	-	-
3440	79 3/4	x 47 3/4	80 1/4	x 48 1/4	NT	-	-	18.9	9.8	-	-	-
3442	79 3/4	x 49 3/4	80 1/4	x 50 1/4	NT	-	-	19.9	10.3	-	-	-
3446	79 3/4	x 53 3/4	80 1/4	x 54 1/4	NT	-	-	21.8	11.3	-	-	-
3450	79 3/4	x 59 3/4	80 1/4	x 60 1/4	NT	-	-	24.6	12.8	-	Yes	-
3452	79 3/4	x 61 3/4	80 1/4	x 62 1/4	NT	-	-	25.5	13.2	-	Yes	-
3456	79 3/4	x 65 3/4	80 1/4	x 66 1/4	NT	-	-	27.4	14.2	-	Yes	-
3460	79 3/4	x 71 3/4	80 1/4	x 72 1/4	NT	-	-	30.2	15.7	-	Yes	-
3460c	79 3/4	x 71 3/4	80 1/4	x 72 1/4	-	NT	-	30.2	-	12.7	-	Yes
3460o	79 3/4	x 71 3/4	80 1/4	x 72 1/4	-	NT	-	30.2	-	12.7	-	Yes
3462	79 3/4	x 73 3/4	80 1/4	x 74 1/4	NT	-	-	31.2	16.2	-	Yes	-
3630	83 3/4	x 35 3/4	84 1/4	x 36 1/4	NT	-	-	14.1	7.3	-	-	-
3632	83 3/4	x 37 3/4	84 1/4	x 38 1/4	NT	-	-	15.1	7.8	-	-	-
3638	83 3/4	x 43 3/4	84 1/4	x 44 1/4	NT	-	-	18.1	9.4	-	-	-
3640	83 3/4	x 47 3/4	84 1/4	x 48 1/4	NT	-	-	20.1	10.4	-	-	-
3642	83 3/4	x 49 3/4	84 1/4	x 50 1/4	NT	-	-	21.1	10.9	-	-	-
3646	83 3/4	x 53 3/4	84 1/4	x 54 1/4	NT	-	-	23.0	11.9	-	-	-
3650	83 3/4	x 59 3/4	84 1/4	x 60 1/4	NT	-	-	26.0	13.5	-	Yes	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Twin Window Units

Date: 09-May-07

Code	Twin Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
3652	83 3/4	x 61 3/4	84 1/4	x 62 1/4	NT	-	-	27.0	14.0	-	Yes	-
3656	83 3/4	x 65 3/4	84 1/4	x 66 1/4	NT	-	-	29.0	15.0	-	Yes	-
3660	83 3/4	x 71 3/4	84 1/4	x 72 1/4	NT	-	-	32.0	16.6	-	Yes	-
3660c	83 3/4	x 71 3/4	84 1/4	x 72 1/4	-	NT	-	32.0	-	13.5	-	Yes
3660o	83 3/4	x 71 3/4	84 1/4	x 72 1/4	-	NT	-	32.0	-	13.5	-	Yes
3662	83 3/4	x 73 3/4	84 1/4	x 74 1/4	NT	-	-	33.0	17.1	-	Yes	-
3830	87 3/4	x 35 3/4	88 1/4	x 36 1/4	NT	-	-	14.9	7.7	-	-	-
3832	87 3/4	x 37 3/4	88 1/4	x 38 1/4	NT	-	-	15.9	8.2	-	-	-
3838	87 3/4	x 43 3/4	88 1/4	x 44 1/4	NT	-	-	19.1	9.9	-	-	-
3840	87 3/4	x 47 3/4	88 1/4	x 48 1/4	NT	-	-	21.2	10.9	-	-	-
3842	87 3/4	x 49 3/4	88 1/4	x 50 1/4	NT	-	-	22.2	11.5	-	-	-
3846	87 3/4	x 53 3/4	88 1/4	x 54 1/4	NT	-	-	24.3	12.6	-	-	-
3850	87 3/4	x 59 3/4	88 1/4	x 60 1/4	NT	-	-	27.5	14.2	-	Yes	-
3852	87 3/4	x 61 3/4	88 1/4	x 62 1/4	NT	-	-	28.5	14.8	-	Yes	-
3856	87 3/4	x 65 3/4	88 1/4	x 66 1/4	NT	-	-	30.6	15.8	-	Yes	-
3860	87 3/4	x 71 3/4	88 1/4	x 72 1/4	NT	-	-	33.8	17.5	-	Yes	-
3860c	87 3/4	x 71 3/4	88 1/4	x 72 1/4	-	NT	-	33.8	-	14.2	-	Yes
3860o	87 3/4	x 71 3/4	88 1/4	x 72 1/4	-	NT	-	33.8	-	14.2	-	Yes
3862	87 3/4	x 73 3/4	88 1/4	x 74 1/4	NT	-	-	-	-	-	Yes	-
31030	91 3/4	x 35 3/4	92 1/4	x 36 1/4	NT	-	-	15.6	8.1	-	-	-
31032	91 3/4	x 37 3/4	92 1/4	x 38 1/4	NT	-	-	16.8	8.7	-	-	-
31038	91 3/4	x 43 3/4	92 1/4	x 44 1/4	NT	-	-	20.1	10.4	-	-	-
31040	91 3/4	x 47 3/4	92 1/4	x 48 1/4	NT	-	-	22.3	11.5	-	-	-
31042	91 3/4	x 49 3/4	92 1/4	x 50 1/4	NT	-	-	23.4	12.1	-	-	-
31046	91 3/4	x 53 3/4	92 1/4	x 54 1/4	NT	-	-	25.6	13.2	-	-	-
31050	91 3/4	x 59 3/4	92 1/4	x 60 1/4	NT	-	-	28.9	14.9	-	Yes	-
31052	91 3/4	x 61 3/4	92 1/4	x 62 1/4	NT	-	-	30.0	15.5	-	Yes	-
31056	91 3/4	x 65 3/4	92 1/4	x 66 1/4	NT	-	-	32.3	16.6	-	Yes	-
31060	91 3/4	x 71 3/4	92 1/4	x 72 1/4	NT	-	-	35.6	18.4	-	Yes	-
31060c	91 3/4	x 71 3/4	92 1/4	x 72 1/4	-	NT	-	35.6	-	14.9	-	Yes

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Twin Window Units

Date: 09-May-07

Code	Twin Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage
31060o	91 3/4	x 71 3/4	92 1/4	x 72 1/4	-	NT	-	35.6	-	14.9	-	Yes
31062	-	-	-	-	-	-	-	-	-	-	-	-
4030	95 3/4	x 35 3/4	96 1/4	x 36 1/4	NT	-	-	16.4	8.5	-	-	-
4032	95 3/4	x 37 3/4	96 1/4	x 38 1/4	NT	-	-	17.6	9.1	-	-	-
4038	95 3/4	x 43 3/4	96 1/4	x 44 1/4	NT	-	-	21.1	10.9	-	-	-
4040	95 3/4	x 47 3/4	96 1/4	x 48 1/4	NT	-	-	23.4	12.1	-	-	-
4042	95 3/4	x 49 3/4	96 1/4	x 50 1/4	NT	-	-	24.6	12.7	-	-	-
4046	95 3/4	x 53 3/4	96 1/4	x 54 1/4	NT	-	-	26.9	13.9	-	-	-
4050	95 3/4	x 59 3/4	96 1/4	x 60 1/4	NT	-	-	30.4	15.7	-	Yes	-
4052	95 3/4	x 61 3/4	96 1/4	x 62 1/4	NT	-	-	31.6	16.3	-	Yes	-
4056	95 3/4	x 65 3/4	96 1/4	x 66 1/4	NT	-	-	33.9	17.5	-	Yes	-
4060	95 3/4	x 71 3/4	96 1/4	x 72 1/4	NT	-	-	37.4	19.3	-	Yes	-
4060c	95 3/4	x 71 3/4	96 1/4	x 72 1/4	-	NT	-	37.4	-	15.6	-	Yes
4060o	95 3/4	x 71 3/4	96 1/4	x 72 1/4	-	NT	-	37.4	-	15.6	-	Yes
4062	-	-	-	-	-	-	-	-	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Triple Window Units

Date: 09-May-07

Code	Triple Window Unit																		
	Unit Dimensions			Rough Opening			DP Rating			Daylight	Ventilation		Clear Opening						
	Width	Height		Width	Height		Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage					
1830	59	7/8	x	35	3/4		60	3/8	x	36	1/4	DP-35	-	DP-50	8.2	4.5	-	-	-
1832	59	7/8	x	37	3/4		60	3/8	x	38	1/4	DP-35	-	DP-50	8.7	4.8	-	-	-
1838	59	7/8	x	43	3/4		60	3/8	x	44	1/4	DP-35	-	DP-50	10.5	5.7	-	-	-
1840	59	7/8	x	47	3/4		60	3/8	x	48	1/4	DP-35	-	DP-50	11.6	6.3	-	-	-
1842	59	7/8	x	49	3/4		60	3/8	x	50	1/4	DP-35	-	DP-50	12.2	6.7	-	-	-
1846	59	7/8	x	53	3/4		60	3/8	x	54	1/4	DP-35	-	DP-50	13.4	7.3	-	-	-
1850	59	7/8	x	59	3/4		60	3/8	x	60	1/4	NT	-	-	15.1	8.2	-	-	-
1852	59	7/8	x	61	3/4		60	3/8	x	62	1/4	NT	-	-	15.7	8.6	-	-	-
1856	59	7/8	x	65	3/4		60	3/8	x	66	1/4	NT	-	-	16.8	9.2	-	-	-
1860	59	7/8	x	71	3/4		60	3/8	x	72	1/4	NT	-	-	18.6	10.1	-	-	-
1860c	59	7/8	x	71	3/4		60	3/8	x	72	1/4	-	NT	-	18.6	-	8.2	-	-
1860o	59	7/8	x	71	3/4		60	3/8	x	72	1/4	-	NT	-	18.6	-	8.2	-	-
1862	59	7/8	x	73	3/4		60	3/8	x	74	1/4	NT	-	-	19.2	10.4	-	-	-
11030	65	7/8	x	35	3/4		66	3/8	x	36	1/4	DP-35	-	DP-50	9.3	5.0	-	-	-
11032	65	7/8	x	37	3/4		66	3/8	x	38	1/4	DP-35	-	DP-50	10.0	5.4	-	-	-
11038	65	7/8	x	43	3/4		66	3/8	x	44	1/4	DP-35	-	DP-50	12.0	6.5	-	-	-
11040	65	7/8	x	47	3/4		66	3/8	x	48	1/4	DP-35	-	DP-50	13.3	7.2	-	-	-
11042	65	7/8	x	49	3/4		66	3/8	x	50	1/4	DP-35	-	DP-50	14.0	7.5	-	-	-
11046	65	7/8	x	53	3/4		66	3/8	x	54	1/4	DP-35	-	DP-50	15.3	8.3	-	-	-
11050	65	7/8	x	59	3/4		66	3/8	x	60	1/4	NT	-	-	17.3	9.3	-	-	-
11052	65	7/8	x	61	3/4		66	3/8	x	62	1/4	NT	-	-	17.9	9.7	-	-	-
11056	65	7/8	x	65	3/4		66	3/8	x	66	1/4	NT	-	-	19.3	10.4	-	-	-
11060	65	7/8	x	71	3/4		66	3/8	x	72	1/4	NT	-	-	21.2	11.5	-	-	-
11060c	65	7/8	x	71	3/4		66	3/8	x	72	1/4	-	NT	-	21.2	-	9.3	-	-
11060o	65	7/8	x	71	3/4		66	3/8	x	72	1/4	-	NT	-	21.2	-	9.3	-	-
11062	65	7/8	x	73	3/4		66	3/8	x	74	1/4	NT	-	-	21.9	11.8	-	-	-
2030	71	7/8	x	35	3/4		72	3/8	x	36	1/4	DP-35	-	DP-50	10.5	5.6	-	-	-
2032	71	7/8	x	37	3/4		72	3/8	x	38	1/4	DP-35	-	DP-50	11.3	6.0	-	-	-
2038	71	7/8	x	43	3/4		72	3/8	x	44	1/4	DP-35	-	DP-50	13.5	7.2	-	-	-
2040	71	7/8	x	47	3/4		72	3/8	x	48	1/4	DP-35	-	DP-50	15.0	8.0	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Triple Window Units

Date: 09-May-07

Code	Triple Window Unit																			
	Unit Dimensions			Rough Opening			DP Rating			Daylight	Ventilation		Clear Opening							
	Width	Height		Width	Height		Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage						
2042	71	7/8	x	49	3/4		72	3/8	x	50	1/4	DP-35	-	DP-50	15.7	8.4	-	-	-	-
2046	71	7/8	x	53	3/4		72	3/8	x	54	1/4	DP-35	-	DP-50	17.2	9.2	-	-	-	-
2050	71	7/8	x	59	3/4		72	3/8	x	60	1/4	-	-	-	19.5	10.4	-	-	-	-
2052	71	7/8	x	61	3/4		72	3/8	x	62	1/4	-	-	-	20.2	10.8	-	-	-	-
2056	71	7/8		65	3/4		72	3/8		66	1/4	-	-	-	21.7	11.6	-	-	-	-
2060	71	7/8		71	3/4		72	3/8		72	1/4	-	-	-	23.9	12.8	-	-	-	-
2060c	71	7/8	x	71	3/4		72	3/8	x	72	1/4	-	NT	-	23.9	-	10.4	-	-	-
2060o	71	7/8	x	71	3/4		72	3/8	x	72	1/4	-	NT	-	23.9	-	10.4	-	-	-
2062	71	7/8	x	73	3/4		72	3/8	x	74	1/4	-	-	-	24.7	13.2	-	-	-	-
2230	77	7/8	x	35	3/4		78	3/8	x	36	1/4	DP-35	-	DP-50	11.7	6.2	-	-	-	-
2232	77	7/8	x	37	3/4		78	3/8	x	38	1/4	DP-35	-	DP-50	12.5	6.7	-	-	-	-
2238	77	7/8	x	43	3/4		78	3/8	x	44	1/4	DP-35	-	DP-50	15.0	8.0	-	-	-	-
2240	77	7/8	x	47	3/4		78	3/8	x	48	1/4	DP-35	-	DP-50	16.7	8.9	-	-	-	-
2242	77	7/8	x	49	3/4		78	3/8	x	50	1/4	DP-35	-	DP-50	17.5	9.3	-	-	-	-
2246	77	7/8	x	53	3/4		78	3/8	x	54	1/4	DP-35	-	DP-50	19.2	10.2	-	-	-	-
2250	77	7/8	x	59	3/4		78	3/8	x	60	1/4	NT	-	-	21.6	11.5	-	-	-	-
2252	77	7/8	x	61	3/4		78	3/8	x	62	1/4	NT	-	-	22.5	11.9	-	-	-	-
2256	77	7/8	x	65	3/4		78	3/8	x	66	1/4	NT	-	-	24.1	12.8	-	-	-	-
2260	77	7/8	x	71	3/4		78	3/8	x	72	1/4	NT	-	-	26.6	14.1	-	-	-	-
2260c	77	7/8	x	71	3/4		78	3/8	x	72	1/4	-	NT	-	26.6	-	11.5	-	-	-
2260o	77	7/8	x	71	3/4		78	3/8	x	72	1/4	-	NT	-	26.6	-	11.5	-	-	-
2262	77	7/8	x	73	3/4		78	3/8	x	74	1/4	NT	-	-	27.4	14.6	-	-	-	-
2430	83	7/8	x	35	3/4		84	3/8	x	36	1/4	DP-35	-	DP-50	12.9	6.8	-	-	-	-
2432	83	7/8	x	37	3/4		84	3/8	x	38	1/4	DP-35	-	DP-50	13.8	7.3	-	-	-	-
2438	83	7/8	x	43	3/4		84	3/8	x	44	1/4	DP-35	-	DP-50	16.5	8.7	-	-	-	-
2440	83	7/8	x	47	3/4		84	3/8	x	48	1/4	DP-35	-	DP-50	18.3	9.7	-	-	-	-
2442	83	7/8	x	49	3/4		84	3/8	x	50	1/4	DP-35	-	DP-50	19.3	10.2	-	-	-	-
2446	83	7/8	x	53	3/4		84	3/8	x	54	1/4	DP-35	-	DP-50	21.1	11.2	-	-	-	-
2450	83	7/8	x	59	3/4		84	3/8	x	60	1/4	-	-	-	23.8	12.6	-	-	-	-
2452	83	7/8	x	61	3/4		84	3/8	x	62	1/4	-	-	-	24.7	13.1	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Triple Window Units

Date: 09-May-07

Code	Triple Window Unit													
	Unit Dimensions			Rough Opening			DP Rating			Ventilation		Clear Opening		
	Width	Height		Width	Height		Equal	Cottage	Optional	Daylight	Equal	Cottage	Equal	Cottage
2456	83	7/8	x	65	3/4		-	-	-	26.5	14.0	-	-	-
2460	83	7/8	x	71	3/4		-	-	-	29.3	15.5	-	-	-
2460c	83	7/8	x	71	3/4		-	NT	-	29.3	-	12.6	-	-
2460o	83	7/8	x	71	3/4		-	NT	-	29.3	-	12.6	-	-
2462	83	7/8	x	73	3/4		-	-	-	30.2	16.0	-	-	-
2630	89	7/8	x	35	3/4		DP-35	-	DP-50	14.1	7.4	-	-	-
2632	89	7/8	x	37	3/4		DP-35	-	DP-50	15.0	7.9	-	-	-
2638	89	7/8	x	43	3/4		DP-35	-	DP-50	18.0	9.5	-	-	-
2640	89	7/8	x	47	3/4		DP-35	-	DP-50	20.0	10.5	-	-	-
2642	89	7/8	x	49	3/4		DP-35	-	DP-50	21.0	11.1	-	-	-
2646	89	7/8	x	53	3/4		DP-35	-	DP-50	23.0	12.1	-	-	-
2650	89	7/8	x	59	3/4		NT	-	-	26.0	13.7	-	-	-
2652	89	7/8	x	61	3/4		NT	-	-	27.0	14.2	-	-	-
2656	89	7/8	x	65	3/4		NT	-	-	29.0	15.3	-	-	-
2660	89	7/8	x	71	3/4		NT	-	-	32.0	16.8	-	-	-
2660c	89	7/8	x	71	3/4		-	NT	-	32.0	-	13.7	-	-
2660o	89	7/8	x	71	3/4		-	NT	-	32.0	-	13.7	-	-
2662	89	7/8	x	73	3/4		NT	-	-	33.0	17.4	-	Yes	-
2830	95	7/8	x	35	3/4		DP-35	-	DP-50	15.2	8.0	-	-	-
2832	95	7/8	x	37	3/4		DP-35	-	DP-50	16.3	8.6	-	-	-
2838	95	7/8	x	43	3/4		DP-35	-	DP-50	19.5	10.3	-	-	-
2840	95	7/8	x	47	3/4		DP-35	-	DP-50	21.7	11.4	-	-	-
2842	95	7/8	x	49	3/4		DP-35	-	DP-50	22.8	12.0	-	-	-
2846	95	7/8	x	53	3/4		DP-35	-	DP-50	24.9	13.1	-	-	-
2850	95	7/8	x	59	3/4		-	-	-	28.2	14.8	-	-	-
2852	95	7/8	x	61	3/4		-	-	-	29.2	15.3	-	-	-
2856	95	7/8	x	65	3/4		-	-	-	31.4	16.5	-	-	-
2860	95	7/8	x	71	3/4		-	-	-	34.6	18.2	-	Yes	-
2860c	95	7/8	x	71	3/4		-	NT	-	34.6	-	14.8	-	-
2860o	95	7/8	x	71	3/4		-	NT	-	34.6	-	14.8	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Triple Window Units

Date: 09-May-07

Code	Triple Window Unit														
	Unit Dimensions			Rough Opening				DP Rating			Daylight	Ventilation		Clear Opening	
	Width	Height		Width	Height		Equal	Cottage	Optional	Equal		Cottage	Equal	Cottage	
2862	95 7/8	x	73 3/4	96 3/8	x	74 1/4	-	-	-	35.7	18.7	-	Yes	-	
21030	101 7/8	x	35 3/4	102 3/8	x	36 1/4	DP-35	-	DP-50	16.4	8.6	-	-	-	
21032	101 7/8	x	37 3/4	102 3/8	x	38 1/4	DP-35	-	DP-50	17.6	9.2	-	-	-	
21038	101 7/8	x	43 3/4	102 3/8	x	44 1/4	DP-35	-	DP-50	21.1	11.0	-	-	-	
21040	101 7/8	x	47 3/4	102 3/8	x	48 1/4	DP-35	-	DP-50	23.4	12.2	-	-	-	
21042	101 7/8	x	49 3/4	102 3/8	x	50 1/4	DP-35	-	DP-50	24.5	12.8	-	-	-	
21046	101 7/8	x	53 3/4	102 3/8	x	54 1/4	DP-35	-	DP-50	26.9	14.0	-	-	-	
21050	101 7/8	x	59 3/4	102 3/8	x	60 1/4	NT	-	-	30.3	15.9	-	-	-	
21052	101 7/8	x	61 3/4	102 3/8	x	62 1/4	NT	-	-	31.5	16.5	-	-	-	
21056	101 7/8	x	65 3/4	102 3/8	x	66 1/4	NT	-	-	33.8	17.7	-	Yes	-	
21060	101 7/8	x	71 3/4	102 3/8	x	72 1/4	NT	-	-	37.3	19.5	-	Yes	-	
21060c	101 7/8	x	71 3/4	102 3/8	x	72 1/4	-	NT	-	37.3	-	15.9	-	-	
21060o	101 7/8	x	71 3/4	102 3/8	x	72 1/4	-	NT	-	37.3	-	15.9	-	-	
21062	101 7/8	x	73 3/4	102 3/8	x	74 1/4	NT	-	-	38.5	20.1	-	Yes	-	
3030	107 7/8	x	35 3/4	108 3/8	x	36 1/4	DP-35	-	DP-50	17.6	9.2	-	-	-	
3032	107 7/8	x	37 3/4	108 3/8	x	38 1/4	DP-35	-	DP-50	18.8	9.8	-	-	-	
3038	107 7/8	x	43 3/4	108 3/8	x	44 1/4	DP-35	-	DP-50	22.6	11.8	-	-	-	
3040	107 7/8	x	47 3/4	108 3/8	x	48 1/4	DP-35	-	DP-50	25.1	13.1	-	-	-	
3042	107 7/8	x	49 3/4	108 3/8	x	50 1/4	DP-35	-	DP-50	26.3	13.7	-	-	-	
3046	107 7/8	x	53 3/4	108 3/8	x	54 1/4	DP-35	-	DP-50	28.8	15.0	-	-	-	
3050	107 7/8	x	59 3/4	108 3/8	x	60 1/4	NT	-	-	32.5	17.0	-	-	-	
3052	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
3056	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
3060	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
3060c	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
3060o	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
3062	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
3230	113 7/8	x	35 3/4	114 3/8	x	36 1/4	DP-35	-	DP-50	18.8	9.8	-	-	-	
3232	113 7/8	x	37 3/4	114 3/8	x	38 1/4	DP-35	-	DP-50	20.1	10.5	-	-	-	
3238	113 7/8	x	43 3/4	114 3/8	x	44 1/4	DP-35	-	DP-50	24.1	12.5	-	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Triple Window Units

Date: 09-May-07

Code	Triple Window Unit																			
	Unit Dimensions			Rough Opening			DP Rating			Daylight	Ventilation		Clear Opening							
	Width	Height		Width	Height		Equal	Cottage	Optional		Equal	Cottage	Equal	Cottage						
3240	113	7/8	x	47	3/4		114	3/8	x	48	1/4	DP-35	-	DP-50	26.7	13.9	-	-	-	-
3242	113	7/8	x	49	3/4		114	3/8	x	50	1/4	DP-35	-	DP-50	28.1	14.6	-	-	-	-
3246	113	7/8	x	53	3/4		114	3/8	x	54	1/4	DP-35	-	DP-50	30.7	16.0	-	-	-	-
3250	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3252	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3256	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3260	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3260c	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3260o	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3262	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3430	119	7/8	x	35	3/4		120	3/8	x	36	1/4	NT	-	-	19.9	10.4	-	-	-	-
3432	119	7/8	x	37	3/4		120	3/8	x	38	1/4	NT	-	-	21.3	11.1	-	-	-	-
3438	119	7/8	x	43	3/4		120	3/8	x	44	1/4	NT	-	-	25.6	13.3	-	-	-	-
3440	119	7/8	x	47	3/4		120	3/8	x	48	1/4	NT	-	-	28.4	14.7	-	-	-	-
3442	119	7/8	x	49	3/4		120	3/8	x	50	1/4	NT	-	-	29.8	15.5	-	-	-	-
3446	119	7/8	x	53	3/4		120	3/8	x	54	1/4	NT	-	-	32.6	16.9	-	-	-	-
3450	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3452	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3456	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3460	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3460c	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3460o	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3462	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3630	125	7/8	x	35	3/4		126	3/8	x	36	1/4	NT	-	-	21.1	10.9	-	-	-	-
3632	125	7/8	x	37	3/4		126	3/8	x	38	1/4	NT	-	-	22.6	11.7	-	-	-	-
3638	125	7/8	x	43	3/4		126	3/8	x	44	1/4	NT	-	-	27.1	14.0	-	-	-	-
3640	125	7/8	x	47	3/4		126	3/8	x	48	1/4	NT	-	-	30.1	15.6	-	-	-	-
3642	125	7/8	x	49	3/4		126	3/8	x	50	1/4	NT	-	-	31.6	16.4	-	-	-	-
3646	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3650	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area
 0

Minimum window width for 20" clear opening width – 74 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Triple Window Units

Date: 09-May-07

Code	Triple Window Unit																			
	Unit Dimensions			Rough Opening			DP Rating			Ventilation		Clear Opening								
	Width	Height		Width	Height		Equal	Cottage	Optional	Daylight	Equal	Cottage	Equal	Cottage						
3652	-	-		-	-		-	-	-	-	-	-	-	-						
3656	-	-		-	-		-	-	-	-	-	-	-	-						
3660	-	-		-	-		-	-	-	-	-	-	-	-						
3660c	-	-		-	-		-	-	-	-	-	-	-	-						
3660o	-	-		-	-		-	-	-	-	-	-	-	-						
3662	-	-		-	-		-	-	-	-	-	-	-	-						
3830	131	7/8	x	35	3/4		132	3/8	x	36	1/4	NT	-	-	22.3	11.5	-	-	-	-
3832	131	7/8	x	37	3/4		132	3/8	x	38	1/4	NT	-	-	23.9	12.3	-	-	-	-
3838	131	7/8	x	43	3/4		132	3/8	x	44	1/4	NT	-	-	28.6	14.8	-	-	-	-
3840	131	7/8	x	47	3/4		132	3/8	x	48	1/4	NT	-	-	31.8	16.4	-	-	-	-
3842	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3846	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3850	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3852	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3856	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3860	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3860c	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3860o	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
3862	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31030	137	7/8	x	35	3/4		138	3/8	x	36	1/4	NT	-	-	23.5	12.1	-	-	-	-
31032	137	7/8	x	37	3/4		138	3/8	x	38	1/4	NT	-	-	25.1	13.0	-	-	-	-
31038	137	7/8	x	43	3/4		138	3/8	x	44	1/4	NT	-	-	30.1	15.6	-	-	-	-
31040	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31042	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31046	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31050	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31052	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31056	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31060	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-
31060c	-	-		-	-		-	-	-	-	-	-	-	-	-	-	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area
 0

Minimum window width for 20" clear opening width – 74 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Triple Window Units

Date: 09-May-07

Code	Triple Window Unit															
	Unit Dimensions				Rough Opening				DP Rating			Ventilation		Clear Opening		
	Width		Height		Width		Height		Equal	Cottage	Optional	Daylight	Equal	Cottage	Equal	Cottage
31060o	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
31062	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4030	143	7/8	x	35 3/4	144	3/8	x	36 1/4	NT	-	-	24.6	12.7	-	-	-
4032	143	7/8	x	37 3/4	144	3/8	x	38 1/4	NT	-	-	26.4	13.6	-	-	-
4038	143	7/8	x	43 3/4	144	3/8	x	44 1/4	NT	-	-	31.6	16.3	-	-	-
4040	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4042	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4046	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4050	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4052	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4056	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4060	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4060c	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4060o	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
4062	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Ventilati

Single Window Units

Date: 09-May-07

Window				Width 18 to 210								
Height	Call Out	Unit Dimension		18	110	20	22	24	26	28	210	
		Rough Opening		19 5/8	21 5/8	23 5/8	25 5/8	27 5/8	29 5/8	31 5/8	33 5/8	
		30	35 3/4	36 1/4	20 1/8	22 1/8	24 1/8	26 1/8	28 1/8	30 1/8	32 1/8	34 1/8
30	35 3/4	36 1/4	Ventilation	1.5	1.7	1.9	2.1	2.3	2.5	2.7	2.9	
			Daylight	2.7	3.1	3.5	3.9	4.3	4.7	5.1	5.5	
	32	37 3/4	38 1/4	Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
				Ventilation	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.1
	38	43 3/4	44 1/4	Daylight	2.9	3.3	3.8	4.2	4.6	5.0	5.4	
				Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50
	40	47 3/4	48 1/4	Ventilation	1.9	2.2	2.4	2.7	2.9	3.2	3.4	3.7
				Daylight	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0
	42	49 3/4	50 1/4	Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50
				Ventilation	2.1	2.4	2.7	3.0	3.2	3.5	3.8	4.1
	46	53 3/4	54 1/4	Daylight	3.9	4.4	5.0	5.6	6.1	6.7	7.2	7.8
				Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50
	50	59 3/4	60 1/4	Ventilation	2.2	2.5	2.8	3.1	3.4	3.7	4.0	4.3
				Daylight	4.1	4.7	5.2	5.8	6.4	7.0	7.6	8.2
52	61 3/4	62 1/4	Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
			Ventilation	2.4	2.8	3.1	3.4	3.7	4.0	4.4	4.7	
56	65 3/4	66 1/4	Daylight	4.5	5.1	5.7	6.4	7.0	7.7	8.3	9.0	
			Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
60	71 3/4	72 1/4	Ventilation	2.7	3.1	3.5	3.8	4.2	4.6	4.9	5.3	
			Daylight	5.0	5.8	6.5	7.2	7.9	8.7	9.4	10.1	
60	71 3/4	72 1/4	Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	
			Ventilation	2.8	3.2	3.6	4.0	4.4	4.7	5.1	5.5	
60	71 3/4	72 1/4	Daylight	5.2	6.0	6.7	7.5	8.2	9.0	9.7	10.5	
			Design Pressure	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-50	DP-25/DP-50	
60	71 3/4	72 1/4	Ventilation	3.1	3.5	3.9	4.3	4.7	5.1	5.5	5.9	
			Daylight	5.6	6.4	7.2	8.0	8.8	9.7	10.5	11.3	
60	71 3/4	72 1/4	Design Pressure	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	
			Ventilation	3.4	3.8	4.3	4.7	5.2	5.6	6.1	6.5	
60	71 3/4	72 1/4	Daylight	6.2	7.1	8.0	8.9	9.8	10.7	11.5	12.4	
			Design Pressure	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	
60	71 3/4	72 1/4	Ventilation	2.7	3.1	3.5	3.8	4.2	4.6	4.9	5.3	
			Daylight	6.1	7.0	7.9	8.8	9.7	10.6	11.5	12.4	
60	71 3/4	72 1/4	Design Pressure	NT	NT	NT	NT	NT	NT	NT	NT	
			Ventilation	2.7	3.1	3.5	3.8	4.2	4.6	4.9	5.3	
60	71 3/4	72 1/4	Daylight	6.2	7.1	8.0	8.9	9.8	10.7	11.5	12.4	
			Design Pressure	NT	NT	NT	NT	NT	NT	NT	NT	
62	73 3/4	74 1/4	Ventilation	3.5	3.9	4.4	4.9	5.3	5.8	6.2	6.7	
			Daylight	6.4	7.3	8.2	9.1	10.1	11.0	11.9	12.8	
62	73 3/4	74 1/4	Design Pressure	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	DP-25/DP-50	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Test Window Dimensions:

44" x 77"	DP-25	37 5/8" x 59"	DP-50
33 7/8" x 65"	DP-50	37 7/8" x 65"	DP-50
33 7/8" x 77"	DP-50	37 5/8" x 71" Cottage	DP-30
35 5/8" x 59 3/4"	DP-50	41 5/8" x 59"	DP-50

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Daylight, ion and Design Pressure

Single Window Units

Date: 09-May-07

Window				Width 30 to 310										
Height	Call Out	Unit Dimension	Rough Opening	30	32	34	36	38	310	40				
				30	35 3/4	36 1/4	Ventilation Daylight Design Pressure	3.1 5.9 DP-50	3.2 6.3 DP-50	3.4 6.6 DP-25/DP-50	3.6 7.0 DP-25/DP-50	3.8 7.4 DP-25	4.0 7.8 NT	4.2 8.2 NT
				32	37 3/4	38 1/4	Ventilation Daylight Design Pressure	3.3 6.3 DP-50	3.5 6.7 DP-50	3.7 7.1 DP-25/DP-50	3.9 7.5 DP-25/DP-50	4.1 8.0 DP-25	4.3 8.4 NT	4.5 8.8 NT
38	43 3/4	44 1/4	Ventilation Daylight Design Pressure	3.9 7.5 DP-50	4.2 8.0 DP-50	4.4 8.5 DP-25/DP-50	4.7 9.0 DP-25/DP-50	4.9 9.5 DP-25	5.2 10.0 NT	5.4 10.5 NT				
40	47 3/4	48 1/4	Ventilation Daylight Design Pressure	4.3 8.4 DP-50	4.6 8.9 DP-50	4.9 9.5 DP-25/DP-50	5.2 10.0 DP-25/DP-50	5.5 10.6 DP-25	5.7 11.1 NT	6.0 11.7 NT				
42	49 3/4	50 1/4	Ventilation Daylight Design Pressure	4.6 8.8 DP-50	4.9 9.4 DP-50	5.2 9.9 DP-25/DP-50	5.4 10.5 DP-25/DP-50	5.7 11.1 DP-25	6.0 11.7 NT	6.3 12.3 NT				
46	53 3/4	54 1/4	Ventilation Daylight Design Pressure	5.0 9.6 DP-50	5.3 10.2 DP-50	5.6 10.9 DP-25/DP-50	6.0 11.5 DP-25/DP-50	6.3 12.2 DP-25	6.6 12.8 NT	6.9 13.4 NT				
50	59 3/4	60 1/4	Ventilation Daylight Design Pressure	5.7 10.8 DP-50	6.0 11.6 DP-25/DP-50	6.4 12.3 DP-25	6.7 13.0 DP-25	7.1 13.7 DP-25	7.5 14.5 NT	7.8 15.2 NT				
52	61 3/4	62 1/4	Ventilation Daylight Design Pressure	5.9 11.3 DP-25/DP-50	6.2 12.0 DP-25/DP-50	6.6 12.8 DP-25	7.0 13.5 DP-25	7.4 14.3 DP-25	7.7 15.0 NT	8.1 15.8 NT				
56	65 3/4	66 1/4	Ventilation Daylight Design Pressure	6.3 12.1 DP-25	6.7 12.9 DP-25	7.1 13.7 DP-25	7.5 14.5 DP-25	7.9 15.3 DP-25	8.3 16.1 NT	8.7 16.9 NT				
60	71 3/4	72 1/4	Ventilation Daylight Design Pressure	6.9 13.3 DP-25	7.4 14.2 DP-25	7.8 15.1 DP-25	8.3 16.0 DP-25	8.7 16.9 DP-25	9.2 17.8 NT	9.6 18.7 NT				
60 Cottage	71 3/4	72 1/4	Ventilation Daylight Design Pressure	5.7 13.2 NT	6.0 14.1 NT	6.4 15.0 NT	6.7 15.9 NT	7.1 16.8 NT	7.5 17.7 NT	7.8 18.6 NT				
60 Oriel	71 3/4	72 1/4	Ventilation Daylight Design Pressure	5.7 13.3 NT	6.0 14.2 NT	6.4 15.1 NT	6.7 16.0 NT	7.1 16.9 NT	7.5 17.8 NT	7.8 18.7 NT				
62	73 3/4	74 1/4	Ventilation Daylight Design Pressure	7.2 13.7 DP-25	7.6 14.7 DP-25	8.1 15.6 DP-25	8.5 16.5 DP-25	9.0 17.4 DP-25	9.5 18.3 NT	9.9 19.3 NT				

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Test Window Dimensions:

44" x 77"	DP-25	37 5/8" x 59"	DP-50
33 7/8" x 65"	DP-50	37 7/8" x 65"	DP-50
33 7/8" x 77"	DP-50	37 5/8" x 71" Cottage	DP-30
35 5/8" x 59 3/4"	DP-50	41 5/8" x 59"	DP-50

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Ventilati

Twin Window Units

Date: 09-May-07

Window		Width 18 to 28											
Height	Call Out	Unit Dimension		18	110	20	22	24	26	28	210		
	30	35 3/4	Rough Opening	39 3/4	43 3/4	47 3/4	51 3/4	55 3/4	59 3/4	63 3/4	67 3/4		
			36 1/4	40 1/4	44 1/4	48 1/4	52 1/4	56 1/4	60 1/4	64 1/4	68 1/4		
30	Ventilation	35 3/4	36 1/4	3.0	3.4	3.8	4.1	4.5	4.9	5.3	5.7	10.9	
													Daylight
	Design Pressure	35 3/4	36 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50
	Ventilation	37 3/4	38 1/4	3.2	3.6	4.0	4.4	4.9	5.3	5.7	6.1	11.7	
													Daylight
	Design Pressure	37 3/4	38 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50
	Ventilation	43 3/4	44 1/4	3.8	4.3	4.8	5.3	5.8	6.3	6.8	7.3	14.0	
													Daylight
	Design Pressure	43 3/4	44 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50
	Ventilation	47 3/4	48 1/4	4.2	4.8	5.3	5.9	6.5	7.0	7.6	8.1	15.6	
													Daylight
Design Pressure	47 3/4	48 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
													42
Ventilation	49 3/4	50 1/4	4.4	5.0	5.6	6.2	6.8	7.4	8.0	8.5	16.4		
												Daylight	8.1
Design Pressure	49 3/4	50 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
													46
Ventilation	53 3/4	54 1/4	4.9	5.5	6.1	6.8	7.4	8.1	8.7	9.4	17.9		
												Daylight	8.9
Design Pressure	53 3/4	54 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
													50
Ventilation	59 3/4	60 1/4	5.5	6.2	6.9	7.7	8.4	9.1	9.8	10.6	20.2		
												Daylight	10.1
Design Pressure	59 3/4	60 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
													52
Ventilation	61 3/4	62 1/4	5.7	6.5	7.2	8.0	8.7	9.5	10.2	11.0	21.0		
												Daylight	10.5
Design Pressure	61 3/4	62 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
													56
Ventilation	65 3/4	66 1/4	6.1	6.9	7.7	8.5	9.4	10.2	11.0	11.8	22.6		
												Daylight	11.2
Design Pressure	65 3/4	66 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
													60
Ventilation	71 3/4	72 1/4	6.7	7.6	8.5	9.4	10.3	11.2	12.1	13.0	24.9		
												Daylight	12.4
Design Pressure	71 3/4	72 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	
													60 Cottage
Ventilation	71 3/4	72 1/4	5.5	6.2	6.9	7.7	8.4	9.1	9.8	10.6	24.7		
												Daylight	12.2
Design Pressure	71 3/4	72 1/4	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	
													60 Oriel
Ventilation	71 3/4	72 1/4	5.5	6.2	6.9	7.7	8.4	9.1	9.8	10.6	24.9		
												Daylight	12.4
Design Pressure	71 3/4	72 1/4	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	
													62
Ventilation	73 3/4	74 1/4	7.0	7.9	8.8	9.7	10.6	11.6	12.5	13.4	25.6		
												Daylight	12.8
Design Pressure	73 3/4	74 1/4	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Test Window Dimensions:

75 3/4" x 77"	DP-30	68" x 77"	DP-50
75" x 59"	DP-50	68" x 65"	DP-50
68" x 71" Cottage	DP-35	76" x 71" Cottage	DP-30

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Daylight,ion and Design Pressure

Twin Window Units

Date: 09-May-07

Window				Width 210 to 310							
Height	Call Out	Unit Dimension		30	32	34	36	38	310	40	
	30	35 3/4	36 1/4	Rough Opening		30		32		34	
				Ventilation	Daylight	DP-30/DP-50	DP-30	DP-30	DP-30	DP-30	DP-30
				71 3/4	75 3/4	79 3/4	83 3/4	87 3/4	91 3/4	95 3/4	
				72 1/4	76 1/4	80 1/4	84 1/4	88 1/4	92 1/4	96 1/4	
				6.1	6.5	6.9	7.3	7.7	8.1	8.5	
				11.7	12.5	13.3	14.1	14.9	15.6	16.4	
				DP-30/DP-50	DP-30	NT	NT	NT	NT	NT	
				6.5	7.0	7.4	7.8	8.2	8.6	9.1	
				12.6	13.4	14.2	15.1	15.9	16.8	17.6	
				DP-30/DP-50	DP-30	NT	NT	NT	NT	NT	
				7.8	8.3	8.8	9.3	9.8	10.4	10.9	
				15.0	16.0	17.1	18.1	19.1	20.1	21.1	
				DP-30/DP-50	DP-30	NT	NT	NT	NT	NT	
				8.7	9.3	9.8	10.4	10.9	11.5	12.1	
				16.7	17.8	18.9	20.1	21.2	22.3	23.4	
				DP-30/DP-50	DP-30	NT	NT	NT	NT	NT	
				9.1	9.7	10.3	10.9	11.5	12.1	12.7	
				17.5	18.7	19.9	21.1	22.2	23.4	24.6	
				DP-30/DP-50	DP-30	NT	NT	NT	NT	NT	
				10.0	10.6	11.3	11.9	12.6	13.2	13.9	
				19.2	20.5	21.8	23.0	24.3	25.6	26.9	
				DP-30/DP-50	DP-30	NT	NT	NT	NT	NT	
				11.3	12.0	12.7	13.5	14.2	14.9	15.6	
				21.7	23.1	24.6	26.0	27.5	28.9	30.4	
				DP-30	DP-30	NT	NT	NT	NT	NT	
				11.7	12.5	13.2	14.0	14.7	15.5	16.2	
				22.5	24.0	25.5	27.0	28.5	30.0	31.6	
				DP-30	DP-30	NT	NT	NT	NT	NT	
				12.6	13.4	14.2	15.0	15.8	16.6	17.4	
				24.2	25.8	27.4	29.0	30.6	32.3	33.9	
				DP-30	DP-30	NT	NT	NT	NT	NT	
				13.9	14.8	15.7	16.6	17.5	18.3	19.2	
				26.7	28.4	30.2	32.0	33.8	35.6	37.4	
				DP-30	DP-30	NT	NT	NT	NT	NT	
				11.3	12.0	12.7	13.5	14.2	14.9	15.6	
				26.5	28.3	30.1	31.8	33.6	35.4	37.2	
				NT	NT	NT	NT	NT	NT	NT	
				11.3	12.0	12.7	13.5	14.2	14.9	15.6	
				26.7	28.4	30.2	32.0	33.8	35.6	37.4	
				NT	NT	NT	NT	NT	NT	NT	
				14.3	15.2	16.2	17.1	18.0	18.9	-	
				27.5	29.3	31.2	33.0	34.9	36.7	-	
				DP-30	DP-30	NT	NT	NT	NT	-	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Test Window Dimensions:

75 3/4" x 77"	DP-30	68" x 77"	DP-50
75" x 59"	DP-50	68" x 65"	DP-50
68" x 71" Cottage	DP-35	76" x 71" Cottage	DP-30

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Triple Window Units

Date: 09-May-05

Window				Width 18 to 210							
Height	Call Out	Unit Dimension	Rough Opening	18	110	20	22	24	26	28	210
				59 7/8	65 7/8	71 7/8	77 7/8	83 7/8	89 7/8	95 7/8	101 7/8
				60 3/8	66 3/8	72 3/8	78 3/8	84 3/8	90 3/8	96 3/8	102 3/8
30	35 3/4	36 1/4	Ventilation	4.5	5.0	5.6	6.2	6.8	7.4	8.0	8.6
			Daylight	8.2	9.3	10.5	11.7	12.9	14.1	15.2	16.4
32	37 3/4	38 1/4	Ventilation	4.8	5.4	6.0	6.7	7.3	7.9	8.5	9.2
			Daylight	8.7	10.0	11.3	12.5	13.8	15.0	16.3	17.6
38	43 3/4	44 1/4	Ventilation	5.7	6.5	7.2	8.0	8.7	9.5	10.2	11.0
			Daylight	10.5	12.0	13.5	15.0	16.5	18.0	19.5	21.1
40	47 3/4	48 1/4	Ventilation	6.3	7.2	8.0	8.9	9.7	10.5	11.4	12.2
			Daylight	11.6	13.3	15.0	16.7	18.3	20.0	21.7	23.4
42	49 3/4	50 1/4	Ventilation	6.7	7.5	8.4	9.3	10.2	11.1	11.9	12.8
			Daylight	12.2	14.0	15.7	17.5	19.3	21.0	22.8	24.5
46	53 3/4	54 1/4	Ventilation	7.3	8.3	9.2	10.2	11.1	12.1	13.1	14.0
			Daylight	13.4	15.3	17.2	19.2	21.1	23.0	24.9	26.9
50	59 3/4	60 1/4	Ventilation	8.2	9.3	10.4	11.5	12.6	13.7	14.8	15.9
			Daylight	15.1	17.3	19.5	21.6	23.8	26.0	28.2	30.3
52	61 3/4	62 1/4	Ventilation	8.5	9.7	10.8	11.9	13.1	14.2	15.3	16.5
			Daylight	15.7	17.9	20.2	22.5	24.7	27.0	29.2	31.5
56	65 3/4	66 1/4	Ventilation	9.2	10.4	11.6	12.8	14.0	15.2	16.5	17.7
			Daylight	16.8	19.3	21.7	24.1	26.5	29.0	31.4	33.8
60	71 3/4	72 1/4	Ventilation	10.1	11.5	12.8	14.1	15.5	16.8	18.2	19.5
			Daylight	18.6	21.2	23.9	26.6	29.3	32.0	34.6	37.3
60 Cottage	71 3/4	72 1/4	Ventilation	8.2	9.3	10.4	11.5	12.6	13.7	14.8	15.9
			Daylight	18.6	21.2	23.9	26.6	29.3	32.0	34.6	37.3
60 Oriel	71 3/4	72 1/4	Ventilation	8.2	9.3	10.4	11.5	12.6	13.7	14.8	15.9
			Daylight	18.6	21.2	23.9	26.6	29.3	32.0	34.6	37.3
62	73 3/4	74 1/4	Ventilation	10.4	11.8	13.2	14.6	16.0	17.3	18.7	20.1
			Daylight	19.2	21.9	24.7	27.4	30.2	33.0	35.7	38.5

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

113 7/8" x 57" DP-35 113 7/8" x 57" DP-50

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Seven D Industries, L.P.

Series 5800 Double Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Triple Window Units

Date: 09-May-05

Window				Width 30 to 40							
Height	Call Out	Unit Dimension		30	32	34	36	38	310	40	
	30	35 3/4	Rough Opening	107 7/8	113 7/8	119 7/8	125 7/8	131 7/8	137 7/8	143 7/8	
			36 1/4	108 3/8	114 3/8	120 3/8	126 3/8	132 3/8	138 3/8	144 3/8	
30	35 3/4	36 1/4	Ventilation	9.2	9.7	10.3	10.9	11.5	12.1	12.7	
			Daylight	17.6	18.8	19.9	21.1	22.3	23.5	24.6	
32	37 3/4	38 1/4	Ventilation	9.8	10.4	11.1	11.7	12.3	13.0	13.6	
			Daylight	18.8	20.1	21.3	22.6	23.9	25.1	26.4	
38	43 3/4	44 1/4	Ventilation	11.8	12.5	13.3	14.0	14.8	15.5	16.3	
			Daylight	22.6	24.1	25.6	27.1	28.6	30.1	31.6	
40	47 3/4	48 1/4	Ventilation	13.0	13.9	14.7	15.6	16.4	-	-	
			Daylight	25.1	26.7	28.4	30.1	31.8	-	-	
42	49 3/4	50 1/4	Ventilation	13.7	14.6	15.5	16.3	-	-	-	
			Daylight	26.3	28.1	29.8	31.6	-	-	-	
46	53 3/4	54 1/4	Ventilation	15.0	16.0	16.9	-	-	-	-	
			Daylight	28.8	30.7	32.6	-	-	-	-	
50	59 3/4	60 1/4	Ventilation	17.0	-	-	-	-	-	-	
			Daylight	32.5	-	-	-	-	-	-	
52	61 3/4	62 1/4	Ventilation	-	-	-	-	-	-	-	
			Daylight	-	-	-	-	-	-	-	
56	65 3/4	66 1/4	Ventilation	-	-	-	-	-	-	-	
			Daylight	-	-	-	-	-	-	-	
60	71 3/4	72 1/4	Ventilation	-	-	-	-	-	-	-	
			Daylight	-	-	-	-	-	-	-	
60 Cottage	71 3/4	72 1/4	Ventilation	-	-	-	-	-	-	-	
			Daylight	-	-	-	-	-	-	-	
60 Oriel	71 3/4	72 1/4	Ventilation	-	-	-	-	-	-	-	
			Daylight	-	-	-	-	-	-	-	
62	73 3/4	74 1/4	Ventilation	-	-	-	-	-	-	-	
			Daylight	-	-	-	-	-	-	-	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

113 7/8" x 57"

DP-35

113 7/8" x 57"

DP-50

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Seven D Industries, L.P.

Series 5800 Double Hung

Screen Dimensions

Code	Unit Dimensions		Screen Dimensions		Code	Unit Dimensions		Screen Dimensions	
	Width	Height	Width	Height		Width	Height	Width	Height
1830	19 5/8	x 35 3/4	15 15/16	x 33 3/16	2430	27 5/8	x 35 3/4	23 15/16	x 33 3/16
1832	19 5/8	x 37 3/4	15 15/16	x 35 3/16	2432	27 5/8	x 37 3/4	23 15/16	x 35 3/16
1838	19 5/8	x 43 3/4	15 15/16	x 41 3/16	2438	27 5/8	x 43 3/4	23 15/16	x 41 3/16
1840	19 5/8	x 47 3/4	15 15/16	x 45 3/16	2440	27 5/8	x 47 3/4	23 15/16	x 45 3/16
1842	19 5/8	x 49 3/4	15 15/16	x 47 3/16	2442	27 5/8	x 49 3/4	23 15/16	x 47 3/16
1846	19 5/8	x 53 3/4	15 15/16	x 51 3/16	2446	27 5/8	x 53 3/4	23 15/16	x 51 3/16
1850	19 5/8	x 59 3/4	15 15/16	x 57 3/16	2450	27 5/8	x 59 3/4	23 15/16	x 57 3/16
1852	19 5/8	x 61 3/4	15 15/16	x 59 3/16	2452	27 5/8	x 61 3/4	23 15/16	x 59 3/16
1856	19 5/8	x 65 3/4	15 15/16	x 63 3/16	2456	27 5/8	x 65 3/4	23 15/16	x 63 3/16
1860	19 5/8	x 71 3/4	15 15/16	x 69 3/16	2460	27 5/8	x 71 3/4	23 15/16	x 69 3/16
1860c	19 5/8	x 71 3/4	15 15/16	x 69 3/16	2460c	27 5/8	x 71 3/4	23 15/16	x 69 3/16
1860o	19 5/8	x 71 3/4	15 15/16	x 69 3/16	2460o	27 5/8	x 71 3/4	23 15/16	x 69 3/16
1862	19 5/8	x 73 3/4	15 15/16	x 71 3/16	2462	27 5/8	x 73 3/4	23 15/16	x 71 3/16
11030	21 5/8	x 35 3/4	17 15/16	x 33 3/16	2630	29 5/8	x 35 3/4	25 15/16	x 33 3/16
11032	21 5/8	x 37 3/4	17 15/16	x 35 3/16	2632	29 5/8	x 37 3/4	25 15/16	x 35 3/16
11038	21 5/8	x 43 3/4	17 15/16	x 41 3/16	2638	29 5/8	x 43 3/4	25 15/16	x 41 3/16
11040	21 5/8	x 47 3/4	17 15/16	x 45 3/16	2640	29 5/8	x 47 3/4	25 15/16	x 45 3/16
11042	21 5/8	x 49 3/4	17 15/16	x 47 3/16	2642	29 5/8	x 49 3/4	25 15/16	x 47 3/16
11046	21 5/8	x 53 3/4	17 15/16	x 51 3/16	2646	29 5/8	x 53 3/4	25 15/16	x 51 3/16
11050	21 5/8	x 59 3/4	17 15/16	x 57 3/16	2650	29 5/8	x 59 3/4	25 15/16	x 57 3/16
11052	21 5/8	x 61 3/4	17 15/16	x 59 3/16	2652	29 5/8	x 61 3/4	25 15/16	x 59 3/16
11056	21 5/8	x 65 3/4	17 15/16	x 63 3/16	2656	29 5/8	x 65 3/4	25 15/16	x 63 3/16
11060	21 5/8	x 71 3/4	17 15/16	x 69 3/16	2660	29 5/8	x 71 3/4	25 15/16	x 69 3/16
11060c	21 5/8	x 71 3/4	17 15/16	x 69 3/16	2660c	29 5/8	x 71 3/4	25 15/16	x 69 3/16
11060o	21 5/8	x 71 3/4	17 15/16	x 69 3/16	2660o	29 5/8	x 71 3/4	25 15/16	x 69 3/16
11062	21 5/8	x 73 3/4	17 15/16	x 71 3/16	2662	29 5/8	x 73 3/4	25 15/16	x 71 3/16
2030	23 5/8	x 35 3/4	19 15/16	x 33 3/16	2830	31 5/8	x 35 3/4	27 15/16	x 33 3/16
2032	23 5/8	x 37 3/4	19 15/16	x 35 3/16	2832	31 5/8	x 37 3/4	27 15/16	x 35 3/16
2038	23 5/8	x 43 3/4	19 15/16	x 41 3/16	2838	31 5/8	x 43 3/4	27 15/16	x 41 3/16
2040	23 5/8	x 47 3/4	19 15/16	x 45 3/16	2840	31 5/8	x 47 3/4	27 15/16	x 45 3/16
2042	23 5/8	x 49 3/4	19 15/16	x 47 3/16	2842	31 5/8	x 49 3/4	27 15/16	x 47 3/16
2046	23 5/8	x 53 3/4	19 15/16	x 51 3/16	2846	31 5/8	x 53 3/4	27 15/16	x 51 3/16
2050	23 5/8	x 59 3/4	19 15/16	x 57 3/16	2850	31 5/8	x 59 3/4	27 15/16	x 57 3/16
2052	23 5/8	x 61 3/4	19 15/16	x 59 3/16	2852	31 5/8	x 61 3/4	27 15/16	x 59 3/16
2056	23 5/8	x 65 3/4	19 15/16	x 63 3/16	2856	31 5/8	x 65 3/4	27 15/16	x 63 3/16
2060	23 5/8	x 71 3/4	19 15/16	x 69 3/16	2860	31 5/8	x 71 3/4	27 15/16	x 69 3/16
2060c	23 5/8	x 71 3/4	19 15/16	x 69 3/16	2860c	31 5/8	x 71 3/4	27 15/16	x 69 3/16
2060o	23 5/8	x 71 3/4	19 15/16	x 69 3/16	2860o	31 5/8	x 71 3/4	27 15/16	x 69 3/16
2062	23 5/8	x 73 3/4	19 15/16	x 71 3/16	2862	31 5/8	x 73 3/4	27 15/16	x 71 3/16
2230	25 5/8	x 35 3/4	21 15/16	x 33 3/16	21030	33 5/8	x 35 3/4	29 15/16	x 33 3/16
2232	25 5/8	x 37 3/4	21 15/16	x 35 3/16	21032	33 5/8	x 37 3/4	29 15/16	x 35 3/16
2238	25 5/8	x 43 3/4	21 15/16	x 41 3/16	21038	33 5/8	x 43 3/4	29 15/16	x 41 3/16
2240	25 5/8	x 47 3/4	21 15/16	x 45 3/16	21040	33 5/8	x 47 3/4	29 15/16	x 45 3/16
2242	25 5/8	x 49 3/4	21 15/16	x 47 3/16	21042	33 5/8	x 49 3/4	29 15/16	x 47 3/16
2246	25 5/8	x 53 3/4	21 15/16	x 51 3/16	21046	33 5/8	x 53 3/4	29 15/16	x 51 3/16
2250	25 5/8	x 59 3/4	21 15/16	x 57 3/16	21050	33 5/8	x 59 3/4	29 15/16	x 57 3/16
2252	25 5/8	x 61 3/4	21 15/16	x 59 3/16	21052	33 5/8	x 61 3/4	29 15/16	x 59 3/16
2256	25 5/8	x 65 3/4	21 15/16	x 63 3/16	21056	33 5/8	x 65 3/4	29 15/16	x 63 3/16
2260	25 5/8	x 71 3/4	21 15/16	x 69 3/16	21060	33 5/8	x 71 3/4	29 15/16	x 69 3/16
2260c	25 5/8	x 71 3/4	21 15/16	x 69 3/16	21060c	33 5/8	x 71 3/4	29 15/16	x 69 3/16
2260o	25 5/8	x 71 3/4	21 15/16	x 69 3/16	21060o	33 5/8	x 71 3/4	29 15/16	x 69 3/16
2262	25 5/8	x 73 3/4	21 15/16	x 71 3/16	21062	33 5/8	x 73 3/4	29 15/16	x 71 3/16

Seven D Industries, L.P.

Series 5800 Double Hung

Screen Dimensions

Code	Unit Dimensions		Screen Dimensions		Code	Unit Dimensions		Screen Dimensions	
	Width	Height	Width	Height		Width	Height	Width	Height
3030	35 5/8	x 35 3/4	31 15/16	x 33 3/16	3830	43 5/8	x 35 3/4	39 15/16	x 33 3/16
3032	35 5/8	x 37 3/4	31 15/16	x 35 3/16	3832	43 5/8	x 37 3/4	39 15/16	x 35 3/16
3038	35 5/8	x 43 3/4	31 15/16	x 41 3/16	3838	43 5/8	x 43 3/4	39 15/16	x 41 3/16
3040	35 5/8	x 47 3/4	31 15/16	x 45 3/16	3840	43 5/8	x 47 3/4	39 15/16	x 45 3/16
3042	35 5/8	x 49 3/4	31 15/16	x 47 3/16	3842	43 5/8	x 49 3/4	39 15/16	x 47 3/16
3046	35 5/8	x 53 3/4	31 15/16	x 51 3/16	3846	43 5/8	x 53 3/4	39 15/16	x 51 3/16
3050	35 5/8	x 59 3/4	31 15/16	x 57 3/16	3850	43 5/8	x 59 3/4	39 15/16	x 57 3/16
3052	35 5/8	x 61 3/4	31 15/16	x 59 3/16	3852	43 5/8	x 61 3/4	39 15/16	x 59 3/16
3056	35 5/8	x 65 3/4	31 15/16	x 63 3/16	3856	43 5/8	x 65 3/4	39 15/16	x 63 3/16
3060	35 5/8	x 71 3/4	31 15/16	x 69 3/16	3860	43 5/8	x 71 3/4	39 15/16	x 69 3/16
3060c	35 5/8	x 71 3/4	31 15/16	x 69 3/16	3860c	43 5/8	x 71 3/4	39 15/16	x 69 3/16
3060o	35 5/8	x 71 3/4	31 15/16	x 69 3/16	3860o	43 5/8	x 71 3/4	39 15/16	x 69 3/16
3062	35 5/8	x 73 3/4	31 15/16	x 71 3/16	3862	43 5/8	x 73 3/4	39 15/16	x 71 3/16
3230	37 5/8	x 35 3/4	33 15/16	x 33 3/16	31030	45 5/8	x 35 3/4	41 15/16	x 33 3/16
3232	37 5/8	x 37 3/4	33 15/16	x 35 3/16	31032	45 5/8	x 37 3/4	41 15/16	x 35 3/16
3238	37 5/8	x 43 3/4	33 15/16	x 41 3/16	31038	45 5/8	x 43 3/4	41 15/16	x 41 3/16
3240	37 5/8	x 47 3/4	33 15/16	x 45 3/16	31040	45 5/8	x 47 3/4	41 15/16	x 45 3/16
3242	37 5/8	x 49 3/4	33 15/16	x 47 3/16	31042	45 5/8	x 49 3/4	41 15/16	x 47 3/16
3246	37 5/8	x 53 3/4	33 15/16	x 51 3/16	31046	45 5/8	x 53 3/4	41 15/16	x 51 3/16
3250	37 5/8	x 59 3/4	33 15/16	x 57 3/16	31050	45 5/8	x 59 3/4	41 15/16	x 57 3/16
3252	37 5/8	x 61 3/4	33 15/16	x 59 3/16	31052	45 5/8	x 61 3/4	41 15/16	x 59 3/16
3256	37 5/8	x 65 3/4	33 15/16	x 63 3/16	31056	45 5/8	x 65 3/4	41 15/16	x 63 3/16
3260	37 5/8	x 71 3/4	33 15/16	x 69 3/16	31060	45 5/8	x 71 3/4	41 15/16	x 69 3/16
3260c	37 5/8	x 71 3/4	33 15/16	x 69 3/16	31060c	45 5/8	x 71 3/4	41 15/16	x 69 3/16
3260o	37 5/8	x 71 3/4	33 15/16	x 69 3/16	31060o	45 5/8	x 71 3/4	41 15/16	x 69 3/16
3262	37 5/8	x 73 3/4	33 15/16	x 71 3/16	31062	45 5/8	x 73 3/4	41 15/16	x 71 3/16
3430	39 5/8	x 35 3/4	35 15/16	x 33 3/16	4030	47 5/8	x 35 3/4	43 15/16	x 33 3/16
3432	39 5/8	x 37 3/4	35 15/16	x 35 3/16	4032	47 5/8	x 37 3/4	43 15/16	x 35 3/16
3438	39 5/8	x 43 3/4	35 15/16	x 41 3/16	4038	47 5/8	x 43 3/4	43 15/16	x 41 3/16
3440	39 5/8	x 47 3/4	35 15/16	x 45 3/16	4040	47 5/8	x 47 3/4	43 15/16	x 45 3/16
3442	39 5/8	x 49 3/4	35 15/16	x 47 3/16	4042	47 5/8	x 49 3/4	43 15/16	x 47 3/16
3446	39 5/8	x 53 3/4	35 15/16	x 51 3/16	4046	47 5/8	x 53 3/4	43 15/16	x 51 3/16
3450	39 5/8	x 59 3/4	35 15/16	x 57 3/16	4050	47 5/8	x 59 3/4	43 15/16	x 57 3/16
3452	39 5/8	x 61 3/4	35 15/16	x 59 3/16	4052	47 5/8	x 61 3/4	43 15/16	x 59 3/16
3456	39 5/8	x 65 3/4	35 15/16	x 63 3/16	4056	47 5/8	x 65 3/4	43 15/16	x 63 3/16
3460	39 5/8	x 71 3/4	35 15/16	x 69 3/16	4060	47 5/8	x 71 3/4	43 15/16	x 69 3/16
3460c	39 5/8	x 71 3/4	35 15/16	x 69 3/16	4060c	47 5/8	x 71 3/4	43 15/16	x 69 3/16
3460o	39 5/8	x 71 3/4	35 15/16	x 69 3/16	4060o	47 5/8	x 71 3/4	43 15/16	x 69 3/16
3462	39 5/8	x 73 3/4	35 15/16	x 71 3/16	4062	47 5/8	x 73 3/4	43 15/16	x 71 3/16
3630	41 5/8	x 35 3/4	37 15/16	x 33 3/16					
3632	41 5/8	x 37 3/4	37 15/16	x 35 3/16					
3638	41 5/8	x 43 3/4	37 15/16	x 41 3/16					
3640	41 5/8	x 47 3/4	37 15/16	x 45 3/16					
3642	41 5/8	x 49 3/4	37 15/16	x 47 3/16					
3646	41 5/8	x 53 3/4	37 15/16	x 51 3/16					
3650	41 5/8	x 59 3/4	37 15/16	x 57 3/16					
3652	41 5/8	x 61 3/4	37 15/16	x 59 3/16					
3656	41 5/8	x 65 3/4	37 15/16	x 63 3/16					
3660	41 5/8	x 71 3/4	37 15/16	x 69 3/16					
3660c	41 5/8	x 71 3/4	37 15/16	x 69 3/16					
3660o	41 5/8	x 71 3/4	37 15/16	x 69 3/16					
3662	41 5/8	x 73 3/4	37 15/16	x 71 3/16					

Seven D Industries, L.P.
Series 5800 Double Hung

Thermal Performance Specifications

SSB Glazing

Glass Type	U-Value	SHGC	VT	w/ Grid	
				SHGC	VT
3/4" IG -Clear/air/Clear	.48	.60	.63	.54	.56
3/4" IG – Clear/90% Argon/Low-E	.32	.37	.53	.33	.47

DSB Glazing

Glass Type	U-Value	SHGC	VT	w/ Grid	
				SHGC	VT
3/4" IG -Clear/air/Clear	.48	.59	.62	.53	.56
3/4" IG – Clear/90% Argon/Low-E	.31	.37	.52	.33	.47

Notes: Actual window dimensions have not effect on the Thermal Performance Rating, as the test criteria is based on a per square foot unit.

Seven D Industries, Series 5700 Double Hung windows utilizing Low-E Glass with Argon Fill, meet all requirements for Energy Star compliance.

10/19/2006

Seven D Industries, L.P. **Series 5800 Double Hung**

Window Width: 15
Window Height: 52

Ventilation Area: 1.568 sq ft
Daylight Area: 2.833 sq ft