

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Single Window Units

Date:

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear C	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage		Equal
1830	19 5/8	x 35 3/4	20 1/8	x 36 1/4	DP-50	-	-	2.9	1.5	-	-	
1832	19 5/8	x 37 3/4	20 1/8	x 38 1/4	DP-50	-	-	3.1	1.6	-	-	
1838	19 5/8	x 43 3/4	20 1/8	x 44 1/4	DP-50	-	-	3.7	1.9	-	-	
1840	19 5/8	x 47 3/4	20 1/8	x 48 1/4	DP-50	-	-	4.2	2.1	-	-	
1842	19 5/8	x 49 3/4	20 1/8	x 50 1/4	DP-50	-	-	4.4	2.2	-	-	
1846	19 5/8	x 53 3/4	20 1/8	x 54 1/4	DP-50	-	-	4.8	2.4	-	-	
1850	19 5/8	x 59 3/4	20 1/8	x 60 1/4	DP-50	-	-	5.4	2.7	-	-	
1852	19 5/8	x 61 3/4	20 1/8	x 62 1/4	DP-50	-	-	5.6	2.8	-	-	
1856	19 5/8	x 65 3/4	20 1/8	x 66 1/4	DP-35	-	DP-50	6.0	3.1	-	-	
1860	19 5/8	x 71 3/4	20 1/8	x 72 1/4	DP-35	-	DP-50	6.6	3.4	-	-	
1860c	19 5/8	x 71 3/4	20 1/8	x 72 1/4	-	NT	-	6.6	-	2.7	-	
1860o	19 5/8	x 71 3/4	20 1/8	x 72 1/4	-	NT	-	6.6	-	2.7	-	
1862	19 5/8	x 73 3/4	20 1/8	x 74 1/4	DP-35	-	DP-50	6.8	3.5	-	-	
11030	21 5/8	x 35 3/4	22 1/8	x 36 1/4	DP-50	-	-	3.3	1.7	-	-	
11032	21 5/8	x 37 3/4	22 1/8	x 38 1/4	DP-50	-	-	3.5	1.8	-	-	
11038	21 5/8	x 43 3/4	22 1/8	x 44 1/4	DP-50	-	-	4.2	2.2	-	-	
11040	21 5/8	x 47 3/4	22 1/8	x 48 1/4	DP-50	-	-	4.7	2.4	-	-	
11042	21 5/8	x 49 3/4	22 1/8	x 50 1/4	DP-50	-	-	4.9	2.5	-	-	
11046	21 5/8	x 53 3/4	22 1/8	x 54 1/4	DP-50	-	-	5.4	2.7	-	-	
11050	21 5/8	x 59 3/4	22 1/8	x 60 1/4	DP-50	-	-	6.1	3.1	-	-	
11052	21 5/8	x 61 3/4	22 1/8	x 62 1/4	DP-50	-	-	6.3	3.2	-	-	
11056	21 5/8	x 65 3/4	22 1/8	x 66 1/4	DP-35	-	DP-50	6.8	3.5	-	-	
11060	21 5/8	x 71 3/4	22 1/8	x 72 1/4	DP-35	-	DP-50	7.5	3.8	-	-	
11060c	21 5/8	x 71 3/4	22 1/8	x 72 1/4	-	NT	-	7.5	-	3.1	-	
11060o	21 5/8	x 71 3/4	22 1/8	x 72 1/4	-	NT	-	7.5	-	3.1	-	
11062	21 5/8	x 73 3/4	22 1/8	x 74 1/4	DP-35	-	DP-50	7.7	3.9	-	-	
2030	23 5/8	x 35 3/4	24 1/8	x 36 1/4	DP-50	-	-	3.7	1.9	-	-	
2032	23 5/8	x 37 3/4	24 1/8	x 38 1/4	DP-50	-	-	4.0	2.0	-	-	
2038	23 5/8	x 43 3/4	24 1/8	x 44 1/4	DP-50	-	-	4.8	2.4	-	-	
2040	23 5/8	x 47 3/4	24 1/8	x 48 1/4	DP-50	-	-	5.3	2.7	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area

Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 57"

Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Single Window Units

Date:

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear C	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage		
2042	23 5/8	x 49 3/4	24 1/8	x 50 1/4	DP-50	-	-	5.5	2.8	-	-	
2046	23 5/8	x 53 3/4	24 1/8	x 54 1/4	DP-50	-	-	6.1	3.1	-	-	
2050	23 5/8	x 59 3/4	24 1/8	x 60 1/4	DP-50	-	-	6.8	3.5	-	-	
2052	23 5/8	x 61 3/4	24 1/8	x 62 1/4	DP-50	-	-	7.1	3.6	-	-	
2056	23 5/8	x 65 3/4	24 1/8	x 66 1/4	DP-35	-	DP-50	7.6	3.9	-	-	
2060	23 5/8	x 71 3/4	24 1/8	x 72 1/4	DP-35	-	DP-50	8.4	4.3	-	-	
2060c	23 5/8	x 71 3/4	24 1/8	x 72 1/4	-	NT	-	8.4	-	3.5	-	
2060o	23 5/8	x 71 3/4	24 1/8	x 72 1/4	-	NT	-	8.4	-	3.5	-	
2062	23 5/8	x 73 3/4	24 1/8	x 74 1/4	DP-35	-	DP-50	8.7	4.4	-	-	
2230	25 5/8	x 35 3/4	26 1/8	x 36 1/4	DP-50	-	-	4.1	2.1	-	-	
2232	25 5/8	x 37 3/4	26 1/8	x 38 1/4	DP-50	-	-	4.4	2.2	-	-	
2238	25 5/8	x 43 3/4	26 1/8	x 44 1/4	DP-50	-	-	5.3	2.7	-	-	
2240	25 5/8	x 47 3/4	26 1/8	x 48 1/4	DP-50	-	-	5.8	2.9	-	-	
2242	25 5/8	x 49 3/4	26 1/8	x 50 1/4	DP-50	-	-	6.1	3.1	-	-	
2246	25 5/8	x 53 3/4	26 1/8	x 54 1/4	DP-50	-	-	6.7	3.4	-	-	
2250	25 5/8	x 59 3/4	26 1/8	x 60 1/4	DP-50	-	-	7.6	3.8	-	-	
2252	25 5/8	x 61 3/4	26 1/8	x 62 1/4	DP-50	-	-	7.9	4.0	-	-	
2256	25 5/8	x 65 3/4	26 1/8	x 66 1/4	DP-35	-	DP-50	8.4	4.3	-	-	
2260	25 5/8	x 71 3/4	26 1/8	x 72 1/4	DP-35	-	DP-50	9.3	4.7	-	-	
2260c	25 5/8	x 71 3/4	26 1/8	x 72 1/4	-	NT	-	9.3	-	3.8	-	
2260o	25 5/8	x 71 3/4	26 1/8	x 72 1/4	-	NT	-	9.3	-	3.8	-	
2262	25 5/8	x 73 3/4	26 1/8	x 74 1/4	DP-35	-	DP-50	9.6	4.9	-	-	
2430	27 5/8	x 35 3/4	28 1/8	x 36 1/4	DP-50	-	-	4.5	2.3	-	-	
2432	27 5/8	x 37 3/4	28 1/8	x 38 1/4	DP-50	-	-	4.8	2.4	-	-	
2438	27 5/8	x 43 3/4	28 1/8	x 44 1/4	DP-50	-	-	5.8	2.9	-	-	
2440	27 5/8	x 47 3/4	28 1/8	x 48 1/4	DP-50	-	-	6.4	3.2	-	-	
2442	27 5/8	x 49 3/4	28 1/8	x 50 1/4	DP-50	-	-	6.7	3.4	-	-	
2446	27 5/8	x 53 3/4	28 1/8	x 54 1/4	DP-50	-	-	7.3	3.7	-	-	
2450	27 5/8	x 59 3/4	28 1/8	x 60 1/4	DP-50	-	-	8.3	4.2	-	-	
2452	27 5/8	x 61 3/4	28 1/8	x 62 1/4	DP-50	-	-	8.6	4.4	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Single Window Units

Date:

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear C	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage		
2456	27 5/8	x 65 3/4	28 1/8	x 66 1/4	DP-35	-	DP-50	9.2	4.7	-	-	
2460	27 5/8	x 71 3/4	28 1/8	x 72 1/4	DP-35	-	DP-50	10.2	5.2	-	-	
2460c	27 5/8	x 71 3/4	28 1/8	x 72 1/4	-	NT	-	10.2	-	4.2	-	
2460o	27 5/8	x 71 3/4	28 1/8	x 72 1/4	-	NT	-	10.2	-	4.2	-	
2462	27 5/8	x 73 3/4	28 1/8	x 74 1/4	DP-35	-	DP-50	10.5	5.3	-	-	
2630	29 5/8	x 35 3/4	30 1/8	x 36 1/4	DP-50	-	-	4.9	2.5	-	-	
2632	29 5/8	x 37 3/4	30 1/8	x 38 1/4	DP-50	-	-	5.2	2.6	-	-	
2638	29 5/8	x 43 3/4	30 1/8	x 44 1/4	DP-50	-	-	6.3	3.2	-	-	
2640	29 5/8	x 47 3/4	30 1/8	x 48 1/4	DP-50	-	-	7.0	3.5	-	-	
2642	29 5/8	x 49 3/4	30 1/8	x 50 1/4	DP-50	-	-	7.3	3.7	-	-	
2646	29 5/8	x 53 3/4	30 1/8	x 54 1/4	DP-50	-	-	8.0	4.0	-	-	
2650	29 5/8	x 59 3/4	30 1/8	x 60 1/4	DP-50	-	-	9.0	4.6	-	-	
2652	29 5/8	x 61 3/4	30 1/8	x 62 1/4	DP-50	-	-	9.4	4.7	-	-	
2656	29 5/8	x 65 3/4	30 1/8	x 66 1/4	DP-35	-	DP-50	10.1	5.1	-	-	
2660	29 5/8	x 71 3/4	30 1/8	x 72 1/4	DP-35	-	DP-50	11.1	5.6	-	-	
2660c	29 5/8	x 71 3/4	30 1/8	x 72 1/4	-	NT	-	11.1	-	4.6	-	
2660o	29 5/8	x 71 3/4	30 1/8	x 72 1/4	-	NT	-	11.1	-	4.6	-	
2662	29 5/8	x 73 3/4	30 1/8	x 74 1/4	DP-35	-	DP-50	11.4	5.8	-	Yes	
2830	31 5/8	x 35 3/4	32 1/8	x 36 1/4	DP-50	-	-	5.3	2.7	-	-	
2832	31 5/8	x 37 3/4	32 1/8	x 38 1/4	DP-50	-	-	5.7	2.8	-	-	
2838	31 5/8	x 43 3/4	32 1/8	x 44 1/4	DP-50	-	-	6.8	3.4	-	-	
2840	31 5/8	x 47 3/4	32 1/8	x 48 1/4	DP-50	-	-	7.5	3.8	-	-	
2842	31 5/8	x 49 3/4	32 1/8	x 50 1/4	DP-50	-	-	7.9	4.0	-	-	
2846	31 5/8	x 53 3/4	32 1/8	x 54 1/4	DP-50	-	-	8.6	4.4	-	-	
2850	31 5/8	x 59 3/4	32 1/8	x 60 1/4	DP-50	-	-	9.8	4.9	-	-	
2852	31 5/8	x 61 3/4	32 1/8	x 62 1/4	DP-50	-	-	10.1	5.1	-	-	
2856	31 5/8	x 65 3/4	32 1/8	x 66 1/4	DP-35	-	DP-50	10.9	5.5	-	-	
2860	31 5/8	x 71 3/4	32 1/8	x 72 1/4	DP-35	-	DP-50	12.0	6.0	-	Yes	
2860c	31 5/8	x 71 3/4	32 1/8	x 72 1/4	-	NT	-	12.0	-	4.9	-	
2860o	31 5/8	x 71 3/4	32 1/8	x 72 1/4	-	NT	-	12.0	-	4.9	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Single Window Units

Date:

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear C	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage		
2862	31 5/8	x 73 3/4	32 1/8	x 74 1/4	DP-35	-	DP-50	12.4	6.2	-	Yes	
21030	33 5/8	x 35 3/4	34 1/8	x 36 1/4	DP-50	-	-	5.7	2.9	-	-	
21032	33 5/8	x 37 3/4	34 1/8	x 38 1/4	DP-50	-	-	6.1	3.1	-	-	
21038	33 5/8	x 43 3/4	34 1/8	x 44 1/4	DP-50	-	-	7.3	3.7	-	-	
21040	33 5/8	x 47 3/4	34 1/8	x 48 1/4	DP-50	-	-	8.1	4.1	-	-	
21042	33 5/8	x 49 3/4	34 1/8	x 50 1/4	DP-50	-	-	8.5	4.3	-	-	
21046	33 5/8	x 53 3/4	34 1/8	x 54 1/4	DP-50	-	-	9.3	4.7	-	-	
21050	33 5/8	x 59 3/4	34 1/8	x 60 1/4	DP-50	-	-	10.5	5.3	-	-	
21052	33 5/8	x 61 3/4	34 1/8	x 62 1/4	DP-50	-	-	10.9	5.5	-	-	
21056	33 5/8	x 65 3/4	34 1/8	x 66 1/4	DP-35	-	DP-50	11.7	5.9	-	Yes	
21060	33 5/8	x 71 3/4	34 1/8	x 72 1/4	DP-35	-	DP-50	12.9	6.5	-	Yes	
21060c	33 5/8	x 71 3/4	34 1/8	x 72 1/4	-	NT	-	12.9	-	5.3	-	
21060o	33 5/8	x 71 3/4	34 1/8	x 72 1/4	-	NT	-	12.9	-	5.3	-	
21062	33 5/8	x 73 3/4	34 1/8	x 74 1/4	DP-35	-	DP-50	13.3	6.7	-	Yes	
3030	35 5/8	x 35 3/4	36 1/8	x 36 1/4	DP-50	-	-	6.1	3.0	-	-	
3032	35 5/8	x 37 3/4	36 1/8	x 38 1/4	DP-50	-	-	6.5	3.3	-	-	
3038	35 5/8	x 43 3/4	36 1/8	x 44 1/4	DP-50	-	-	7.8	3.9	-	-	
3040	35 5/8	x 47 3/4	36 1/8	x 48 1/4	DP-50	-	-	8.6	4.3	-	-	
3042	35 5/8	x 49 3/4	36 1/8	x 50 1/4	DP-50	-	-	9.1	4.6	-	-	
3046	35 5/8	x 53 3/4	36 1/8	x 54 1/4	DP-50	-	-	9.9	5.0	-	-	
3050	35 5/8	x 59 3/4	36 1/8	x 60 1/4	DP-50	-	-	11.2	5.7	-	Yes	
3052	35 5/8	x 61 3/4	36 1/8	x 62 1/4	DP-35	-	DP-50	11.6	5.9	-	Yes	
3056	35 5/8	x 65 3/4	36 1/8	x 66 1/4	DP-35	-	-	12.5	6.3	-	Yes	
3060	35 5/8	x 71 3/4	36 1/8	x 72 1/4	DP-35	-	-	13.8	6.9	-	Yes	
3060c	35 5/8	x 71 3/4	36 1/8	x 72 1/4	-	NT	-	13.8	-	5.6	-	
3060o	35 5/8	x 71 3/4	36 1/8	x 72 1/4	-	NT	-	13.8	-	5.6	-	
3062	35 5/8	x 73 3/4	36 1/8	x 74 1/4	DP-35	-	-	14.2	7.2	-	Yes	
3230	37 5/8	x 35 3/4	38 1/8	x 36 1/4	DP-50	-	-	6.5	3.2	-	-	
3232	37 5/8	x 37 3/4	38 1/8	x 38 1/4	DP-50	-	-	6.9	3.5	-	-	
3238	37 5/8	x 43 3/4	38 1/8	x 44 1/4	DP-50	-	-	8.3	4.2	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 57"
 Minimum window height for 24" clear opening height cottage style window – 69"

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Single Window Units

Date:

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear C	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage		
3240	37 5/8	x 47 3/4	38 1/8	x 48 1/4	DP-50	-	-	9.2	4.6	-	-	
3242	37 5/8	x 49 3/4	38 1/8	x 50 1/4	DP-50	-	-	9.7	4.9	-	-	
3246	37 5/8	x 53 3/4	38 1/8	x 54 1/4	DP-50	-	-	10.6	5.3	-	-	
3250	37 5/8	x 59 3/4	38 1/8	x 60 1/4	DP-35	-	DP-50	11.9	6.0	-	Yes	
3252	37 5/8	x 61 3/4	38 1/8	x 62 1/4	DP-35	-	DP-50	12.4	6.2	-	Yes	
3256	37 5/8	x 65 3/4	38 1/8	x 66 1/4	DP-35	-	-	13.3	6.7	-	Yes	
3260	37 5/8	x 71 3/4	38 1/8	x 72 1/4	DP-35	-	-	14.7	7.4	-	Yes	
3260c	37 5/8	x 71 3/4	38 1/8	x 72 1/4	-	NT	-	14.7	-	6.0	-	
3260o	37 5/8	x 71 3/4	38 1/8	x 72 1/4	-	NT	-	14.7	-	6.0	-	
3262	37 5/8	x 73 3/4	38 1/8	x 74 1/4	DP-35	-	-	15.1	7.6	-	Yes	
3430	39 5/8	x 35 3/4	40 1/8	x 36 1/4	DP-35	-	DP-50	6.9	3.4	-	-	
3432	39 5/8	x 37 3/4	40 1/8	x 38 1/4	DP-35	-	DP-50	7.3	3.7	-	-	
3438	39 5/8	x 43 3/4	40 1/8	x 44 1/4	DP-35	-	DP-50	8.8	4.4	-	-	
3440	39 5/8	x 47 3/4	40 1/8	x 48 1/4	DP-35	-	DP-50	9.8	4.9	-	-	
3442	39 5/8	x 49 3/4	40 1/8	x 50 1/4	DP-35	-	DP-50	10.2	5.1	-	-	
3446	39 5/8	x 53 3/4	40 1/8	x 54 1/4	DP-35	-	DP-50	11.2	5.6	-	-	
3450	39 5/8	x 59 3/4	40 1/8	x 60 1/4	DP-35	-	-	12.7	6.4	-	Yes	
3452	39 5/8	x 61 3/4	40 1/8	x 62 1/4	DP-35	-	-	13.1	6.6	-	Yes	
3456	39 5/8	x 65 3/4	40 1/8	x 66 1/4	DP-35	-	-	14.1	7.1	-	Yes	
3460	39 5/8	x 71 3/4	40 1/8	x 72 1/4	DP-35	-	-	15.6	7.8	-	Yes	
3460c	39 5/8	x 71 3/4	40 1/8	x 72 1/4	-	NT	-	15.6	-	6.4	-	
3460o	39 5/8	x 71 3/4	40 1/8	x 72 1/4	-	NT	-	15.6	-	6.4	-	
3462	39 5/8	x 73 3/4	40 1/8	x 74 1/4	DP-35	-	-	16.0	8.1	-	Yes	
3630	41 5/8	x 35 3/4	42 1/8	x 36 1/4	DP-35	-	DP-50	7.3	3.6	-	-	
3632	41 5/8	x 37 3/4	42 1/8	x 38 1/4	DP-35	-	DP-50	7.8	3.9	-	-	
3638	41 5/8	x 43 3/4	42 1/8	x 44 1/4	DP-35	-	DP-50	9.3	4.7	-	-	
3640	41 5/8	x 47 3/4	42 1/8	x 48 1/4	DP-35	-	DP-50	10.3	5.2	-	-	
3642	41 5/8	x 49 3/4	42 1/8	x 50 1/4	DP-35	-	DP-50	10.8	5.4	-	-	
3646	41 5/8	x 53 3/4	42 1/8	x 54 1/4	DP-35	-	DP-50	11.9	6.0	-	-	
3650	41 5/8	x 59 3/4	42 1/8	x 60 1/4	DP-35	-	-	13.4	6.7	-	Yes	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Single Window Units

Date:

Code	Single Window Unit											
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear C	
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage		
3652	41 5/8	x 61 3/4	42 1/8	x 62 1/4	DP-35	-	-	13.9	7.0	-	Yes	
3656	41 5/8	x 65 3/4	42 1/8	x 66 1/4	DP-35	-	-	14.9	7.5	-	Yes	
3660	41 5/8	x 71 3/4	42 1/8	x 72 1/4	DP-35	-	-	16.5	8.3	-	Yes	
3660c	41 5/8	x 71 3/4	42 1/8	x 72 1/4	-	NT	-	16.5	-	6.7	-	
3660o	41 5/8	x 71 3/4	42 1/8	x 72 1/4	-	NT	-	16.5	-	6.7	-	
3662	41 5/8	x 73 3/4	42 1/8	x 74 1/4	DP-35	-	-	17.0	8.5	-	Yes	
3830	43 5/8	x 35 3/4	44 1/8	x 36 1/4	DP-35	-	-	7.6	3.8	-	-	
3832	43 5/8	x 37 3/4	44 1/8	x 38 1/4	DP-35	-	-	8.2	4.1	-	-	
3838	43 5/8	x 43 3/4	44 1/8	x 44 1/4	DP-35	-	-	9.8	4.9	-	-	
3840	43 5/8	x 47 3/4	44 1/8	x 48 1/4	DP-35	-	-	10.9	5.5	-	-	
3842	43 5/8	x 49 3/4	44 1/8	x 50 1/4	DP-35	-	-	11.4	5.7	-	-	
3846	43 5/8	x 53 3/4	44 1/8	x 54 1/4	DP-35	-	-	12.5	6.3	-	-	
3850	43 5/8	x 59 3/4	44 1/8	x 60 1/4	DP-35	-	-	14.1	7.1	-	Yes	
3852	43 5/8	x 61 3/4	44 1/8	x 62 1/4	DP-35	-	-	14.7	7.4	-	Yes	
3856	43 5/8	x 65 3/4	44 1/8	x 66 1/4	DP-35	-	-	15.7	7.9	-	Yes	
3860	43 5/8	x 71 3/4	44 1/8	x 72 1/4	DP-35	-	-	17.4	8.7	-	Yes	
3860c	43 5/8	x 71 3/4	44 1/8	x 72 1/4	-	NT	-	17.4	-	7.1	-	
3860o	43 5/8	x 71 3/4	44 1/8	x 72 1/4	-	NT	-	17.4	-	7.1	-	
3862	43 5/8	x 73 3/4	44 1/8	x 74 1/4	DP-35	-	-	17.9	9.0	-	Yes	
31030	45 5/8	x 35 3/4	46 1/8	x 36 1/4	NT	-	-	8.0	4.0	-	-	
31032	45 5/8	x 37 3/4	46 1/8	x 38 1/4	NT	-	-	8.6	4.3	-	-	
31038	45 5/8	x 43 3/4	46 1/8	x 44 1/4	NT	-	-	10.3	5.2	-	-	
31040	45 5/8	x 47 3/4	46 1/8	x 48 1/4	NT	-	-	11.4	5.7	-	-	
31042	45 5/8	x 49 3/4	46 1/8	x 50 1/4	NT	-	-	12.0	6.0	-	-	
31046	45 5/8	x 53 3/4	46 1/8	x 54 1/4	NT	-	-	13.1	6.6	-	-	
31050	45 5/8	x 59 3/4	46 1/8	x 60 1/4	NT	-	-	14.8	7.5	-	Yes	
31052	45 5/8	x 61 3/4	46 1/8	x 62 1/4	NT	-	-	15.4	7.7	-	Yes	
31056	45 5/8	x 65 3/4	46 1/8	x 66 1/4	NT	-	-	16.5	8.3	-	Yes	
31060	45 5/8	x 71 3/4	46 1/8	x 72 1/4	NT	-	-	18.2	9.2	-	Yes	
31060c	45 5/8	x 71 3/4	46 1/8	x 72 1/4	-	NT	-	18.2	-	7.5	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Single Window Units

Date:

Code	Single Window Unit												
	Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation		Clear C		
	Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage			
31060o	45 5/8	x 71 3/4	46 1/8	x 72 1/4	-	NT	-	18.2	-	7.5	-		
31062	45 5/8	x 73 3/4	46 1/8	x 74 1/4	NT	-	-	18.8	9.5	-	Yes		
4030	47 5/8	x 35 3/4	48 1/8	x 36 1/4	NT	-	-	8.4	4.2	-	-		
4032	47 5/8	x 37 3/4	48 1/8	x 38 1/4	NT	-	-	9.0	4.5	-	-		
4038	47 5/8	x 43 3/4	48 1/8	x 44 1/4	NT	-	-	10.8	5.4	-	-		
4040	47 5/8	x 47 3/4	48 1/8	x 48 1/4	NT	-	-	12.0	6.0	-	-		
4042	47 5/8	x 49 3/4	48 1/8	x 50 1/4	NT	-	-	12.6	6.3	-	-		
4046	47 5/8	x 53 3/4	48 1/8	x 54 1/4	NT	-	-	13.8	6.9	-	-		
4050	47 5/8	x 59 3/4	48 1/8	x 60 1/4	NT	-	-	15.6	7.8	-	Yes		
4052	47 5/8	x 61 3/4	48 1/8	x 62 1/4	NT	-	-	16.2	8.1	-	Yes		
4056	47 5/8	x 65 3/4	48 1/8	x 66 1/4	NT	-	-	17.4	8.7	-	Yes		
4060	47 5/8	x 71 3/4	48 1/8	x 72 1/4	NT	-	-	19.1	9.6	-	Yes		
4060c	47 5/8	x 71 3/4	48 1/8	x 72 1/4	-	NT	-	19.1	-	7.8	-		
4060o	47 5/8	x 71 3/4	48 1/8	x 72 1/4	-	NT	-	19.1	-	7.8	-		
4062	47 5/8	x 73 3/4	48 1/8	x 74 1/4	NT	-	-	19.7	9.9	-	Yes		

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

09-May-07 Product Specifications - Twin Window Units

Code	Opening Cottage	Twin Window Unit									
		Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation	
		Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage
1830	-	39 3/4	x 35 3/4	40 1/4	x 36 1/4	DP-30	-	DP-50	5.8	3.0	-
1832	-	39 3/4	x 37 3/4	40 1/4	x 38 1/4	DP-30	-	DP-50	6.2	3.2	-
1838	-	39 3/4	x 43 3/4	40 1/4	x 44 1/4	DP-30	-	DP-50	7.5	3.8	-
1840	-	39 3/4	x 47 3/4	40 1/4	x 48 1/4	DP-30	-	DP-50	8.3	4.2	-
1842	-	39 3/4	x 49 3/4	40 1/4	x 50 1/4	DP-30	-	DP-50	8.7	4.4	-
1846	-	39 3/4	x 53 3/4	40 1/4	x 54 1/4	DP-30	-	DP-50	9.5	4.9	-
1850	-	39 3/4	x 59 3/4	40 1/4	x 60 1/4	DP-30	-	DP-50	10.8	5.5	-
1852	-	39 3/4	x 61 3/4	40 1/4	x 62 1/4	DP-30	-	DP-50	11.2	5.7	-
1856	-	39 3/4	x 65 3/4	40 1/4	x 66 1/4	DP-30	-	DP-50	12.0	6.1	-
1860	-	39 3/4	x 71 3/4	40 1/4	x 72 1/4	DP-30	-	DP-50	13.2	6.7	-
1860c	-	39 3/4	x 71 3/4	40 1/4	x 72 1/4	-	NT	-	13.2	-	5.5
1860o	-	39 3/4	x 71 3/4	40 1/4	x 72 1/4	-	NT	-	13.2	-	5.5
1862	-	39 3/4	x 73 3/4	40 1/4	x 74 1/4	DP-30	-	DP-50	13.7	7.0	-
11030	-	43 3/4	x 35 3/4	44 1/4	x 36 1/4	DP-30	-	DP-50	6.6	3.4	-
11032	-	43 3/4	x 37 3/4	44 1/4	x 38 1/4	DP-30	-	DP-50	7.1	3.6	-
11038	-	43 3/4	x 43 3/4	44 1/4	x 44 1/4	DP-30	-	DP-50	8.5	4.3	-
11040	-	43 3/4	x 47 3/4	44 1/4	x 48 1/4	DP-30	-	DP-50	9.4	4.8	-
11042	-	43 3/4	x 49 3/4	44 1/4	x 50 1/4	DP-30	-	DP-50	9.9	5.0	-
11046	-	43 3/4	x 53 3/4	44 1/4	x 54 1/4	DP-30	-	DP-50	10.8	5.5	-
11050	-	43 3/4	x 59 3/4	44 1/4	x 60 1/4	DP-30	-	DP-50	12.2	6.2	-
11052	-	43 3/4	x 61 3/4	44 1/4	x 62 1/4	DP-30	-	DP-50	12.7	6.4	-
11056	-	43 3/4	x 65 3/4	44 1/4	x 66 1/4	DP-30	-	DP-50	13.6	6.9	-
11060	-	43 3/4	x 71 3/4	44 1/4	x 72 1/4	DP-30	-	DP-50	15.0	7.6	-
11060c	-	43 3/4	x 71 3/4	44 1/4	x 72 1/4	-	NT	-	15.0	-	6.2
11060o	-	43 3/4	x 71 3/4	44 1/4	x 72 1/4	-	NT	-	15.0	-	6.2
11062	-	43 3/4	x 73 3/4	44 1/4	x 74 1/4	DP-30	-	DP-50	15.5	7.9	-
2030	-	47 3/4	x 35 3/4	48 1/4	x 36 1/4	DP-30	-	DP-50	7.4	3.7	-
2032	-	47 3/4	x 37 3/4	48 1/4	x 38 1/4	DP-30	-	DP-50	7.9	4.0	-
2038	-	47 3/4	x 43 3/4	48 1/4	x 44 1/4	DP-30	-	DP-50	9.5	4.8	-
2040	-	47 3/4	x 47 3/4	48 1/4	x 48 1/4	DP-30	-	DP-50	10.6	5.3	-

Note: Daylight and Ventilation calculations are given in square foot of area

Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

09-May-07 Product Specifications - Twin Window Units

Code	Opening Cottage	Twin Window Unit									
		Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation	
		Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage
2042	-	47 3/4	x 49 3/4	48 1/4	x 50 1/4	DP-30	-	DP-50	11.1	5.6	-
2046	-	47 3/4	x 53 3/4	48 1/4	x 54 1/4	DP-30	-	DP-50	12.1	6.1	-
2050	-	47 3/4	x 59 3/4	48 1/4	x 60 1/4	DP-30	-	DP-50	13.7	6.9	-
2052	-	47 3/4	x 61 3/4	48 1/4	x 62 1/4	DP-30	-	DP-50	14.2	7.2	-
2056	-	47 3/4	x 65 3/4	48 1/4	x 66 1/4	DP-30	-	DP-50	15.3	7.7	-
2060	-	47 3/4	x 71 3/4	48 1/4	x 72 1/4	DP-30	-	DP-50	16.8	8.5	-
2060c	-	47 3/4	x 71 3/4	48 1/4	x 72 1/4	-	NT	-	16.8	-	6.9
2060o	-	47 3/4	x 71 3/4	48 1/4	x 72 1/4	-	NT	-	16.8	-	6.9
2062	-	47 3/4	x 73 3/4	48 1/4	x 74 1/4	DP-30	-	DP-50	17.3	8.8	-
2230	-	51 3/4	x 35 3/4	52 1/4	x 36 1/4	DP-30	-	DP-50	8.2	4.1	-
2232	-	51 3/4	x 37 3/4	52 1/4	x 38 1/4	DP-30	-	DP-50	8.8	4.4	-
2238	-	51 3/4	x 43 3/4	52 1/4	x 44 1/4	DP-30	-	DP-50	10.5	5.3	-
2240	-	51 3/4	x 47 3/4	52 1/4	x 48 1/4	DP-30	-	DP-50	11.7	5.9	-
2242	-	51 3/4	x 49 3/4	52 1/4	x 50 1/4	DP-30	-	DP-50	12.2	6.2	-
2246	-	51 3/4	x 53 3/4	52 1/4	x 54 1/4	DP-30	-	DP-50	13.4	6.8	-
2250	-	51 3/4	x 59 3/4	52 1/4	x 60 1/4	DP-30	-	DP-50	15.1	7.7	-
2252	-	51 3/4	x 61 3/4	52 1/4	x 62 1/4	DP-30	-	DP-50	15.7	7.9	-
2256	-	51 3/4	x 65 3/4	52 1/4	x 66 1/4	DP-30	-	DP-50	16.9	8.5	-
2260	-	51 3/4	x 71 3/4	52 1/4	x 72 1/4	DP-30	-	DP-50	18.6	9.4	-
2260c	-	51 3/4	x 71 3/4	52 1/4	x 72 1/4	-	NT	-	18.6	-	7.7
2260o	-	51 3/4	x 71 3/4	52 1/4	x 72 1/4	-	NT	-	18.6	-	7.7
2262	-	51 3/4	x 73 3/4	52 1/4	x 74 1/4	DP-30	-	DP-50	19.2	9.7	-
2430	-	55 3/4	x 35 3/4	56 1/4	x 36 1/4	DP-30	-	DP-50	9.0	4.5	-
2432	-	55 3/4	x 37 3/4	56 1/4	x 38 1/4	DP-30	-	DP-50	9.6	4.8	-
2438	-	55 3/4	x 43 3/4	56 1/4	x 44 1/4	DP-30	-	DP-50	11.5	5.8	-
2440	-	55 3/4	x 47 3/4	56 1/4	x 48 1/4	DP-30	-	DP-50	12.8	6.5	-
2442	-	55 3/4	x 49 3/4	56 1/4	x 50 1/4	DP-30	-	DP-50	13.4	6.8	-
2446	-	55 3/4	x 53 3/4	56 1/4	x 54 1/4	DP-30	-	DP-50	14.7	7.4	-
2450	-	55 3/4	x 59 3/4	56 1/4	x 60 1/4	DP-30	-	DP-50	16.6	8.4	-
2452	-	55 3/4	x 61 3/4	56 1/4	x 62 1/4	DP-30	-	DP-50	17.2	8.7	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

09-May-07 Product Specifications - Twin Window Units

Code	Opening Cottage	Twin Window Unit									
		Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation	
		Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage
2456	-	55 3/4	x 65 3/4	56 1/4	x 66 1/4	DP-30	-	DP-50	18.5	9.3	-
2460	-	55 3/4	x 71 3/4	56 1/4	x 72 1/4	DP-30	-	DP-50	20.4	10.3	-
2460c	-	55 3/4	x 71 3/4	56 1/4	x 72 1/4		NT		20.4	-	8.4
2460o	-	55 3/4	x 71 3/4	56 1/4	x 72 1/4		NT		20.4	-	8.4
2462	-	55 3/4	x 73 3/4	56 1/4	x 74 1/4	DP-30	-	DP-50	21.0	10.6	-
2630	-	59 3/4	x 35 3/4	60 1/4	x 36 1/4	DP-30	-	DP-50	9.8	4.9	-
2632	-	59 3/4	x 37 3/4	60 1/4	x 38 1/4	DP-30	-	DP-50	10.5	5.3	-
2638	-	59 3/4	x 43 3/4	60 1/4	x 44 1/4	DP-30	-	DP-50	12.5	6.3	-
2640	-	59 3/4	x 47 3/4	60 1/4	x 48 1/4	DP-30	-	DP-50	13.9	7.0	-
2642	-	59 3/4	x 49 3/4	60 1/4	x 50 1/4	DP-30	-	DP-50	14.6	7.4	-
2646	-	59 3/4	x 53 3/4	60 1/4	x 54 1/4	DP-30	-	DP-50	16.0	8.1	-
2650	-	59 3/4	x 59 3/4	60 1/4	x 60 1/4	DP-30	-	DP-50	18.1	9.1	-
2652	-	59 3/4	x 61 3/4	60 1/4	x 62 1/4	DP-30	-	DP-50	18.7	9.5	-
2656	-	59 3/4	x 65 3/4	60 1/4	x 66 1/4	DP-30	-	DP-50	20.1	10.2	-
2660	-	59 3/4	x 71 3/4	60 1/4	x 72 1/4	DP-30	-	DP-50	22.2	11.2	-
2660c	-	59 3/4	x 71 3/4	60 1/4	x 72 1/4	-	NT	-	22.2	-	9.1
2660o	-	59 3/4	x 71 3/4	60 1/4	x 72 1/4	-	NT	-	22.2	-	9.1
2662	-	59 3/4	x 73 3/4	60 1/4	x 74 1/4	DP-30	-	DP-50	22.9	11.5	-
2830	-	63 3/4	x 35 3/4	64 1/4	x 36 1/4	DP-30	-	DP-50	10.6	5.3	-
2832	-	63 3/4	x 37 3/4	64 1/4	x 38 1/4	DP-30	-	DP-50	11.3	5.7	-
2838	-	63 3/4	x 43 3/4	64 1/4	x 44 1/4	DP-30	-	DP-50	13.5	6.8	-
2840	-	63 3/4	x 47 3/4	64 1/4	x 48 1/4	DP-30	-	DP-50	15.0	7.6	-
2842	-	63 3/4	x 49 3/4	64 1/4	x 50 1/4	DP-30	-	DP-50	15.8	7.9	-
2846	-	63 3/4	x 53 3/4	64 1/4	x 54 1/4	DP-30	-	DP-50	17.3	8.7	-
2850	-	63 3/4	x 59 3/4	64 1/4	x 60 1/4	DP-30	-	DP-50	19.5	9.8	-
2852	-	63 3/4	x 61 3/4	64 1/4	x 62 1/4	DP-30	-	DP-50	20.2	10.2	-
2856	-	63 3/4	x 65 3/4	64 1/4	x 66 1/4	DP-30	-	DP-50	21.7	11.0	-
2860	-	63 3/4	x 71 3/4	64 1/4	x 72 1/4	DP-30	-	DP-50	24.0	12.1	-
2860c	-	63 3/4	x 71 3/4	64 1/4	x 72 1/4	DP-30	-	DP-50	24.0	-	9.8
2860o	-	63 3/4	x 71 3/4	64 1/4	x 72 1/4	DP-30	-	DP-50	24.0	-	9.8

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

09-May-07 Product Specifications - Twin Window Units

Code	Opening Cottage	Twin Window Unit									
		Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation	
		Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage
2862	-	63 3/4	x 73 3/4	64 1/4	x 74 1/4	DP-30	-	DP-50	24.7	12.5	-
21030	-	67 3/4	x 35 3/4	68 1/4	x 36 1/4	DP-30	-	DP-50	11.4	5.7	-
21032	-	67 3/4	x 37 3/4	68 1/4	x 38 1/4	DP-30	-	DP-50	12.2	6.1	-
21038	-	67 3/4	x 43 3/4	68 1/4	x 44 1/4	DP-30	-	DP-50	14.6	7.3	-
21040	-	67 3/4	x 47 3/4	68 1/4	x 48 1/4	DP-30	-	DP-50	16.2	8.1	-
21042	-	67 3/4	x 49 3/4	68 1/4	x 50 1/4	DP-30	-	DP-50	17.0	8.5	-
21046	-	67 3/4	x 53 3/4	68 1/4	x 54 1/4	DP-30	-	DP-50	18.6	9.3	-
21050	-	67 3/4	x 59 3/4	68 1/4	x 60 1/4	DP-30	-	DP-50	21.0	10.6	-
21052	-	67 3/4	x 61 3/4	68 1/4	x 62 1/4	DP-30	-	DP-50	21.8	11.0	-
21056	-	67 3/4	x 65 3/4	68 1/4	x 66 1/4	DP-30	-	DP-50	23.4	11.8	-
21060	-	67 3/4	x 71 3/4	68 1/4	x 72 1/4	DP-30	-	DP-50	25.8	13.0	-
21060c	-	67 3/4	x 71 3/4	68 1/4	x 72 1/4	-	NT	-	25.8	-	10.6
21060o	-	67 3/4	x 71 3/4	68 1/4	x 72 1/4	-	NT	-	25.8	-	10.6
21062	-	67 3/4	x 73 3/4	68 1/4	x 74 1/4	DP-30	-	DP-50	26.6	13.4	-
3030	-	71 3/4	x 35 3/4	72 1/4	x 36 1/4	DP-30	-	DP-50	12.1	6.1	-
3032	-	71 3/4	x 37 3/4	72 1/4	x 38 1/4	DP-30	-	DP-50	13.0	6.5	-
3038	-	71 3/4	x 43 3/4	72 1/4	x 44 1/4	DP-30	-	DP-50	15.6	7.8	-
3040	-	71 3/4	x 47 3/4	72 1/4	x 48 1/4	DP-30	-	DP-50	17.3	8.7	-
3042	-	71 3/4	x 49 3/4	72 1/4	x 50 1/4	DP-30	-	DP-50	18.1	9.1	-
3046	-	71 3/4	x 53 3/4	72 1/4	x 54 1/4	DP-30	-	DP-50	19.8	10.0	-
3050	-	71 3/4	x 59 3/4	72 1/4	x 60 1/4	DP-30	-	-	22.4	11.4	-
3052	-	71 3/4	x 61 3/4	72 1/4	x 62 1/4	DP-30	-	-	23.3	11.7	-
3056	-	71 3/4	x 65 3/4	72 1/4	x 66 1/4	DP-30	-	-	25.0	12.6	-
3060	-	71 3/4	x 71 3/4	72 1/4	x 72 1/4	DP-30	-	-	27.6	13.9	-
3060c	-	71 3/4	x 71 3/4	72 1/4	x 72 1/4	-	NT	-	27.6	-	11.3
3060o	-	71 3/4	x 71 3/4	72 1/4	x 72 1/4	-	NT	-	27.6	-	11.3
3062	-	71 3/4	x 73 3/4	72 1/4	x 74 1/4	DP-30	-	-	28.4	14.3	-
3230	-	75 3/4	x 35 3/4	76 1/4	x 36 1/4	DP-30	-	-	12.9	6.5	-
3232	-	75 3/4	x 37 3/4	76 1/4	x 38 1/4	DP-30	-	-	13.8	6.9	-
3238	-	75 3/4	x 43 3/4	76 1/4	x 44 1/4	DP-30	-	-	16.6	8.3	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

09-May-07 Product Specifications - Twin Window Units

Code	Opening Cottage	Twin Window Unit									
		Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation	
		Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage
3240	-	75 3/4	x 47 3/4	76 1/4	x 48 1/4	DP-30	-	-	18.4	9.2	-
3242	-	75 3/4	x 49 3/4	76 1/4	x 50 1/4	DP-30	-	-	19.3	9.7	-
3246	-	75 3/4	x 53 3/4	76 1/4	x 54 1/4	DP-30	-	-	21.1	10.6	-
3250	-	75 3/4	x 59 3/4	76 1/4	x 60 1/4	DP-30	-	-	23.9	12.0	-
3252	-	75 3/4	x 61 3/4	76 1/4	x 62 1/4	DP-30	-	-	24.8	12.5	-
3256	-	75 3/4	x 65 3/4	76 1/4	x 66 1/4	DP-30	-	-	26.6	13.4	-
3260	-	75 3/4	x 71 3/4	76 1/4	x 72 1/4	DP-30	-	-	29.3	14.8	-
3260c	Yes	75 3/4	x 71 3/4	76 1/4	x 72 1/4	-	NT	-	29.3	-	12.0
3260o	Yes	75 3/4	x 71 3/4	76 1/4	x 72 1/4	-	NT	-	29.3	-	12.0
3262	-	75 3/4	x 73 3/4	76 1/4	x 74 1/4	DP-30	-	-	30.2	15.2	-
3430	-	79 3/4	x 35 3/4	80 1/4	x 36 1/4	NT	-	-	13.7	6.9	-
3432	-	79 3/4	x 37 3/4	80 1/4	x 38 1/4	NT	-	-	14.7	7.4	-
3438	-	79 3/4	x 43 3/4	80 1/4	x 44 1/4	NT	-	-	17.6	8.8	-
3440	-	79 3/4	x 47 3/4	80 1/4	x 48 1/4	NT	-	-	19.5	9.8	-
3442	-	79 3/4	x 49 3/4	80 1/4	x 50 1/4	NT	-	-	20.5	10.3	-
3446	-	79 3/4	x 53 3/4	80 1/4	x 54 1/4	NT	-	-	22.4	11.3	-
3450	-	79 3/4	x 59 3/4	80 1/4	x 60 1/4	NT	-	-	25.3	12.7	-
3452	-	79 3/4	x 61 3/4	80 1/4	x 62 1/4	NT	-	-	26.3	13.2	-
3456	-	79 3/4	x 65 3/4	80 1/4	x 66 1/4	NT	NT	-	28.2	14.2	-
3460	-	79 3/4	x 71 3/4	80 1/4	x 72 1/4	NT	-	-	31.1	15.7	-
3460c	Yes	79 3/4	x 71 3/4	80 1/4	x 72 1/4	-	-	-	31.1	-	12.7
3460o	Yes	79 3/4	x 71 3/4	80 1/4	x 72 1/4	-	-	-	31.1	-	12.7
3462	-	79 3/4	x 73 3/4	80 1/4	x 74 1/4	NT	-	-	32.1	16.1	-
3630	-	83 3/4	x 35 3/4	84 1/4	x 36 1/4	NT	-	-	14.5	7.3	-
3632	-	83 3/4	x 37 3/4	84 1/4	x 38 1/4	NT	-	-	15.5	7.8	-
3638	-	83 3/4	x 43 3/4	84 1/4	x 44 1/4	NT	-	-	18.6	9.3	-
3640	-	83 3/4	x 47 3/4	84 1/4	x 48 1/4	NT	-	-	20.6	10.4	-
3642	-	83 3/4	x 49 3/4	84 1/4	x 50 1/4	NT	-	-	21.7	10.9	-
3646	-	83 3/4	x 53 3/4	84 1/4	x 54 1/4	NT	-	-	23.7	11.9	-
3650	-	83 3/4	x 59 3/4	84 1/4	x 60 1/4	NT	-	-	26.8	13.5	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

09-May-07 Product Specifications - Twin Window Units

Code	Opening Cottage	Twin Window Unit									
		Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation	
		Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage
3652	-	83 3/4	x 61 3/4	84 1/4	x 62 1/4	NT	-	-	27.8	14.0	-
3656	-	83 3/4	x 65 3/4	84 1/4	x 66 1/4	NT	NT	-	29.8	15.0	-
3660	-	83 3/4	x 71 3/4	84 1/4	x 72 1/4	NT	-	-	32.9	16.5	-
3660c	Yes	83 3/4	x 71 3/4	84 1/4	x 72 1/4	-	-	-	32.9	-	13.5
3660o	Yes	83 3/4	x 71 3/4	84 1/4	x 72 1/4	-	-	-	32.9	-	13.5
3662	-	83 3/4	x 73 3/4	84 1/4	x 74 1/4	NT	-	-	33.9	17.1	-
3830	-	87 3/4	x 35 3/4	88 1/4	x 36 1/4	NT	-	-	15.3	7.7	-
3832	-	87 3/4	x 37 3/4	88 1/4	x 38 1/4	NT	-	-	16.4	8.2	-
3838	-	87 3/4	x 43 3/4	88 1/4	x 44 1/4	NT	-	-	19.6	9.8	-
3840	-	87 3/4	x 47 3/4	88 1/4	x 48 1/4	NT	-	-	21.8	10.9	-
3842	-	87 3/4	x 49 3/4	88 1/4	x 50 1/4	NT	-	-	22.8	11.5	-
3846	-	87 3/4	x 53 3/4	88 1/4	x 54 1/4	NT	-	-	25.0	12.5	-
3850	-	87 3/4	x 59 3/4	88 1/4	x 60 1/4	NT	-	-	28.2	14.2	-
3852	-	87 3/4	x 61 3/4	88 1/4	x 62 1/4	NT	-	-	29.3	14.7	-
3856	-	87 3/4	x 65 3/4	88 1/4	x 66 1/4	NT	NT	-	31.5	15.8	-
3860	-	87 3/4	x 71 3/4	88 1/4	x 72 1/4	NT	-	-	34.7	17.4	-
3860c	Yes	87 3/4	x 71 3/4	88 1/4	x 72 1/4	-	-	-	34.7	-	14.2
3860o	Yes	87 3/4	x 71 3/4	88 1/4	x 72 1/4	-	-	-	34.7	-	14.2
3862	-	87 3/4	x 73 3/4	88 1/4	x 74 1/4	NT	-	-	-	-	-
31030	-	91 3/4	x 35 3/4	92 1/4	x 36 1/4	NT	-	-	16.1	8.1	-
31032	-	91 3/4	x 37 3/4	92 1/4	x 38 1/4	NT	-	-	17.2	8.6	-
31038	-	91 3/4	x 43 3/4	92 1/4	x 44 1/4	NT	-	-	20.6	10.3	-
31040	-	91 3/4	x 47 3/4	92 1/4	x 48 1/4	NT	-	-	22.9	11.5	-
31042	-	91 3/4	x 49 3/4	92 1/4	x 50 1/4	NT	-	-	24.0	12.0	-
31046	-	91 3/4	x 53 3/4	92 1/4	x 54 1/4	NT	-	-	26.3	13.2	-
31050	-	91 3/4	x 59 3/4	92 1/4	x 60 1/4	NT	-	-	29.7	14.9	-
31052	-	91 3/4	x 61 3/4	92 1/4	x 62 1/4	NT	-	-	30.8	15.5	-
31056	-	91 3/4	x 65 3/4	92 1/4	x 66 1/4	NT	-	-	33.1	16.6	-
31060	-	91 3/4	x 71 3/4	92 1/4	x 72 1/4	NT	-	-	36.5	18.3	-
31060c	Yes	91 3/4	x 71 3/4	92 1/4	x 72 1/4	-	NT	-	36.5	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 49 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

09-May-07 Product Specifications - Twin Window Units

Code	Opening Cottage	Twin Window Unit									
		Unit Dimensions		Rough Opening		DP Rating			Daylight	Ventilation	
		Width	Height	Width	Height	Equal	Cottage	Optional		Equal	Cottage
31060o	Yes	91 3/4	x 71 3/4	92 1/4	x 72 1/4	-	NT	-	36.5	-	-
31062	-	-	-	-	-	-	-	-	-	-	-
4030	-	95 3/4	x 35 3/4	96 1/4	x 36 1/4	NT	-	-	16.9	8.4	-
4032	-	95 3/4	x 37 3/4	96 1/4	x 38 1/4	NT	-	-	18.1	9.0	-
4038	-	95 3/4	x 43 3/4	96 1/4	x 44 1/4	NT	-	-	21.6	10.8	-
4040	-	95 3/4	x 47 3/4	96 1/4	x 48 1/4	NT	-	-	24.0	12.0	-
4042	-	95 3/4	x 49 3/4	96 1/4	x 50 1/4	NT	-	-	25.2	12.6	-
4046	-	95 3/4	x 53 3/4	96 1/4	x 54 1/4	NT	-	-	27.6	13.8	-
4050	-	95 3/4	x 59 3/4	96 1/4	x 60 1/4	NT	-	-	31.1	15.6	-
4052	-	95 3/4	x 61 3/4	96 1/4	x 62 1/4	NT	-	-	32.3	16.2	-
4056	-	95 3/4	x 65 3/4	96 1/4	x 66 1/4	NT	-	-	34.7	17.4	-
4060	-	95 3/4	x 71 3/4	96 1/4	x 72 1/4	NT	-	-	38.3	19.2	-
4060c	Yes	95 3/4	x 71 3/4	96 1/4	x 72 1/4	-	NT	-	38.3	-	15.6
4060o	Yes	95 3/4	x 71 3/4	96 1/4	x 72 1/4	-	NT	-	38.3	-	15.6
4062	-	-	-	-	-	-	-	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Date: 09-May-07 **Product Specifications - Triple Window Units**

Code	Clear Opening		Triple Window Unit										
	Equal	Cottage	Unit Dimensions		Rough Opening			DP Rating		Daylight	Ventilation		
			Width	Height	Width	Height	Equal	Cottage	Equal		Cottage		
1830	-	-	59 7/8	x 35 3/4	60 3/8	x 36 1/4	DP-35	-	8.8	4.4	-		
1832	-	-	59 7/8	x 37 3/4	60 3/8	x 38 1/4	DP-35	-	9.4	4.8	-		
1838	-	-	59 7/8	x 43 3/4	60 3/8	x 44 1/4	DP-35	-	11.2	5.7	-		
1840	-	-	59 7/8	x 47 3/4	60 3/8	x 48 1/4	DP-35	-	12.5	6.3	-		
1842	-	-	59 7/8	x 49 3/4	60 3/8	x 50 1/4	DP-35	-	13.1	6.6	-		
1846	-	-	59 7/8	x 53 3/4	60 3/8	x 54 1/4	DP-35	-	14.3	7.3	-		
1850	-	-	59 7/8	x 59 3/4	60 3/8	x 60 1/4	DP-35	-	16.2	8.2	-		
1852	-	-	59 7/8	x 61 3/4	60 3/8	x 62 1/4	DP-35	-	16.8	8.5	-		
1856	-	-	59 7/8	x 65 3/4	60 3/8	x 66 1/4	DP-35	-	18.0	9.2	-		
1860	-	-	59 7/8	x 71 3/4	60 3/8	x 72 1/4	DP-35	-	19.9	10.1	-		
1860c	-	-	59 7/8	x 71 3/4	60 3/8	x 72 1/4	-	NT	19.9	-	8.2		
1860o	-	-	59 7/8	x 71 3/4	60 3/8	x 72 1/4	-	NT	19.9	-	8.2		
1862	-	-	59 7/8	x 73 3/4	60 3/8	x 74 1/4	DP-35	-	20.5	10.4	-		
11030	-	-	65 7/8	x 35 3/4	66 3/8	x 36 1/4	DP-35	-	9.9	5.0	-		
11032	-	-	65 7/8	x 37 3/4	66 3/8	x 38 1/4	DP-35	-	10.6	5.4	-		
11038	-	-	65 7/8	x 43 3/4	66 3/8	x 44 1/4	DP-35	-	12.7	6.5	-		
11040	-	-	65 7/8	x 47 3/4	66 3/8	x 48 1/4	DP-35	-	14.1	7.2	-		
11042	-	-	65 7/8	x 49 3/4	66 3/8	x 50 1/4	DP-35	-	14.8	7.5	-		
11046	-	-	65 7/8	x 53 3/4	66 3/8	x 54 1/4	DP-35	-	16.2	8.2	-		
11050	-	-	65 7/8	x 59 3/4	66 3/8	x 60 1/4	DP-35	-	18.3	9.3	-		
11052	-	-	65 7/8	x 61 3/4	66 3/8	x 62 1/4	DP-35	-	19.0	9.7	-		
11056	-	-	65 7/8	x 65 3/4	66 3/8	x 66 1/4	DP-35	-	20.4	10.4	-		
11060	-	-	65 7/8	x 71 3/4	66 3/8	x 72 1/4	DP-35	-	22.5	11.5	-		
11060c	-	-	65 7/8	x 71 3/4	66 3/8	x 72 1/4	-	NT	22.5	-	9.3		
11060o	-	-	65 7/8	x 71 3/4	66 3/8	x 72 1/4	-	NT	22.5	-	9.3		
11062	-	-	65 7/8	x 73 3/4	66 3/8	x 74 1/4	DP-35	-	23.2	11.8	-		
2030	-	-	71 7/8	x 35 3/4	72 3/8	x 36 1/4	DP-35	-	11.1	5.6	-		
2032	-	-	71 7/8	x 37 3/4	72 3/8	x 38 1/4	DP-35	-	11.9	6.0	-		
2038	-	-	71 7/8	x 43 3/4	72 3/8	x 44 1/4	DP-35	-	14.3	7.2	-		
2040	-	-	71 7/8	x 47 3/4	72 3/8	x 48 1/4	DP-35	-	15.8	8.0	-		

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Date: 09-May-07 **Product Specifications - Triple Window Units**

Code	Clear Opening		Triple Window Unit												
	Equal	Cottage	Unit Dimensions				Rough Opening				DP Rating		Daylight	Ventilation	
			Width	Height	Width	Height	Equal	Cottage	Equal	Cottage					
2042	-	-	71 7/8	x 49 3/4	72 3/8	x 50 1/4	DP-35	-	16.6	8.4	-				
2046	-	-	71 7/8	x 53 3/4	72 3/8	x 54 1/4	DP-35	-	18.2	9.2	-				
2050	-	-	71 7/8	x 59 3/4	72 3/8	x 60 1/4	DP-35	-	20.5	10.4	-				
2052	-	-	71 7/8	x 61 3/4	72 3/8	x 62 1/4	DP-35	-	21.3	10.8	-				
2056	-	-	71 7/8	x 65 3/4	72 3/8	x 66 1/4	DP-35	-	22.9	11.6	-				
2060	-	-	71 7/8	x 71 3/4	72 3/8	x 72 1/4	DP-35	-	25.2	12.8	-				
2060c	-	-	71 7/8	x 71 3/4	72 3/8	x 72 1/4	-	NT	25.2	-	10.4				
2060o	-	-	71 7/8	x 71 3/4	72 3/8	x 72 1/4	-	NT	25.2	-	10.4				
2062	-	-	71 7/8	x 73 3/4	72 3/8	x 74 1/4	DP-35	-	26.0	13.2	-				
2230	-	-	77 7/8	x 35 3/4	78 3/8	x 36 1/4	DP-35	-	12.3	6.2	-				
2232	-	-	77 7/8	x 37 3/4	78 3/8	x 38 1/4	DP-35	-	13.2	6.6	-				
2238	-	-	77 7/8	x 43 3/4	78 3/8	x 44 1/4	DP-35	-	15.8	8.0	-				
2240	-	-	77 7/8	x 47 3/4	78 3/8	x 48 1/4	DP-35	-	17.5	8.8	-				
2242	-	-	77 7/8	x 49 3/4	78 3/8	x 50 1/4	DP-35	-	18.4	9.3	-				
2246	-	-	77 7/8	x 53 3/4	78 3/8	x 54 1/4	DP-35	-	20.1	10.2	-				
2250	-	-	77 7/8	x 59 3/4	78 3/8	x 60 1/4	DP-35	-	22.7	11.5	-				
2252	-	-	77 7/8	x 61 3/4	78 3/8	x 62 1/4	DP-35	-	23.6	11.9	-				
2256	-	-	77 7/8	x 65 3/4	78 3/8	x 66 1/4	DP-35	-	25.3	12.8	-				
2260	-	-	77 7/8	x 71 3/4	78 3/8	x 72 1/4	DP-35	-	27.9	14.1	-				
2260c	-	-	77 7/8	x 71 3/4	78 3/8	x 72 1/4	-	NT	27.9	-	11.5				
2260o	-	-	77 7/8	x 71 3/4	78 3/8	x 72 1/4	-	NT	27.9	-	11.5				
2262	-	-	77 7/8	x 73 3/4	78 3/8	x 74 1/4	DP-35	-	28.8	14.6	-				
2430	-	-	83 7/8	x 35 3/4	84 3/8	x 36 1/4	DP-35	-	13.5	6.8	-				
2432	-	-	83 7/8	x 37 3/4	84 3/8	x 38 1/4	DP-35	-	14.4	7.3	-				
2438	-	-	83 7/8	x 43 3/4	84 3/8	x 44 1/4	DP-35	-	17.3	8.7	-				
2440	-	-	83 7/8	x 47 3/4	84 3/8	x 48 1/4	DP-35	-	19.2	9.7	-				
2442	-	-	83 7/8	x 49 3/4	84 3/8	x 50 1/4	DP-35	-	20.1	10.2	-				
2446	-	-	83 7/8	x 53 3/4	84 3/8	x 54 1/4	DP-35	-	22.0	11.1	-				
2450	-	-	83 7/8	x 59 3/4	84 3/8	x 60 1/4	DP-35	-	24.9	12.6	-				
2452	-	-	83 7/8	x 61 3/4	84 3/8	x 62 1/4	DP-35	-	25.8	13.1	-				

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Date: 09-May-07 **Product Specifications - Triple Window Units**

Code	Clear Opening		Triple Window Unit												
	Equal	Cottage	Unit Dimensions				Rough Opening				DP Rating		Daylight	Ventilation	
			Width	Height	Width	Height	Width	Height	Equal	Cottage	Equal	Cottage			
2456	-	-	83 7/8	x 65 3/4	84 3/8	x 66 1/4	DP-35	-	27.7	14.0	-				
2460	-	-	83 7/8	x 71 3/4	84 3/8	x 72 1/4	DP-35	-	30.6	15.5	-				
2460c	-	-	83 7/8	x 71 3/4	84 3/8	x 72 1/4	-	NT	30.6	-	12.6				
2460o	-	-	83 7/8	x 71 3/4	84 3/8	x 72 1/4	-	NT	30.6	-	12.6				
2462	-	-	83 7/8	x 73 3/4	84 3/8	x 74 1/4	DP-35	-	31.5	15.9	-				
2630	-	-	89 7/8	x 35 3/4	90 3/8	x 36 1/4	DP-35	-	14.7	7.4	-				
2632	-	-	89 7/8	x 37 3/4	90 3/8	x 38 1/4	DP-35	-	15.7	7.9	-				
2638	-	-	89 7/8	x 43 3/4	90 3/8	x 44 1/4	DP-35	-	18.8	9.5	-				
2640	-	-	89 7/8	x 47 3/4	90 3/8	x 48 1/4	DP-35	-	20.9	10.5	-				
2642	-	-	89 7/8	x 49 3/4	90 3/8	x 50 1/4	DP-35	-	21.9	11.0	-				
2646	-	-	89 7/8	x 53 3/4	90 3/8	x 54 1/4	DP-35	-	24.0	12.1	-				
2650	-	-	89 7/8	x 59 3/4	90 3/8	x 60 1/4	DP-35	-	27.1	13.7	-				
2652	-	-	89 7/8	x 61 3/4	90 3/8	x 62 1/4	DP-35	-	28.1	14.2	-				
2656	-	-	89 7/8	x 65 3/4	90 3/8	x 66 1/4	DP-35	-	30.2	15.2	-				
2660	-	-	89 7/8	x 71 3/4	90 3/8	x 72 1/4	DP-35	-	33.3	16.8	-				
2660c	-	-	89 7/8	x 71 3/4	90 3/8	x 72 1/4	-	NT	33.3	-	13.7				
2660o	-	-	89 7/8	x 71 3/4	90 3/8	x 72 1/4	-	NT	33.3	-	13.7				
2662	Yes	-	89 7/8	x 73 3/4	90 3/8	x 74 1/4	DP-35	-	34.3	17.3	-				
2830	-	-	95 7/8	x 35 3/4	96 3/8	x 36 1/4	DP-35	-	15.9	8.0	-				
2832	-	-	95 7/8	x 37 3/4	96 3/8	x 38 1/4	DP-35	-	17.0	8.5	-				
2838	-	-	95 7/8	x 43 3/4	96 3/8	x 44 1/4	DP-35	-	20.3	10.2	-				
2840	-	-	95 7/8	x 47 3/4	96 3/8	x 48 1/4	DP-35	-	22.6	11.4	-				
2842	-	-	95 7/8	x 49 3/4	96 3/8	x 50 1/4	DP-35	-	23.7	11.9	-				
2846	-	-	95 7/8	x 53 3/4	96 3/8	x 54 1/4	DP-35	-	25.9	13.1	-				
2850	-	-	95 7/8	x 59 3/4	96 3/8	x 60 1/4	DP-35	-	29.3	14.7	-				
2852	-	-	95 7/8	x 61 3/4	96 3/8	x 62 1/4	DP-35	-	30.4	15.3	-				
2856	-	-	95 7/8	x 65 3/4	96 3/8	x 66 1/4	DP-35	-	32.6	16.4	-				
2860	Yes	-	95 7/8	x 71 3/4	96 3/8	x 72 1/4	DP-35	-	36.0	18.1	-				
2860c	-	-	95 7/8	x 71 3/4	96 3/8	x 72 1/4	-	NT	36.0	-	14.7				
2860o	-	-	95 7/8	x 71 3/4	96 3/8	x 72 1/4	-	NT	36.0	-	14.7				

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Date: 09-May-07 **Product Specifications - Triple Window Units**

Code	Clear Opening		Triple Window Unit										
	Equal	Cottage	Unit Dimensions			Rough Opening			DP Rating		Daylight	Ventilation	
			Width	Height		Width	Height		Equal	Cottage		Equal	Cottage
2862	Yes	-	95 7/8	x	73 3/4	96 3/8	x	74 1/4	DP-35	-	37.1	18.7	-
21030	-	-	101 7/8	x	35 3/4	102 3/8	x	36 1/4	DP-35	-	17.0	8.6	-
21032	-	-	101 7/8	x	37 3/4	102 3/8	x	38 1/4	DP-35	-	18.2	9.2	-
21038	-	-	101 7/8	x	43 3/4	102 3/8	x	44 1/4	DP-35	-	21.8	11.0	-
21040	-	-	101 7/8	x	47 3/4	102 3/8	x	48 1/4	DP-35	-	24.2	12.2	-
21042	-	-	101 7/8	x	49 3/4	102 3/8	x	50 1/4	DP-35	-	25.4	12.8	-
21046	-	-	101 7/8	x	53 3/4	102 3/8	x	54 1/4	DP-35	-	27.8	14.0	-
21050	-	-	101 7/8	x	59 3/4	102 3/8	x	60 1/4	DP-35	-	31.4	15.8	-
21052	-	-	101 7/8	x	61 3/4	102 3/8	x	62 1/4	DP-35	-	32.6	16.4	-
21056	Yes	-	101 7/8	x	65 3/4	102 3/8	x	66 1/4	DP-35	-	35.0	17.7	-
21060	Yes	-	101 7/8	x	71 3/4	102 3/8	x	72 1/4	DP-35	-	38.6	19.5	-
21060c	-	-	101 7/8	x	71 3/4	102 3/8	x	72 1/4	-	NT	38.6	-	15.8
21060o	-	-	101 7/8	x	71 3/4	102 3/8	x	72 1/4	-	NT	38.6	-	15.8
21062	Yes	-	101 7/8	x	73 3/4	102 3/8	x	74 1/4	DP-35	-	39.8	20.1	-
3030	-	-	107 7/8	x	35 3/4	108 3/8	x	36 1/4	NT	-	18.2	9.1	-
3032	-	-	107 7/8	x	37 3/4	108 3/8	x	38 1/4	NT	-	19.5	9.8	-
3038	-	-	107 7/8	x	43 3/4	108 3/8	x	44 1/4	NT	-	23.4	11.7	-
3040	-	-	107 7/8	x	47 3/4	108 3/8	x	48 1/4	NT	-	25.9	13.0	-
3042	-	-	107 7/8	x	49 3/4	108 3/8	x	50 1/4	NT	-	27.2	13.7	-
3046	-	-	107 7/8	x	53 3/4	108 3/8	x	54 1/4	NT	-	29.8	15.0	-
3050	Yes	-	107 7/8	x	59 3/4	108 3/8	x	60 1/4	NT	-	33.6	17.1	-
3052	Yes	-	-	-	-	-	-	-	-	-	-	-	-
3056	Yes	-	-	-	-	-	-	-	-	-	-	-	-
3060	Yes	-	-	-	-	-	-	-	-	-	-	-	-
3060c	-	-	-	-	-	-	-	-	-	-	-	-	-
3060o	-	-	-	-	-	-	-	-	-	-	-	-	-
3062	Yes	-	-	-	-	-	-	-	-	-	-	-	-
3230	-	-	113 7/8	x	35 3/4	114 3/8	x	36 1/4	NT	-	19.4	9.7	-
3232	-	-	113 7/8	x	37 3/4	114 3/8	x	38 1/4	NT	-	20.8	10.4	-
3238	-	-	113 7/8	x	43 3/4	114 3/8	x	44 1/4	NT	-	24.9	12.5	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 74 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Date: 09-May-07 **Product Specifications - Triple Window Units**

Code	Triple Window Unit												
	Clear Opening		Unit Dimensions				Rough Opening		DP Rating		Daylight	Ventilation	
	Equal	Cottage	Width	Height	Width	Height	Equal	Cottage	Equal	Cottage			
3240	-	-	113 7/8	x 47 3/4	114 3/8	x 48 1/4	NT	-	27.6	13.9	-		
3242	-	-	113 7/8	x 49 3/4	114 3/8	x 50 1/4	NT	-	29.0	14.6	-		
3246	-	-	113 7/8	x 53 3/4	114 3/8	x 54 1/4	NT	-	31.7	15.9	-		
3250	Yes	-	-	-	-	-	-	-	-	-	-		
3252	Yes	-	-	-	-	-	-	-	-	-	-		
3256	Yes	-	-	-	-	-	-	-	-	-	-		
3260	Yes	-	-	-	-	-	-	-	-	-	-		
3260c	-	Yes	-	-	-	-	-	-	-	-	-		
3260o	-	Yes	-	-	-	-	-	-	-	-	-		
3262	Yes	-	-	-	-	-	-	-	-	-	-		
3430	-	-	119 7/8	x 35 3/4	120 3/8	x 36 1/4	NT	-	20.6	10.3	-		
3432	-	-	119 7/8	x 37 3/4	120 3/8	x 38 1/4	NT	-	22.0	11.0	-		
3438	-	-	119 7/8	x 43 3/4	120 3/8	x 44 1/4	NT	-	26.4	13.2	-		
3440	-	-	119 7/8	x 47 3/4	120 3/8	x 48 1/4	NT	-	29.3	14.7	-		
3442	-	-	119 7/8	x 49 3/4	120 3/8	x 50 1/4	NT	-	30.7	15.4	-		
3446	-	-	119 7/8	x 53 3/4	120 3/8	x 54 1/4	NT	-	33.6	16.9	-		
3450	Yes	-	-	-	-	-	-	-	-	-	-		
3452	Yes	-	-	-	-	-	-	-	-	-	-		
3456	Yes	-	-	-	-	-	-	-	-	-	-		
3460	Yes	-	-	-	-	-	-	-	-	-	-		
3460c	-	Yes	-	-	-	-	-	-	-	-	-		
3460o	-	Yes	-	-	-	-	-	-	-	-	-		
3462	Yes	-	-	-	-	-	-	-	-	-	-		
3630	-	-	125 7/8	x 35 3/4	126 3/8	x 36 1/4	NT	-	21.8	10.9	-		
3632	-	-	125 7/8	x 37 3/4	126 3/8	x 38 1/4	NT	-	23.3	11.7	-		
3638	-	-	125 7/8	x 43 3/4	126 3/8	x 44 1/4	NT	-	27.9	14.0	-		
3640	-	-	125 7/8	x 47 3/4	126 3/8	x 48 1/4	NT	-	31.0	15.5	-		
3642	-	-	125 7/8	x 49 3/4	126 3/8	x 50 1/4	NT	-	32.5	16.3	-		
3646	-	-	-	-	-	-	-	-	-	-	-		
3650	Yes	-	-	-	-	-	-	-	-	-	-		

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area
 0
 Minimum window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Date: 09-May-07 **Product Specifications - Triple Window Units**

Code	Clear Opening		Unit Dimensions		Rough Opening		DP Rating		Daylight	Ventilation	
	Equal	Cottage	Width	Height	Width	Height	Equal	Cottage		Equal	Cottage
3652	Yes	-	-	-	-	-	-	-	-	-	-
3656	Yes	-	-	-	-	-	-	-	-	-	-
3660	Yes	-	-	-	-	-	-	-	-	-	-
3660c	-	Yes	-	-	-	-	-	-	-	-	-
3660o	-	Yes	-	-	-	-	-	-	-	-	-
3662	Yes	-	-	-	-	-	-	-	-	-	-
3830	-	-	131 7/8 x 35 3/4		132 3/8 x 36 1/4		NT	-	22.9	11.5	-
3832	-	-	131 7/8 x 37 3/4		132 3/8 x 38 1/4		NT	-	24.6	12.3	-
3838	-	-	131 7/8 x 43 3/4		132 3/8 x 44 1/4		NT	-	29.4	14.7	-
3840	-	-	131 7/8 x 47 3/4		132 3/8 x 48 1/4		NT	-	32.6	16.4	-
3842	-	-	-	-	-	-	-	-	-	-	-
3846	-	-	-	-	-	-	-	-	-	-	-
3850	Yes	-	-	-	-	-	-	-	-	-	-
3852	Yes	-	-	-	-	-	-	-	-	-	-
3856	Yes	-	-	-	-	-	-	-	-	-	-
3860	Yes	-	-	-	-	-	-	-	-	-	-
3860c	-	Yes	-	-	-	-	-	-	-	-	-
3860o	-	Yes	-	-	-	-	-	-	-	-	-
3862	Yes	-	-	-	-	-	-	-	-	-	-
31030	-	-	137 7/8 x 35 3/4		138 3/8 x 36 1/4		NT	-	24.1	12.1	-
31032	-	-	137 7/8 x 37 3/4		138 3/8 x 38 1/4		NT	-	25.8	12.9	-
31038	-	-	137 7/8 x 43 3/4		138 3/8 x 44 1/4		NT	-	30.9	15.5	-
31040	-	-	-	-	-	-	-	-	-	-	-
31042	-	-	-	-	-	-	-	-	-	-	-
31046	-	-	-	-	-	-	-	-	-	-	-
31050	Yes	-	-	-	-	-	-	-	-	-	-
31052	Yes	-	-	-	-	-	-	-	-	-	-
31056	Yes	-	-	-	-	-	-	-	-	-	-
31060	Yes	-	-	-	-	-	-	-	-	-	-
31060c	-	Yes	-	-	-	-	-	-	-	-	-

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area
 0
 Minimum window width for 20" clear opening width – 74 1/2"
 Minimum window height for 24" clear opening height – 56"
 Minimum window height for 24" clear opening height cottage style window – 68"

Seven D Industries, L.P.

Series 5800 Single Hung

Date: 09-May-07 **Product Specifications - Triple Window Units**

Code	Triple Window Unit												
	Clear Opening		Unit Dimensions				Rough Opening		DP Rating		Ventilation		
	Equal	Cottage	Width	Height	Width	Height	Equal	Cottage	Daylight	Equal	Cottage		
31060o	-	Yes	-	-	-	-	-	-	-	-	-	-	-
31062	-	-	-	-	-	-	-	-	-	-	-	-	-
4030	-	-	143 7/8 x 35 3/4		144 3/8 x 36 1/4		NT	-	25.3	12.7	-	-	
4032	-	-	143 7/8 x 37 3/4		144 3/8 x 38 1/4		NT	-	27.1	13.6	-	-	
4038	-	-	143 7/8 x 43 3/4		144 3/8 x 44 1/4		NT	-	32.4	16.3	-	-	
4040	-	-	-	-	-	-	-	-	-	-	-	-	
4042	-	-	-	-	-	-	-	-	-	-	-	-	
4046	-	-	-	-	-	-	-	-	-	-	-	-	
4050	Yes	-	-	-	-	-	-	-	-	-	-	-	
4052	Yes	-	-	-	-	-	-	-	-	-	-	-	
4056	Yes	-	-	-	-	-	-	-	-	-	-	-	
4060	Yes	-	-	-	-	-	-	-	-	-	-	-	
4060c	-	Yes	-	-	-	-	-	-	-	-	-	-	
4060o	-	Yes	-	-	-	-	-	-	-	-	-	-	
4062	-	-	-	-	-	-	-	-	-	-	-	-	

Note: Daylight and Ventilation calculations are given in square foot of area
 Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 56"

Minimum window height for 24" clear opening height cottage style window – 68"

Date: 09-May-07

Code	Clear Opening	
	Equal	Cottage
1830	-	-
1832	-	-
1838	-	-
1840	-	-
1842	-	-
1846	-	-
1850	-	-
1852	-	-
1856	-	-
1860	-	-
1860c	-	-
1860o	-	-
1862	-	-
11030	-	-
11032	-	-
11038	-	-
11040	-	-
11042	-	-
11046	-	-
11050	-	-
11052	-	-
11056	-	-
11060	-	-
11060c	-	-
11060o	-	-
11062	-	-
2030	-	-
2032	-	-
2038	-	-
2040	-	-

Date: 09-May-07

Code	Clear Opening	
	Equal	Cottage
2042	-	-
2046	-	-
2050	-	-
2052	-	-
2056	-	-
2060	-	-
2060c	-	-
2060o	-	-
2062	-	-
2230	-	-
2232	-	-
2238	-	-
2240	-	-
2242	-	-
2246	-	-
2250	-	-
2252	-	-
2256	-	-
2260	-	-
2260c	-	-
2260o	-	-
2262	-	-
2430	-	-
2432	-	-
2438	-	-
2440	-	-
2442	-	-
2446	-	-
2450	-	-
2452	-	-

Date: 09-May-07

Code	Clear Opening	
	Equal	Cottage
2456	-	-
2460	-	-
2460c	-	-
2460o	-	-
2462	-	-
2630	-	-
2632	-	-
2638	-	-
2640	-	-
2642	-	-
2646	-	-
2650	-	-
2652	-	-
2656	-	-
2660	-	-
2660c	-	-
2660o	-	-
2662	Yes	-
2830	-	-
2832	-	-
2838	-	-
2840	-	-
2842	-	-
2846	-	-
2850	-	-
2852	-	-
2856	-	-
2860	Yes	-
2860c	-	-
2860o	-	-

Date: 09-May-07

Code	Clear Opening	
	Equal	Cottage
2862	Yes	-
21030	-	-
21032	-	-
21038	-	-
21040	-	-
21042	-	-
21046	-	-
21050	-	-
21052	-	-
21056	Yes	-
21060	Yes	-
21060c	-	-
21060o	-	-
21062	Yes	-
3030	-	-
3032	-	-
3038	-	-
3040	-	-
3042	-	-
3046	-	-
3050	Yes	-
3052	-	-
3056	-	-
3060	-	-
3060c	-	-
3060o	-	-
3062	-	-
3230	-	-
3232	-	-
3238	-	-

Date: 09-May-07

Code	Clear Opening	
	Equal	Cottage
3240	-	-
3242	-	-
3246	-	-
3250	-	-
3252	-	-
3256	-	-
3260	-	-
3260c	-	-
3260o	-	-
3262	-	-
3430	-	-
3432	-	-
3438	-	-
3440	-	-
3442	-	-
3446	-	-
3450	-	-
3452	-	-
3456	-	-
3460	-	-
3460c	-	-
3460o	-	-
3462	-	-
3630	-	-
3632	-	-
3638	-	-
3640	-	-
3642	-	-
3646	-	-
3650	-	-

Date: 09-May-07

Code	Clear Opening	
	Equal	Cottage
3652	-	-
3656	-	-
3660	-	-
3660c	-	-
3660o	-	-
3662	-	-
3830	-	-
3832	-	-
3838	-	-
3840	-	-
3842	-	-
3846	-	-
3850	-	-
3852	-	-
3856	-	-
3860	-	-
3860c	-	-
3860o	-	-
3862	-	-
31030	-	-
31032	-	-
31038	-	-
31040	-	-
31042	-	-
31046	-	-
31050	-	-
31052	-	-
31056	-	-
31060	-	-
31060c	-	-

Date: 09-May-07

Code	Clear Opening	
	Equal	Cottage
31060o	-	-
31062	-	-
4030	-	-
4032	-	-
4038	-	-
4040	-	-
4042	-	-
4046	-	-
4050	-	-
4052	-	-
4056	-	-
4060	-	-
4060c	-	-
4060o	-	-
4062	-	-

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Single Window Units

Date: 09-May-07

Window			Width 18 to 210									
Height	Call Out	Unit Dimension	Rough Opening	18	110	20	22	24	26	28	210	
				19 5/8	21 5/8	23 5/8	25 5/8	27 5/8	29 5/8	31 5/8	33 5/8	
				20 1/8	22 1/8	24 1/8	26 1/8	28 1/8	30 1/8	32 1/8	34 1/8	
30	35 3/4	36 1/4	Ventilation	1.5	1.7	1.9	2.1	2.3	2.5	2.7	2.9	
			Daylight	2.9	3.3	3.7	4.1	4.5	4.9	5.3	5.7	
	32	37 3/4	38 1/4	Ventilation	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.1
				Daylight	3.1	3.5	4.0	4.4	4.8	5.2	5.7	6.1
	38	43 3/4	44 1/4	Ventilation	1.9	2.2	2.4	2.7	2.9	3.2	3.4	3.7
				Daylight	3.7	4.2	4.8	5.3	5.8	6.3	6.8	7.3
	40	47 3/4	48 1/4	Ventilation	2.1	2.4	2.7	2.9	3.2	3.5	3.8	4.1
				Daylight	4.2	4.7	5.3	5.8	6.4	7.0	7.5	8.1
	42	49 3/4	50 1/4	Ventilation	2.2	2.5	2.8	3.1	3.4	3.7	4.0	4.3
				Daylight	4.4	4.9	5.5	6.1	6.7	7.3	7.9	8.5
	46	53 3/4	54 1/4	Ventilation	2.4	2.7	3.1	3.4	3.7	4.0	4.4	4.7
				Daylight	4.8	5.4	6.1	6.7	7.3	8.0	8.6	9.3
	50	59 3/4	60 1/4	Ventilation	2.7	3.1	3.5	3.8	4.2	4.6	4.9	5.3
				Daylight	5.4	6.1	6.8	7.6	8.3	9.0	9.8	10.5
52	61 3/4	62 1/4	Ventilation	2.8	3.2	3.6	4.0	4.4	4.7	5.1	5.5	
			Daylight	5.6	6.3	7.1	7.9	8.6	9.4	10.1	10.9	
56	65 3/4	66 1/4	Ventilation	3.1	3.5	3.9	4.3	4.7	5.1	5.5	5.9	
			Daylight	6.0	6.8	7.6	8.4	9.2	10.1	10.9	11.7	
60	71 3/4	72 1/4	Ventilation	3.4	3.8	4.3	4.7	5.2	5.6	6.0	6.5	
			Daylight	6.6	7.5	8.4	9.3	10.2	11.1	12.0	12.9	
60 Cottage	71 3/4	72 1/4	Ventilation	2.7	3.1	3.5	3.8	4.2	4.6	4.9	5.3	
			Daylight	6.1	7.0	7.9	8.8	9.7	10.6	11.5	12.4	
60 Oriel	71 3/4	72 1/4	Ventilation	2.7	3.1	3.5	3.8	4.2	4.6	4.9	5.3	
			Daylight	6.1	7.0	7.9	8.8	9.7	10.6	11.5	12.4	
62	73 3/4	74 1/4	Ventilation	3.5	3.9	4.4	4.9	5.3	5.8	6.2	6.7	
			Daylight	6.8	7.7	8.7	9.6	10.5	11.4	12.4	13.3	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

44" x 77"	DP-25	37 5/8" x 59"	DP-50
33 7/8" x 65"	DP-50	37 7/8" x 65"	DP-50
33 7/8" x 77"	DP-50	37 5/8" x 71" Cottage	DP-30

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Seven D Industries, L.P.
Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Single Window Units

41 5/8" x 59" DP-50

Date: 09-May-07

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Single Window Units

Date: 09-May-07

Window		Width 30 to 40															
Height	Call Out	Unit Dimension		30		32		34		36		38		310		40	
		Rough Opening		35 5/8		37 5/8		39 5/8		41 5/8		43 5/8		45 5/8		47 5/8	
		Rough Opening		36 1/8		38 1/8		40 1/8		42 1/8		44 1/8		46 1/8		48 1/8	
30	35 3/4	36 1/4	Ventilation	3.0	3.2	3.4	3.6	3.8	4.0	4.2							
			Daylight	6.1	6.5	6.9	7.3	7.6	8.0	8.4							
32	37 3/4	38 1/4	Ventilation	3.3	3.5	3.7	3.9	4.1	4.3	4.5							
			Daylight	6.5	6.9	7.3	7.8	8.2	8.6	9.0							
38	43 3/4	44 1/4	Ventilation	3.9	4.2	4.4	4.7	4.9	5.2	5.4							
			Daylight	7.8	8.3	8.8	9.3	9.8	10.3	10.8							
40	47 3/4	48 1/4	Ventilation	4.3	4.6	4.9	5.2	5.5	5.7	6.0							
			Daylight	8.6	9.2	9.8	10.3	10.9	11.4	12.0							
42	49 3/4	50 1/4	Ventilation	4.6	4.9	5.1	5.4	5.7	6.0	6.3							
			Daylight	9.1	9.7	10.2	10.8	11.4	12.0	12.6							
46	53 3/4	54 1/4	Ventilation	5.0	5.3	5.6	6.0	6.3	6.6	6.9							
			Daylight	9.9	10.6	11.2	11.9	12.5	13.1	13.8							
50	59 3/4	60 1/4	Ventilation	5.7	6.0	6.4	6.7	7.1	7.5	7.8							
			Daylight	11.2	11.9	12.7	13.4	14.1	14.8	15.6							
52	61 3/4	62 1/4	Ventilation	5.9	6.2	6.6	7.0	7.4	7.7	8.1							
			Daylight	11.6	12.4	13.1	13.9	14.7	15.4	16.2							
56	65 3/4	66 1/4	Ventilation	6.3	6.7	7.1	7.5	7.9	8.3	8.7							
			Daylight	12.5	13.3	14.1	14.9	15.7	16.5	17.4							
60	71 3/4	72 1/4	Ventilation	6.9	7.4	7.8	8.3	8.7	9.2	9.6							
			Daylight	13.8	14.7	15.6	16.5	17.4	18.2	19.1							
60 Cottage	71 3/4	72 1/4	Ventilation	5.6	6.0	6.4	6.7	7.1	7.5	7.8							
			Daylight	13.3	14.2	15.1	16.0	16.8	17.7	18.6							
60 Oriel	71 3/4	72 1/4	Ventilation	5.6	6.0	6.4	6.7	7.1	7.5	7.8							
			Daylight	13.3	14.2	15.1	16.0	16.8	17.7	18.6							
62	73 3/4	74 1/4	Ventilation	7.2	7.6	8.1	8.5	9.0	9.5	9.9							
			Daylight	14.2	15.1	16.0	17.0	17.9	18.8	19.7							

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

44" x 77"	DP-25	37 5/8" x 59"	DP-50
33 7/8" x 65"	DP-50	37 7/8" x 65"	DP-50
33 7/8" x 77"	DP-50	37 5/8" x 71" Cottage	DP-30

Seven D Industries, L.P.
Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Single Window Units

41 5/8" x 59"

DP-50

Date: 09-May-07

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Ventilat

Twin Window Units

Window				Width 18 to 210								
Height	Call Out	Rough Opening		18	110	20	22	24	26	28	210	30
				39 3/4	43 3/4	47 3/4	51 3/4	55 3/4	59 3/4	63 3/4	67 3/4	71 3/4
				40 1/4	44 1/4	48 1/4	52 1/4	56 1/4	60 1/4	64 1/4	68 1/4	72 1/4
30	35 3/4	36 1/4	Ventilation	3.0	3.4	3.7	4.1	4.5	4.9	5.3	5.7	6.1
			Daylight	5.8	6.6	7.4	8.2	9.0	9.8	10.6	11.4	12.1
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
32	37 3/4	38 1/4	Ventilation	3.2	3.6	4.0	4.4	4.8	5.3	5.7	6.1	6.5
			Daylight	6.2	7.1	7.9	8.8	9.6	10.5	11.3	12.2	13.0
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
38	43 3/4	44 1/4	Ventilation	3.8	4.3	4.8	5.3	5.8	6.3	6.8	7.3	7.8
			Daylight	7.5	8.5	9.5	10.5	11.5	12.5	13.5	14.6	15.6
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
40	47 3/4	48 1/4	Ventilation	4.2	4.8	5.3	5.9	6.5	7.0	7.6	8.1	8.7
			Daylight	8.3	9.4	10.6	11.7	12.8	13.9	15.0	16.2	17.3
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
42	49 3/4	50 1/4	Ventilation	4.4	5.0	5.6	6.2	6.8	7.4	7.9	8.5	9.1
			Daylight	8.7	9.9	11.1	12.2	13.4	14.6	15.8	17.0	18.1
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
46	53 3/4	54 1/4	Ventilation	4.9	5.5	6.1	6.8	7.4	8.1	8.7	9.3	10.0
			Daylight	9.5	10.8	12.1	13.4	14.7	16.0	17.3	18.6	19.8
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
50	59 3/4	60 1/4	Ventilation	5.5	6.2	6.9	7.7	8.4	9.1	9.8	10.6	11.4
			Daylight	10.8	12.2	13.7	15.1	16.6	18.1	19.5	21.0	22.4
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
52	61 3/4	62 1/4	Ventilation	5.7	6.4	7.2	7.9	8.7	9.5	10.2	11.0	11.7
			Daylight	11.2	12.7	14.2	15.7	17.2	18.7	20.2	21.8	23.3
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
56	65 3/4	66 1/4	Ventilation	6.1	6.9	7.7	8.5	9.3	10.2	11.0	11.8	12.6
			Daylight	12.0	13.6	15.3	16.9	18.5	20.1	21.7	23.4	25.0
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
60	71 3/4	72 1/4	Ventilation	6.7	7.6	8.5	9.4	10.3	11.2	12.1	13.0	13.9
			Daylight	13.2	15.0	16.8	18.6	20.4	22.2	24.0	25.8	27.6
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30
60 Cottage	71 3/4	72 1/4	Ventilation	5.5	6.2	6.9	7.7	8.4	9.1	9.8	10.6	11.3
			Daylight	13.3	15.1	16.9	18.7	20.5	22.3	24.0	25.8	27.6
			Design Pressure	NT	NT	NT	NT	NT	NT	NT	NT	NT
60 Oriel	71 3/4	72 1/4	Ventilation	5.5	6.2	6.9	7.7	8.4	9.1	9.8	10.6	11.3
			Daylight	13.3	15.1	16.9	18.7	20.5	22.3	24.0	25.8	27.6
			Design Pressure	NT	NT	NT	NT	NT	NT	NT	NT	NT
62	73 3/4	74 1/4	Ventilation	7.0	7.9	8.8	9.7	10.6	11.5	12.5	13.4	14.3
			Daylight	13.7	15.5	17.3	19.2	21.0	22.9	24.7	26.6	28.4
			Design Pressure	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30/DP-50	DP-30

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

- 76" x 59" DP-50
- 68" x 65" DP-50
- 68" x 77" DP-50
- 76" x 77" DP-30
- 68 1/4" x 71" DP-40
- 75 3/4" x 71" Cottage DP-35

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Seven D Industries, L.P.
Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Ventilat

Twin Window Units

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Daylight, tion and Design Pressure

Twin Window Units

Window			Width 30 to 40						
Height	Call Out		32	34	36	38	310	40	
		Rough Opening	75 3/4	79 3/4	83 3/4	87 3/4	91 3/4	95 3/4	
			76 1/4	80 1/4	84 1/4	88 1/4	92 1/4	96 1/4	
30	35 3/4	36 1/4	Ventilation	6.5	6.9	7.3	7.7	8.1	8.4
			Daylight	12.9	13.7	14.5	15.3	16.1	16.9
32	37 3/4	38 1/4	Ventilation	6.9	7.4	7.8	8.2	8.6	9.0
			Daylight	13.8	14.7	15.5	16.4	17.2	18.1
38	43 3/4	44 1/4	Ventilation	8.3	8.8	9.3	9.8	10.3	10.8
			Daylight	16.6	17.6	18.6	19.6	20.6	21.6
40	47 3/4	48 1/4	Ventilation	9.2	9.8	10.4	10.9	11.5	12.0
			Daylight	18.4	19.5	20.6	21.8	22.9	24.0
42	49 3/4	50 1/4	Ventilation	9.7	10.3	10.9	11.5	12.0	12.6
			Daylight	19.3	20.5	21.7	22.8	24.0	25.2
46	53 3/4	54 1/4	Ventilation	10.6	11.3	11.9	12.5	13.2	13.8
			Daylight	21.1	22.4	23.7	25.0	26.3	27.6
50	59 3/4	60 1/4	Ventilation	12.0	12.7	13.5	14.2	14.9	15.6
			Daylight	23.9	25.3	26.8	28.2	29.7	31.1
52	61 3/4	62 1/4	Ventilation	12.5	13.2	14.0	14.7	15.5	16.2
			Daylight	24.8	26.3	27.8	29.3	30.8	32.3
56	65 3/4	66 1/4	Ventilation	13.4	14.2	15.0	15.8	16.6	17.4
			Daylight	26.6	28.2	29.8	31.5	33.1	34.7
60	71 3/4	72 1/4	Ventilation	14.8	15.7	16.5	17.4	18.3	19.2
			Daylight	29.3	31.1	32.9	34.7	36.5	38.3
60 Cottage	71 3/4	72 1/4	Ventilation	12.0	12.7	13.5	14.2	14.9	15.6
			Daylight	29.4	31.2	33.0	34.8	36.6	38.3
60 Oriel	71 3/4	72 1/4	Ventilation	12.0	12.7	13.5	14.2	14.9	15.6
			Daylight	29.4	31.2	33.0	34.8	36.6	38.3
62	73 3/4	74 1/4	Ventilation	15.2	16.1	17.1	18.0	18.9	19.8
			Daylight	30.2	32.1	33.9	35.8	37.6	39.5

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

76" x 59"	DP-50	68" x 65"	DP-50
68" x 77"	DP-50	76" x 77"	DP-30
68 1/4" x 71"	DP-40	75 3/4" x 71" Cottage	DP-35

Seven D Industries, L.P.
Series 5800 Single Hung

Product Specifications - Daylight, tion and Design Pressure

Twin Window Units

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Ventilat

Twin Window Units

Window		Width 18 to 210										
Height	Call Out	18	110	20	22	24	26	28	210	30		
	Rough Opening	59 7/8	65 7/8	71 7/8	77 7/8	83 7/8	89 7/8	95 7/8	101 7/8	107 7/8		
		60 3/8	66 3/8	72 3/8	78 3/8	84 3/8	90 3/8	96 3/8	102 3/8	108 3/8		
30	35 3/4	36 1/4	Ventilation	4.4	5.0	5.6	6.2	6.8	7.4	8.0	8.6	9.1
			Daylight	8.8	9.9	11.1	12.3	13.5	14.7	15.9	17.0	18.2
	Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	NT
		32	37 3/4	38 1/4	Ventilation	4.7	5.4	6.0	6.6	7.3	7.9	8.5
	Daylight	9.4	10.6	11.9	13.2	14.4	15.7	17.0	18.2	19.5		
		Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	NT
	38		43 3/4	44 1/4	Ventilation	5.7	6.4	7.2	8.0	8.7	9.5	10.2
	Daylight	11.2	12.7	14.3	15.8	17.3	18.8	20.3	21.8	23.4		
		Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	NT
	40		47 3/4	48 1/4	Ventilation	6.3	7.1	8.0	8.8	9.7	10.5	11.4
	Daylight	12.5	14.1	15.8	17.5	19.2	20.9	22.6	24.2	25.9		
		Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	NT
	42		49 3/4	50 1/4	Ventilation	6.6	7.5	8.4	9.3	10.2	11.0	11.9
	Daylight	13.1	14.8	16.6	18.4	20.1	21.9	23.7	25.4	27.2		
Design Pressure		DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	NT	
	46	53 3/4	54 1/4	Ventilation	7.2	8.2	9.2	10.2	11.1	12.1	13.1	14.0
Daylight	14.3	16.2	18.2	20.1	22.0	24.0	25.9	27.8	29.8			
	Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	NT	
50		59 3/4	60 1/4	Ventilation	8.2	9.3	10.4	11.5	12.6	13.7	14.7	15.8
Daylight	16.2	18.3	20.5	22.7	24.9	27.1	29.3	31.4	33.6			
	Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	NT	
52		61 3/4	62 1/4	Ventilation	8.5	9.6	10.8	11.9	13.1	14.2	15.3	16.4
Daylight	16.8	19.0	21.3	23.6	25.8	28.1	30.4	32.6	-			
	Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	-	
56		65 3/4	66 1/4	Ventilation	9.1	10.3	11.6	12.8	14.0	15.2	16.4	17.7
Daylight	18.0	20.4	22.9	25.3	27.7	30.2	32.6	35.0	-			
	Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	-	
60		71 3/4	72 1/4	Ventilation	10.1	11.4	12.8	14.1	15.5	16.8	18.1	19.5
Daylight	19.9	22.5	25.2	27.9	30.6	33.3	36.0	38.6	-			
	Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	-	
60 Cottage		71 3/4	72 1/4	Ventilation	6.9	7.9	8.8	9.7	10.6	11.6	12.5	13.4
Daylight	20.0	22.7	25.3	28.0	30.7	33.4	36.1	38.7	-			
	Design Pressure	NT	NT	NT	NT	NT	NT	NT	NT	NT	-	
60 Oriel		71 3/4	72 1/4	Ventilation	6.9	7.9	8.8	9.7	10.6	11.6	12.5	13.4
Daylight	20.0	22.7	25.3	28.0	30.7	33.4	36.1	38.7	-			
	Design Pressure	NT	NT	NT	NT	NT	NT	NT	NT	NT	-	
62		73 3/4	74 1/4	Ventilation	10.4	11.8	13.2	14.6	15.9	17.3	18.7	20.1
Daylight	20.5	23.2	26.0	28.8	31.5	34.3	37.1	39.8	-			
	Design Pressure	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	DP-35	-	

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

102 5/8" x 65"

DP-35

102 5/8" x 77"

DP-35

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Seven D Industries, L.P.
Series 5800 Single Hung

Product Specifications - Daylight, Ventilation and Design Pressure

Ventilat

Twin Window Units

Seven D Industries, L.P.

Series 5800 Single Hung

Product Specifications - Daylight, tion and Design Pressure

Twin Window Units

Window		Width 30 to 40							
Height	Call Out	Rough Opening		32	34	36	38	310	40
				113 7/8	119 7/8	125 7/8	131 7/8	137 7/8	143 7/8
				114 3/8	120 3/8	126 3/8	132 3/8	138 3/8	144 3/8
30	35 3/4	36 1/4	Ventilation	9.7	10.3	10.9	11.5	12.1	12.7
			Daylight	19.4	20.6	21.8	22.9	24.1	25.3
			Design Pressure	NT	NT	NT	NT	NT	NT
32	37 3/4	38 1/4	Ventilation	10.4	11.0	11.7	12.3	12.9	13.6
			Daylight	20.8	22.0	23.3	24.6	25.8	27.1
			Design Pressure	NT	NT	NT	NT	NT	NT
38	43 3/4	44 1/4	Ventilation	12.5	13.2	14.0	14.7	15.5	16.3
			Daylight	24.9	26.4	27.9	29.4	30.9	32.4
			Design Pressure	NT	NT	NT	NT	NT	NT
40	47 3/4	48 1/4	Ventilation	13.9	14.7	15.5	16.4	-	-
			Daylight	27.6	29.3	31.0	32.6	-	-
			Design Pressure	NT	NT	NT	NT	-	-
42	49 3/4	50 1/4	Ventilation	14.6	15.4	16.3	-	-	-
			Daylight	29.0	30.7	32.5	-	-	-
			Design Pressure	NT	NT	NT	-	-	-
46	53 3/4	54 1/4	Ventilation	15.9	16.9	-	-	-	-
			Daylight	31.7	33.6	-	-	-	-
			Design Pressure	NT	NT	-	-	-	-
50	59 3/4	60 1/4	Ventilation	-	-	-	-	-	-
			Daylight	-	-	-	-	-	-
			Design Pressure	-	-	-	-	-	-
52	61 3/4	62 1/4	Ventilation	-	-	-	-	-	-
			Daylight	-	-	-	-	-	-
			Design Pressure	-	-	-	-	-	-
56	65 3/4	66 1/4	Ventilation	-	-	-	-	-	-
			Daylight	-	-	-	-	-	-
			Design Pressure	-	-	-	-	-	-
60	71 3/4	72 1/4	Ventilation	-	-	-	-	-	-
			Daylight	-	-	-	-	-	-
			Design Pressure	-	-	-	-	-	-
60 Cottage	71 3/4	72 1/4	Ventilation	-	-	-	-	-	-
			Daylight	-	-	-	-	-	-
			Design Pressure	-	-	-	-	-	-
60 Oriel	71 3/4	72 1/4	Ventilation	-	-	-	-	-	-
			Daylight	-	-	-	-	-	-
			Design Pressure	-	-	-	-	-	-
62	73 3/4	74 1/4	Ventilation	-	-	-	-	-	-
			Daylight	-	-	-	-	-	-
			Design Pressure	-	-	-	-	-	-

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions:

102 5/8" x 65"

DP-35

102 5/8" x 77"

DP-35

Note: Daylight and Ventilation calculations are given in square foot of area
10/19/2006

Seven D Industries, L.P.
Series 5800 Single Hung

Product Specifications - Daylight, tion and Design Pressure

Twin Window Units

Seven D Industries, L.P.

Series 5800 Single Hung

Screen Dimensions

Code	Unit Dimensions			Screen Dimensions			Code	Unit Dimensions			Screen Dimensions		
	Width	Height		Width	Height			Width	Height		Width	Height	
1830	19 5/8	x	35 3/4	15 9/16	x	16 13/16	2430	27 5/8	x	35 3/4	23 9/16	x	16 13/16
1832	19 5/8	x	37 3/4	15 9/16	x	17 13/16	2432	27 5/8	x	37 3/4	23 9/16	x	17 13/16
1838	19 5/8	x	43 3/4	15 9/16	x	20 13/16	2438	27 5/8	x	43 3/4	23 9/16	x	20 13/16
1840	19 5/8	x	47 3/4	15 9/16	x	22 13/16	2440	27 5/8	x	47 3/4	23 9/16	x	22 13/16
1842	19 5/8	x	49 3/4	15 9/16	x	23 13/16	2442	27 5/8	x	49 3/4	23 9/16	x	23 13/16
1846	19 5/8	x	53 3/4	15 9/16	x	25 13/16	2446	27 5/8	x	53 3/4	23 9/16	x	25 13/16
1850	19 5/8	x	59 3/4	15 9/16	x	28 13/16	2450	27 5/8	x	59 3/4	23 9/16	x	28 13/16
1852	19 5/8	x	61 3/4	15 9/16	x	29 13/16	2452	27 5/8	x	61 3/4	23 9/16	x	29 13/16
1856	19 5/8	x	65 3/4	15 9/16	x	31 13/16	2456	27 5/8	x	65 3/4	23 9/16	x	31 13/16
1860	19 5/8	x	71 3/4	15 9/16	x	34 13/16	2460	27 5/8	x	71 3/4	23 9/16	x	34 13/16
1860c	19 5/8	x	71 3/4	15 9/16	x	40 13/16	2460c	27 5/8	x	71 3/4	23 9/16	x	40 13/16
1860o	19 5/8	x	71 3/4	15 9/16	x	28 13/16	2460o	27 5/8	x	71 3/4	23 9/16	x	28 13/16
1862	19 5/8	x	73 3/4	15 9/16	x	35 13/16	2462	27 5/8	x	73 3/4	23 9/16	x	35 13/16
11030	21 5/8	x	35 3/4	17 9/16	x	16 13/16	2630	29 5/8	x	35 3/4	25 9/16	x	16 13/16
11032	21 5/8	x	37 3/4	17 9/16	x	17 13/16	2632	29 5/8	x	37 3/4	25 9/16	x	17 13/16
11038	21 5/8	x	43 3/4	17 9/16	x	20 13/16	2638	29 5/8	x	43 3/4	25 9/16	x	20 13/16
11040	21 5/8	x	47 3/4	17 9/16	x	22 13/16	2640	29 5/8	x	47 3/4	25 9/16	x	22 13/16
11042	21 5/8	x	49 3/4	17 9/16	x	23 13/16	2642	29 5/8	x	49 3/4	25 9/16	x	23 13/16
11046	21 5/8	x	53 3/4	17 9/16	x	25 13/16	2646	29 5/8	x	53 3/4	25 9/16	x	25 13/16
11050	21 5/8	x	59 3/4	17 9/16	x	28 13/16	2650	29 5/8	x	59 3/4	25 9/16	x	28 13/16
11052	21 5/8	x	61 3/4	17 9/16	x	29 13/16	2652	29 5/8	x	61 3/4	25 9/16	x	29 13/16
11056	21 5/8	x	65 3/4	17 9/16	x	31 13/16	2656	29 5/8	x	65 3/4	25 9/16	x	31 13/16
11060	21 5/8	x	71 3/4	17 9/16	x	34 13/16	2660	29 5/8	x	71 3/4	25 9/16	x	34 13/16
11060c	21 5/8	x	71 3/4	17 9/16	x	40 13/16	2660c	29 5/8	x	71 3/4	25 9/16	x	40 13/16
11060o	21 5/8	x	71 3/4	17 9/16	x	28 13/16	2660o	29 5/8	x	71 3/4	25 9/16	x	28 13/16
11062	21 5/8	x	73 3/4	17 9/16	x	35 13/16	2662	29 5/8	x	73 3/4	25 9/16	x	35 13/16
2030	23 5/8	x	35 3/4	19 9/16	x	16 13/16	2830	31 5/8	x	35 3/4	27 9/16	x	16 13/16
2032	23 5/8	x	37 3/4	19 9/16	x	17 13/16	2832	31 5/8	x	37 3/4	27 9/16	x	17 13/16
2038	23 5/8	x	43 3/4	19 9/16	x	20 13/16	2838	31 5/8	x	43 3/4	27 9/16	x	20 13/16
2040	23 5/8	x	47 3/4	19 9/16	x	22 13/16	2840	31 5/8	x	47 3/4	27 9/16	x	22 13/16
2042	23 5/8	x	49 3/4	19 9/16	x	23 13/16	2842	31 5/8	x	49 3/4	27 9/16	x	23 13/16
2046	23 5/8	x	53 3/4	19 9/16	x	25 13/16	2846	31 5/8	x	53 3/4	27 9/16	x	25 13/16
2050	23 5/8	x	59 3/4	19 9/16	x	28 13/16	2850	31 5/8	x	59 3/4	27 9/16	x	28 13/16
2052	23 5/8	x	61 3/4	19 9/16	x	29 13/16	2852	31 5/8	x	61 3/4	27 9/16	x	29 13/16
2056	23 5/8	x	65 3/4	19 9/16	x	31 13/16	2856	31 5/8	x	65 3/4	27 9/16	x	31 13/16
2060	23 5/8	x	71 3/4	19 9/16	x	34 13/16	2860	31 5/8	x	71 3/4	27 9/16	x	34 13/16
2060c	23 5/8	x	71 3/4	19 9/16	x	40 13/16	2860c	31 5/8	x	71 3/4	27 9/16	x	40 13/16
2060o	23 5/8	x	71 3/4	19 9/16	x	28 13/16	2860o	31 5/8	x	71 3/4	27 9/16	x	28 13/16
2062	23 5/8	x	73 3/4	19 9/16	x	35 13/16	2862	31 5/8	x	73 3/4	27 9/16	x	35 13/16
2230	25 5/8	x	35 3/4	21 9/16	x	16 13/16	21030	33 5/8	x	35 3/4	29 9/16	x	16 13/16
2232	25 5/8	x	37 3/4	21 9/16	x	17 13/16	21032	33 5/8	x	37 3/4	29 9/16	x	17 13/16
2238	25 5/8	x	43 3/4	21 9/16	x	20 13/16	21038	33 5/8	x	43 3/4	29 9/16	x	20 13/16
2240	25 5/8	x	47 3/4	21 9/16	x	22 13/16	21040	33 5/8	x	47 3/4	29 9/16	x	22 13/16
2242	25 5/8	x	49 3/4	21 9/16	x	23 13/16	21042	33 5/8	x	49 3/4	29 9/16	x	23 13/16
2246	25 5/8	x	53 3/4	21 9/16	x	25 13/16	21046	33 5/8	x	53 3/4	29 9/16	x	25 13/16
2250	25 5/8	x	59 3/4	21 9/16	x	28 13/16	21050	33 5/8	x	59 3/4	29 9/16	x	28 13/16
2252	25 5/8	x	61 3/4	21 9/16	x	29 13/16	21052	33 5/8	x	61 3/4	29 9/16	x	29 13/16
2256	25 5/8	x	65 3/4	21 9/16	x	31 13/16	21056	33 5/8	x	65 3/4	29 9/16	x	31 13/16
2260	25 5/8	x	71 3/4	21 9/16	x	34 13/16	21060	33 5/8	x	71 3/4	29 9/16	x	34 13/16

Seven D Industries, L.P.

Series 5800 Single Hung

Screen Dimensions

Code	Unit Dimensions		Screen Dimensions		Code	Unit Dimensions		Screen Dimensions	
	Width	Height	Width	Height		Width	Height	Width	Height
2260c	25 5/8	x 71 3/4	21 9/16	x 40 13/16	21060c	33 5/8	x 71 3/4	29 9/16	x 40 13/16
2260o	25 5/8	x 71 3/4	21 9/16	x 28 13/16	21060o	33 5/8	x 71 3/4	29 9/16	x 28 13/16
2262	25 5/8	x 73 3/4	21 9/16	x 35 13/16	21062	33 5/8	x 73 3/4	29 9/16	x 35 13/16
3030	35 5/8	x 35 3/4	31 9/16	x 16 13/16	3830	43 5/8	x 35 3/4	39 9/16	x 16 13/16
3032	35 5/8	x 37 3/4	31 9/16	x 17 13/16	3832	43 5/8	x 37 3/4	39 9/16	x 17 13/16
3038	35 5/8	x 43 3/4	31 9/16	x 20 13/16	3838	43 5/8	x 43 3/4	39 9/16	x 20 13/16
3040	35 5/8	x 47 3/4	31 9/16	x 22 13/16	3840	43 5/8	x 47 3/4	39 9/16	x 22 13/16
3042	35 5/8	x 49 3/4	31 9/16	x 23 13/16	3842	43 5/8	x 49 3/4	39 9/16	x 23 13/16
3046	35 5/8	x 53 3/4	31 9/16	x 25 13/16	3846	43 5/8	x 53 3/4	39 9/16	x 25 13/16
3050	35 5/8	x 59 3/4	31 9/16	x 28 13/16	3850	43 5/8	x 59 3/4	39 9/16	x 28 13/16
3052	35 5/8	x 61 3/4	31 9/16	x 29 13/16	3852	43 5/8	x 61 3/4	39 9/16	x 29 13/16
3056	35 5/8	x 65 3/4	31 9/16	x 31 13/16	3856	43 5/8	x 65 3/4	39 9/16	x 31 13/16
3060	35 5/8	x 71 3/4	31 9/16	x 34 13/16	3860	43 5/8	x 71 3/4	39 9/16	x 34 13/16
3060c	35 5/8	x 71 3/4	31 9/16	x 40 13/16	3860c	43 5/8	x 71 3/4	39 9/16	x 40 13/16
3060o	35 5/8	x 71 3/4	31 9/16	x 28 13/16	3860o	43 5/8	x 71 3/4	39 9/16	x 28 13/16
3062	35 5/8	x 73 3/4	31 9/16	x 35 13/16	3862	43 5/8	x 73 3/4	39 9/16	x 35 13/16
3230	37 5/8	x 35 3/4	33 9/16	x 16 13/16	31030	45 5/8	x 35 3/4	41 9/16	x 16 13/16
3232	37 5/8	x 37 3/4	33 9/16	x 17 13/16	31032	45 5/8	x 37 3/4	41 9/16	x 17 13/16
3238	37 5/8	x 43 3/4	33 9/16	x 20 13/16	31038	45 5/8	x 43 3/4	41 9/16	x 20 13/16
3240	37 5/8	x 47 3/4	33 9/16	x 22 13/16	31040	45 5/8	x 47 3/4	41 9/16	x 22 13/16
3242	37 5/8	x 49 3/4	33 9/16	x 23 13/16	31042	45 5/8	x 49 3/4	41 9/16	x 23 13/16
3246	37 5/8	x 53 3/4	33 9/16	x 25 13/16	31046	45 5/8	x 53 3/4	41 9/16	x 25 13/16
3250	37 5/8	x 59 3/4	33 9/16	x 28 13/16	31050	45 5/8	x 59 3/4	41 9/16	x 28 13/16
3252	37 5/8	x 61 3/4	33 9/16	x 29 13/16	31052	45 5/8	x 61 3/4	41 9/16	x 29 13/16
3256	37 5/8	x 65 3/4	33 9/16	x 31 13/16	31056	45 5/8	x 65 3/4	41 9/16	x 31 13/16
3260	37 5/8	x 71 3/4	33 9/16	x 34 13/16	31060	45 5/8	x 71 3/4	41 9/16	x 34 13/16
3260c	37 5/8	x 71 3/4	33 9/16	x 40 13/16	31060c	45 5/8	x 71 3/4	41 9/16	x 40 13/16
3260o	37 5/8	x 71 3/4	33 9/16	x 28 13/16	31060o	45 5/8	x 71 3/4	41 9/16	x 28 13/16
3262	37 5/8	x 73 3/4	33 9/16	x 35 13/16	31062	45 5/8	x 73 3/4	41 9/16	x 35 13/16
3430	39 5/8	x 35 3/4	35 9/16	x 16 13/16	4030	47 5/8	x 35 3/4	43 9/16	x 16 13/16
3432	39 5/8	x 37 3/4	35 9/16	x 17 13/16	4032	47 5/8	x 37 3/4	43 9/16	x 17 13/16
3438	39 5/8	x 43 3/4	35 9/16	x 20 13/16	4038	47 5/8	x 43 3/4	43 9/16	x 20 13/16
3440	39 5/8	x 47 3/4	35 9/16	x 22 13/16	4040	47 5/8	x 47 3/4	43 9/16	x 22 13/16
3442	39 5/8	x 49 3/4	35 9/16	x 23 13/16	4042	47 5/8	x 49 3/4	43 9/16	x 23 13/16
3446	39 5/8	x 53 3/4	35 9/16	x 25 13/16	4046	47 5/8	x 53 3/4	43 9/16	x 25 13/16
3450	39 5/8	x 59 3/4	35 9/16	x 28 13/16	4050	47 5/8	x 59 3/4	43 9/16	x 28 13/16
3452	39 5/8	x 61 3/4	35 9/16	x 29 13/16	4052	47 5/8	x 61 3/4	43 9/16	x 29 13/16
3456	39 5/8	x 65 3/4	35 9/16	x 31 13/16	4056	47 5/8	x 65 3/4	43 9/16	x 31 13/16
3460	39 5/8	x 71 3/4	35 9/16	x 34 13/16	4060	47 5/8	x 71 3/4	43 9/16	x 34 13/16
3460c	39 5/8	x 71 3/4	35 9/16	x 40 13/16	4060c	47 5/8	x 71 3/4	43 9/16	x 40 13/16
3460o	39 5/8	x 71 3/4	35 9/16	x 28 13/16	4060o	47 5/8	x 71 3/4	43 9/16	x 28 13/16
3462	39 5/8	x 73 3/4	35 9/16	x 35 13/16	4062	47 5/8	x 73 3/4	43 9/16	x 35 13/16
3630	41 5/8	x 35 3/4	37 9/16	x 16 13/16					
3632	41 5/8	x 37 3/4	37 9/16	x 17 13/16					
3638	41 5/8	x 43 3/4	37 9/16	x 20 13/16					
3640	41 5/8	x 47 3/4	37 9/16	x 22 13/16					
3642	41 5/8	x 49 3/4	37 9/16	x 23 13/16					
3646	41 5/8	x 53 3/4	37 9/16	x 25 13/16					
3650	41 5/8	x 59 3/4	37 9/16	x 28 13/16					

Seven D Industries, L.P.

Series 5800 Single Hung

Screen Dimensions

Code	Unit Dimensions			Screen Dimensions		
	Width		Height	Width		Height
3652	41	5/8	x	61	3/4	
3656	41	5/8	x	65	3/4	
3660	41	5/8	x	71	3/4	
3660c	41	5/8	x	71	3/4	
3660o	41	5/8	x	71	3/4	
3662	41	5/8	x	73	3/4	

Code	Unit Dimensions			Screen Dimensions		
	Width		Height	Width		Height

Seven D Industries, L.P.
Series 5800 Single Hung

Thermal Performance Specifications

SSB Glazing

Glass Type	U-Value	SHGC	VT	w/ Grid	
				SHGC	VT
3/4" IG -Clear/air/Clear	.48	.63	.65	.56	.58
3/4" IG – Clear/90% Argon/Low-E	.31	.39	.55	.35	.49

DSB Glazing

Glass Type	U-Value	SHGC	VT	w/ Grid	
				SHGC	VT
3/4" IG -Clear/air/Clear	.48	.61	.65	.55	.58
3/4" IG – Clear/90% Argon/Low-E	.31	.38	.54	.34	.49

Notes: Actual window dimensions have not effect on the Thermal Performance Rating, as the test criteria is based on a per square foot unit.

Seven D Industries, Series 5800 Single Hung windows utilizing Low-E Glass with Argon Fill, meet all requirements for Energy Star compliance.

10/19/2006

Seven D Industries, L.P.

Series 5800 Single Hung

Window Width: 15
Window Height: 52

Ventilation Area: 1.568 sq ft
Daylight Area: 2.833 sq ft