

Seven D Industries, L.P.

Series 5900 Impact Single Hung

Product Specifications - Design Pressure, Daylight and Ventilation

| Code | Single Window Unit | | | | | | | | | | | | |
|--------|--------------------|-----|--------|---------------|----|--------|-----------|----------|-------------|---------------|------|-----|---|
| | Dimensions | | | Rough Opening | | | DP Rating | Daylight | Ventilation | Clear Opening | | | |
| | Width | | Height | Width | | Height | | | | | | | |
| 16210 | 19 | 5/8 | x | 37 | 20 | 1/8 | x | 37 | 1/2 | DP-50 | 3.0 | 1.4 | - |
| 1632 | 19 | 5/8 | x | 41 | 20 | 1/8 | x | 41 | 1/2 | DP-50 | 3.5 | 1.6 | - |
| 16310 | 19 | 5/8 | x | 49 | 20 | 1/8 | x | 49 | 1/2 | DP-50 | 4.3 | 2.0 | - |
| 1642 | 19 | 5/8 | x | 53 | 20 | 1/8 | x | 53 | 1/2 | DP-50 | 4.7 | 2.3 | - |
| 1646 | 19 | 5/8 | x | 57 | 20 | 1/8 | x | 57 | 1/2 | DP-50 | 5.1 | 2.3 | - |
| 1648 | 19 | 5/8 | x | 59 | 20 | 1/8 | x | 59 | 1/2 | DP-50 | 5.3 | 2.4 | - |
| 1652 | 19 | 5/8 | x | 65 | 20 | 1/8 | x | 65 | 1/2 | DP-50 | 5.9 | 2.8 | - |
| 1656 | 19 | 5/8 | x | 69 | 20 | 1/8 | x | 69 | 1/2 | DP-50 | 6.3 | 3.0 | - |
| 1662 | 19 | 5/8 | x | 77 | 20 | 1/8 | x | 77 | 1/2 | DP-50 | 7.2 | 3.4 | - |
| 18210 | 21 | 5/8 | x | 37 | 22 | 1/8 | x | 37 | 1/2 | DP-50 | 3.5 | 1.6 | - |
| 1832 | 21 | 5/8 | x | 41 | 22 | 1/8 | x | 41 | 1/2 | DP-50 | 3.9 | 1.8 | - |
| 18310 | 21 | 5/8 | x | 49 | 22 | 1/8 | x | 49 | 1/2 | DP-50 | 4.9 | 2.3 | - |
| 1842 | 21 | 5/8 | x | 53 | 22 | 1/8 | x | 53 | 1/2 | DP-50 | 5.3 | 2.4 | - |
| 1846 | 21 | 5/8 | x | 57 | 22 | 1/8 | x | 57 | 1/2 | DP-50 | 5.8 | 2.6 | - |
| 1848 | 21 | 5/8 | x | 59 | 22 | 1/8 | x | 59 | 1/2 | DP-50 | 6.0 | 2.8 | - |
| 1852 | 21 | 5/8 | x | 65 | 22 | 1/8 | x | 65 | 1/2 | DP-50 | 6.7 | 3.1 | - |
| 1856 | 21 | 5/8 | x | 69 | 22 | 1/8 | x | 69 | 1/2 | DP-50 | 7.2 | 3.4 | - |
| 1862 | 21 | 5/8 | x | 77 | 22 | 1/8 | x | 77 | 1/2 | DP-50 | 8.1 | 3.8 | - |
| 110210 | 23 | 5/8 | x | 37 | 24 | 1/8 | x | 37 | 1/2 | DP-50 | 3.9 | 1.8 | - |
| 11032 | 23 | 5/8 | x | 41 | 24 | 1/8 | x | 41 | 1/2 | DP-50 | 4.4 | 2.1 | - |
| 110310 | 23 | 5/8 | x | 49 | 24 | 1/8 | x | 49 | 1/2 | DP-50 | 5.4 | 2.4 | - |
| 11042 | 23 | 5/8 | x | 53 | 24 | 1/8 | x | 53 | 1/2 | DP-50 | 6.0 | 2.7 | - |
| 11046 | 23 | 5/8 | x | 57 | 24 | 1/8 | x | 57 | 1/2 | DP-50 | 6.5 | 2.9 | - |
| 11048 | 23 | 5/8 | x | 59 | 24 | 1/8 | x | 59 | 1/2 | DP-50 | 6.7 | 3.1 | - |
| 11052 | 23 | 5/8 | x | 65 | 24 | 1/8 | x | 65 | 1/2 | DP-50 | 7.5 | 3.5 | - |
| 11056 | 23 | 5/8 | x | 69 | 24 | 1/8 | x | 69 | 1/2 | DP-50 | 8.1 | 3.7 | - |
| 11062 | 23 | 5/8 | x | 77 | 24 | 1/8 | x | 77 | 1/2 | DP-50 | 9.1 | 4.3 | - |
| 20210 | 25 | 5/8 | x | 37 | 26 | 1/8 | x | 37 | 1/2 | DP-50 | 4.3 | 2.0 | - |
| 2032 | 25 | 5/8 | x | 41 | 26 | 1/8 | x | 41 | 1/2 | DP-50 | 4.9 | 2.3 | - |
| 20310 | 25 | 5/8 | x | 49 | 26 | 1/8 | x | 49 | 1/2 | DP-50 | 6.0 | 2.7 | - |
| 2042 | 25 | 5/8 | x | 53 | 26 | 1/8 | x | 53 | 1/2 | DP-50 | 6.6 | 3.0 | - |
| 2046 | 25 | 5/8 | x | 57 | 26 | 1/8 | x | 57 | 1/2 | DP-50 | 7.2 | 3.3 | - |
| 2048 | 25 | 5/8 | x | 59 | 26 | 1/8 | x | 59 | 1/2 | DP-50 | 7.5 | 3.4 | - |
| 2052 | 25 | 5/8 | x | 65 | 26 | 1/8 | x | 65 | 1/2 | DP-50 | 8.3 | 3.8 | - |
| 2056 | 25 | 5/8 | x | 69 | 26 | 1/8 | x | 69 | 1/2 | DP-50 | 8.9 | 4.1 | - |
| 2062 | 25 | 5/8 | x | 77 | 26 | 1/8 | x | 77 | 1/2 | DP-50 | 10.1 | 4.7 | - |

Note: Daylight and Ventilation calculations are given in square foot of area

Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 60 5/8"

Seven D Industries, L.P.

Series 5900 Impact Single Hung

Product Specifications - Design Pressure, Daylight and Ventilation

| Code | Single Window Unit | | | | | | | | | |
|-------|--------------------|--------|----|---------------|--------|--------|-----------|----------|-------------|---------------|
| | Dimensions | | | Rough Opening | | | DP Rating | Daylight | Ventilation | Clear Opening |
| | Width | Height | | Width | Height | | | | | |
| 22210 | 27 5/8 | x | 37 | 28 1/8 | x | 37 1/2 | DP-50 | 4.7 | 2.2 | - |
| 2232 | 27 5/8 | x | 41 | 28 1/8 | x | 41 1/2 | DP-50 | 5.3 | 2.3 | - |
| 22310 | 27 5/8 | x | 49 | 28 1/8 | x | 49 1/2 | DP-50 | 6.6 | 2.9 | - |
| 2242 | 27 5/8 | x | 53 | 28 1/8 | x | 53 1/2 | DP-50 | 7.2 | 3.2 | - |
| 2246 | 27 5/8 | x | 57 | 28 1/8 | x | 57 1/2 | DP-50 | 7.9 | 3.6 | - |
| 2248 | 27 5/8 | x | 59 | 28 1/8 | x | 59 1/2 | DP-50 | 8.2 | 3.7 | - |
| 2252 | 27 5/8 | x | 65 | 28 1/8 | x | 65 1/2 | DP-50 | 9.1 | 4.2 | - |
| 2256 | 27 5/8 | x | 69 | 28 1/8 | x | 69 1/2 | DP-50 | 9.8 | 4.5 | - |
| 2262 | 27 5/8 | x | 77 | 28 1/8 | x | 77 1/2 | DP-50 | 11.0 | 5.2 | - |
| 24210 | 29 5/8 | x | 37 | 30 1/8 | x | 37 1/2 | DP-50 | 5.1 | 2.1 | - |
| 2432 | 29 5/8 | x | 41 | 30 1/8 | x | 41 1/2 | DP-50 | 5.8 | 2.5 | - |
| 24310 | 29 5/8 | x | 49 | 30 1/8 | x | 49 1/2 | DP-50 | 7.2 | 3.2 | - |
| 2442 | 29 5/8 | x | 53 | 30 1/8 | x | 53 1/2 | DP-50 | 7.9 | 3.5 | - |
| 2446 | 29 5/8 | x | 57 | 30 1/8 | x | 57 1/2 | DP-50 | 8.6 | 3.9 | - |
| 2448 | 29 5/8 | x | 59 | 30 1/8 | x | 59 1/2 | DP-50 | 8.9 | 4.0 | - |
| 2452 | 29 5/8 | x | 65 | 30 1/8 | x | 65 1/2 | DP-50 | 9.9 | 4.6 | - |
| 2456 | 29 5/8 | x | 69 | 30 1/8 | x | 69 1/2 | DP-50 | 10.6 | 4.9 | - |
| 2462 | 29 5/8 | x | 77 | 30 1/8 | x | 77 1/2 | DP-50 | 12.0 | 5.4 | - |
| 26210 | 31 5/8 | x | 37 | 32 1/8 | x | 37 1/2 | DP-50 | 5.5 | 2.3 | - |
| 2632 | 31 5/8 | x | 41 | 32 1/8 | x | 41 1/2 | DP-50 | 6.3 | 2.7 | - |
| 26310 | 31 5/8 | x | 49 | 32 1/8 | x | 49 1/2 | DP-50 | 7.8 | 3.4 | - |
| 2642 | 31 5/8 | x | 53 | 32 1/8 | x | 53 1/2 | DP-50 | 8.5 | 3.8 | - |
| 2646 | 31 5/8 | x | 57 | 32 1/8 | x | 57 1/2 | DP-50 | 9.2 | 4.2 | - |
| 2648 | 31 5/8 | x | 59 | 32 1/8 | x | 59 1/2 | DP-50 | 9.6 | 4.4 | - |
| 2652 | 31 5/8 | x | 65 | 32 1/8 | x | 65 1/2 | DP-50 | 10.7 | 4.9 | - |
| 2656 | 31 5/8 | x | 69 | 32 1/8 | x | 69 1/2 | DP-50 | 11.5 | 5.1 | - |
| 2662 | 31 5/8 | x | 77 | 32 1/8 | x | 77 1/2 | DP-50 | 13.0 | 5.8 | yes |
| 28210 | 33 5/8 | x | 37 | 34 1/8 | x | 37 1/2 | DP-50 | 5.9 | 2.5 | - |
| 2832 | 33 5/8 | x | 41 | 34 1/8 | x | 41 1/2 | DP-50 | 6.7 | 2.9 | - |
| 28310 | 33 5/8 | x | 49 | 34 1/8 | x | 49 1/2 | DP-50 | 8.3 | 3.7 | - |
| 2842 | 33 5/8 | x | 53 | 34 1/8 | x | 53 1/2 | DP-50 | 9.1 | 4.1 | - |
| 2846 | 33 5/8 | x | 57 | 34 1/8 | x | 57 1/2 | DP-50 | 9.9 | 4.5 | - |
| 2848 | 33 5/8 | x | 59 | 34 1/8 | x | 59 1/2 | DP-50 | 10.3 | 4.7 | - |
| 2852 | 33 5/8 | x | 65 | 34 1/8 | x | 65 1/2 | DP-50 | 11.5 | 5.0 | - |
| 2856 | 33 5/8 | x | 69 | 34 1/8 | x | 69 1/2 | DP-50 | 12.3 | 5.7 | yes |
| 2862 | 33 5/8 | x | 77 | 34 1/8 | x | 77 1/2 | DP-50 | 13.9 | 6.3 | yes |

Note: Daylight and Ventilation calculations are given in square foot of area

Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 60 5/8"

Seven D Industries, L.P.

Series 5900 Impact Single Hung

Product Specifications - Design Pressure, Daylight and Ventilation

| Code | Single Window Unit | | | | | | | | | |
|--------|--------------------|--------|----|---------------|--------|--------|-----------|----------|-------------|---------------|
| | Dimensions | | | Rough Opening | | | DP Rating | Daylight | Ventilation | Clear Opening |
| | Width | Height | | Width | Height | | | | | |
| 210210 | 35 5/8 | x | 37 | 36 1/8 | x | 37 1/2 | DP-50 | 6.3 | 2.6 | - |
| 21032 | 35 5/8 | x | 41 | 36 1/8 | x | 41 1/2 | DP-50 | 7.2 | 3.1 | - |
| 210310 | 35 5/8 | x | 49 | 36 1/8 | x | 49 1/2 | DP-50 | 8.9 | 3.9 | - |
| 21042 | 35 5/8 | x | 53 | 36 1/8 | x | 53 1/2 | DP-50 | 9.8 | 4.4 | - |
| 21046 | 35 5/8 | x | 57 | 36 1/8 | x | 57 1/2 | DP-50 | 10.6 | 4.8 | - |
| 21048 | 35 5/8 | x | 59 | 36 1/8 | x | 59 1/2 | DP-50 | 11.0 | 5.0 | - |
| 21052 | 35 5/8 | x | 65 | 36 1/8 | x | 65 1/2 | DP-50 | 12.3 | 5.7 | yes |
| 21056 | 35 5/8 | x | 69 | 36 1/8 | x | 69 1/2 | DP-50 | 13.2 | 5.8 | yes |
| 21062 | 35 5/8 | x | 77 | 36 1/8 | x | 77 1/2 | DP-50 | 14.9 | 6.7 | yes |
| 30210 | 37 5/8 | x | 37 | 38 1/8 | x | 37 1/2 | DP-50 | 6.8 | 2.8 | - |
| 3032 | 37 5/8 | x | 41 | 38 1/8 | x | 41 1/2 | DP-50 | 7.7 | 3.3 | - |
| 30310 | 37 5/8 | x | 49 | 38 1/8 | x | 49 1/2 | DP-50 | 9.5 | 4.2 | - |
| 3042 | 37 5/8 | x | 53 | 38 1/8 | x | 53 1/2 | DP-50 | 10.4 | 4.6 | - |
| 3046 | 37 5/8 | x | 57 | 38 1/8 | x | 57 1/2 | DP-50 | 11.3 | 5.1 | - |
| 3048 | 37 5/8 | x | 59 | 38 1/8 | x | 59 1/2 | DP-50 | 11.8 | 5.0 | - |
| 3052 | 37 5/8 | x | 65 | 38 1/8 | x | 65 1/2 | DP-50 | 13.1 | 5.7 | yes |
| 3056 | 37 5/8 | x | 69 | 38 1/8 | x | 69 1/2 | DP-55 | 14.0 | 6.2 | yes |
| 3062 | 37 5/8 | x | 77 | 38 1/8 | x | 77 1/2 | DP-55 | 15.9 | 7.1 | yes |

Custom Sized Windows

| Code | Single Window Unit | | | | | | | | | |
|------|--------------------|--------|--------|---------------|--------|--------|-----------|----------|-------------|---------------|
| | Dimensions | | | Rough Opening | | | DP Rating | Daylight | Ventilation | Clear Opening |
| | Width | Height | | Width | Height | | | | | |
| | 35 5/8 | x | 65 3/4 | 36 1/8 | x | 66 1/4 | DP-50 | 12.5 | 5.7 | yes |
| | 37 5/8 | x | 61 3/4 | 38 1/8 | x | 62 1/4 | DP-50 | 12.4 | 5.7 | yes |

Note: Daylight and Ventilation calculations are given in square foot of area

Yes - Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 sq ft area

Minimum window width for 20" clear opening width – 24 1/2"

Minimum window height for 24" clear opening height – 60 5/8"

Seven D Industries, L.P.

Series 5900 Impact Single Hung

Product Specifications - Ventilation, Daylight and Design Pressure

Single Window Units

Note: Daylight and Ventilation calculations are given in square foot of area

| Window | | Width | | | | | | | | | | | |
|--------|----------|----------------|---------------|-----------------|--------|--------|--------|--------|--------|--------|--------|--------|-------|
| Height | Call Out | Unit Dimension | | 16 | 18 | 110 | 20 | 22 | 24 | 26 | 28 | 210 | |
| | 210 | 37 | Rough Opening | 19 5/8 | 21 5/8 | 23 5/8 | 25 5/8 | 27 5/8 | 29 5/8 | 31 5/8 | 33 5/8 | 35 5/8 | |
| | | | 20 1/8 | 22 1/8 | 24 1/8 | 26 1/8 | 28 1/8 | 30 1/8 | 32 1/8 | 34 1/8 | 36 1/8 | | |
| | | | | Ventilation | 1.3 | 1.5 | 1.7 | 1.9 | 2.0 | 2.2 | 2.4 | 2.6 | 2.7 |
| | | | | Daylight | 3.0 | 3.5 | 3.9 | 4.3 | 4.7 | 5.1 | 5.5 | 5.9 | 6.3 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 32 | 41 | 41 1/2 | Ventilation | 1.5 | 1.7 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 |
| | | | | Daylight | 3.5 | 3.9 | 4.4 | 4.9 | 5.3 | 5.8 | 6.3 | 6.7 | 7.2 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 310 | 49 | 49 1/2 | Ventilation | 2.0 | 2.2 | 2.5 | 2.7 | 3.0 | 3.3 | 3.5 | 3.8 | 4.0 |
| | | | | Daylight | 4.3 | 4.9 | 5.4 | 6.0 | 6.6 | 7.2 | 7.8 | 8.3 | 8.9 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 42 | 53 | 53 1/2 | Ventilation | 2.2 | 2.5 | 2.7 | 3.0 | 3.3 | 3.6 | 3.9 | 4.2 | 4.5 |
| | | | | Daylight | 4.7 | 5.3 | 6.0 | 6.6 | 7.2 | 7.9 | 8.5 | 9.1 | 9.8 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 46 | 57 | 57 1/2 | Ventilation | 2.4 | 2.7 | 3.0 | 3.3 | 3.6 | 4.0 | 4.3 | 4.6 | 4.9 |
| | | | | Daylight | 5.1 | 5.8 | 6.5 | 7.2 | 7.9 | 8.6 | 9.2 | 9.9 | 10.6 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 48 | 59 | 59 1/2 | Ventilation | 2.5 | 2.8 | 3.1 | 3.5 | 3.8 | 4.1 | 4.5 | 4.8 | 5.1 |
| | | | | Daylight | 5.3 | 6.0 | 6.7 | 7.5 | 8.2 | 8.9 | 9.6 | 10.3 | 11.0 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 52 | 65 | 65 1/2 | Ventilation | 2.8 | 3.2 | 3.5 | 3.9 | 4.3 | 4.7 | 5.0 | 5.4 | 5.8 |
| | | | | Daylight | 5.9 | 6.7 | 7.5 | 8.3 | 9.1 | 9.9 | 10.7 | 11.5 | 12.3 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 56 | 69 | 69 1/2 | Ventilation | 3.0 | 3.4 | 3.8 | 4.2 | 4.6 | 5.0 | 5.4 | 5.8 | 6.2 |
| | | | | Daylight | 6.3 | 7.2 | 8.1 | 8.9 | 9.8 | 10.6 | 11.5 | 12.3 | 13.2 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |
| | 62 | 77 | 77 1/2 | Ventilation | 3.4 | 3.9 | 4.3 | 4.8 | 5.2 | 5.7 | 6.2 | 6.6 | 7.1 |
| | | | | Daylight | 7.2 | 8.1 | 9.1 | 10.1 | 11.0 | 12.0 | 13.0 | 13.9 | 14.9 |
| | | | | Design Pressure | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 | DP-50 |

Meets Clear Opening Requirements: 20" width, 24" height, & 5.7 Sq ft Area

Test Window Dimensions: 37 5/8" x 77" DP-50

| |
|--------|
| |
| 30 |
| 37 5/8 |
| 38 1/8 |
| 2.9 |
| 6.8 |
| DP-50 |
| 3.4 |
| 7.7 |
| DP-50 |
| 4.3 |
| 9.5 |
| DP-50 |
| 4.8 |
| 10.4 |
| DP-50 |
| 5.2 |
| 11.3 |
| DP-50 |
| 5.4 |
| 11.8 |
| DP-50 |
| 6.1 |
| 13.1 |
| DP-50 |
| 6.6 |
| 14.0 |
| DP-50 |
| 7.5 |
| 15.9 |
| DP-50 |

Seven D Industries, L.P.

Series 5900 Impact Single Hung

Screen Dimensions

| Code | Dimensions | | Screen Dimensions | | Code | Dimensions | | Screen Dimensions | |
|--------|------------|--------|-------------------|-----------|--------|------------|--------|-------------------|-----------|
| | Width | Height | Width | Height | | Width | Height | Width | Height |
| 16210 | 19 5/8 | x 37 | 15 9/16 | x 16 1/16 | 24210 | 29 5/8 | x 37 | 25 9/16 | x 16 1/16 |
| 1632 | 19 5/8 | x 41 | 15 9/16 | x 18 1/16 | 2432 | 29 5/8 | x 41 | 25 9/16 | x 18 1/16 |
| 16310 | 19 5/8 | x 49 | 15 9/16 | x 22 1/16 | 24310 | 29 5/8 | x 49 | 25 9/16 | x 22 1/16 |
| 1642 | 19 5/8 | x 53 | 15 9/16 | x 24 1/16 | 2442 | 29 5/8 | x 53 | 25 9/16 | x 24 1/16 |
| 1646 | 19 5/8 | x 57 | 15 9/16 | x 26 1/16 | 2446 | 29 5/8 | x 57 | 25 9/16 | x 26 1/16 |
| 1648 | 19 5/8 | x 59 | 15 9/16 | x 27 1/16 | 2448 | 29 5/8 | x 59 | 25 9/16 | x 27 1/16 |
| 1652 | 19 5/8 | x 65 | 15 9/16 | x 30 1/16 | 2452 | 29 5/8 | x 65 | 25 9/16 | x 30 1/16 |
| 1656 | 19 5/8 | x 69 | 15 9/16 | x 32 1/16 | 2456 | 29 5/8 | x 69 | 25 9/16 | x 32 1/16 |
| 1662 | 19 5/8 | x 77 | 15 9/16 | x 36 1/16 | 2462 | 29 5/8 | x 77 | 25 9/16 | x 36 1/16 |
| 18210 | 21 5/8 | x 37 | 17 9/16 | x 16 1/16 | 26210 | 31 5/8 | x 37 | 27 9/16 | x 16 1/16 |
| 1832 | 21 5/8 | x 41 | 17 9/16 | x 18 1/16 | 2632 | 31 5/8 | x 41 | 27 9/16 | x 18 1/16 |
| 18310 | 21 5/8 | x 49 | 17 9/16 | x 22 1/16 | 26310 | 31 5/8 | x 49 | 27 9/16 | x 22 1/16 |
| 1842 | 21 5/8 | x 53 | 17 9/16 | x 24 1/16 | 2642 | 31 5/8 | x 53 | 27 9/16 | x 24 1/16 |
| 1846 | 21 5/8 | x 57 | 17 9/16 | x 26 1/16 | 2646 | 31 5/8 | x 57 | 27 9/16 | x 26 1/16 |
| 1848 | 21 5/8 | x 59 | 17 9/16 | x 27 1/16 | 2648 | 31 5/8 | x 59 | 27 9/16 | x 27 1/16 |
| 1852 | 21 5/8 | x 65 | 17 9/16 | x 30 1/16 | 2652 | 31 5/8 | x 65 | 27 9/16 | x 30 1/16 |
| 1856 | 21 5/8 | x 69 | 17 9/16 | x 32 1/16 | 2658 | 31 5/8 | x 71 | 27 9/16 | x 33 1/16 |
| 1862 | 21 5/8 | x 77 | 17 9/16 | x 36 1/16 | 2662 | 31 5/8 | x 77 | 27 9/16 | x 36 1/16 |
| 110210 | 23 5/8 | x 37 | 19 9/16 | x 16 1/16 | 28210 | 33 7/8 | x 37 | 29 13/16 | x 16 1/16 |
| 11032 | 23 5/8 | x 41 | 19 9/16 | x 18 1/16 | 2832 | 33 7/8 | x 41 | 29 13/16 | x 18 1/16 |
| 110310 | 23 5/8 | x 49 | 19 9/16 | x 22 1/16 | 28310 | 33 7/8 | x 49 | 29 13/16 | x 22 1/16 |
| 11042 | 23 5/8 | x 53 | 19 9/16 | x 24 1/16 | 2842 | 33 7/8 | x 53 | 29 13/16 | x 24 1/16 |
| 11046 | 23 5/8 | x 57 | 19 9/16 | x 26 1/16 | 2846 | 33 7/8 | x 57 | 29 13/16 | x 26 1/16 |
| 11048 | 23 5/8 | x 59 | 19 9/16 | x 27 1/16 | 2848 | 33 7/8 | x 59 | 29 13/16 | x 27 1/16 |
| 11052 | 23 5/8 | x 65 | 19 9/16 | x 30 1/16 | 2852 | 33 7/8 | x 65 | 29 13/16 | x 30 1/16 |
| 11056 | 23 5/8 | x 69 | 19 9/16 | x 32 1/16 | 2858 | 33 7/8 | x 71 | 29 13/16 | x 33 1/16 |
| 11062 | 23 5/8 | x 77 | 19 9/16 | x 36 1/16 | 2862 | 33 7/8 | x 77 | 29 13/16 | x 36 1/16 |
| 20210 | 25 5/8 | x 37 | 21 9/16 | x 16 1/16 | 210210 | 35 5/8 | x 37 | 31 9/16 | x 16 1/16 |
| 2032 | 25 5/8 | x 41 | 21 9/16 | x 18 1/16 | 21032 | 35 5/8 | x 41 | 31 9/16 | x 18 1/16 |
| 20310 | 25 5/8 | x 49 | 21 9/16 | x 22 1/16 | 210310 | 35 5/8 | x 49 | 31 9/16 | x 22 1/16 |
| 2042 | 25 5/8 | x 53 | 21 9/16 | x 24 1/16 | 21042 | 35 5/8 | x 53 | 31 9/16 | x 24 1/16 |
| 2046 | 25 5/8 | x 57 | 21 9/16 | x 26 1/16 | 21046 | 35 5/8 | x 57 | 31 9/16 | x 26 1/16 |
| 2048 | 25 5/8 | x 59 | 21 9/16 | x 27 1/16 | 21048 | 35 5/8 | x 59 | 31 9/16 | x 27 1/16 |
| 2052 | 25 5/8 | x 65 | 21 9/16 | x 30 1/16 | 21052 | 35 5/8 | x 65 | 31 9/16 | x 30 1/16 |
| 2056 | 25 5/8 | x 69 | 21 9/16 | x 32 1/16 | 21056 | 35 5/8 | x 69 | 31 9/16 | x 32 1/16 |
| 2062 | 25 5/8 | x 77 | 21 9/16 | x 36 1/16 | 21062 | 35 5/8 | x 77 | 31 9/16 | x 36 1/16 |
| 22210 | 27 5/8 | x 37 | 23 9/16 | x 16 1/16 | 30210 | 37 5/8 | x 37 | 33 9/16 | x 16 1/16 |
| 2232 | 27 5/8 | x 41 | 23 9/16 | x 18 1/16 | 3032 | 37 5/8 | x 41 | 33 9/16 | x 18 1/16 |
| 22310 | 27 5/8 | x 49 | 23 9/16 | x 22 1/16 | 30310 | 37 5/8 | x 49 | 33 9/16 | x 22 1/16 |
| 2242 | 27 5/8 | x 53 | 23 9/16 | x 24 1/16 | 3042 | 37 5/8 | x 53 | 33 9/16 | x 24 1/16 |
| 2246 | 27 5/8 | x 57 | 23 9/16 | x 26 1/16 | 3046 | 37 5/8 | x 57 | 33 9/16 | x 26 1/16 |
| 2248 | 27 5/8 | x 59 | 23 9/16 | x 27 1/16 | 3048 | 37 5/8 | x 59 | 33 9/16 | x 27 1/16 |
| 2252 | 27 5/8 | x 65 | 23 9/16 | x 30 1/16 | 3052 | 37 5/8 | x 65 | 33 9/16 | x 30 1/16 |
| 2256 | 27 5/8 | x 69 | 23 9/16 | x 32 1/16 | 3058 | 37 5/8 | x 71 | 33 9/16 | x 33 1/16 |
| 2262 | 27 5/8 | x 77 | 23 9/16 | x 36 1/16 | 3062 | 37 5/8 | x 77 | 33 9/16 | x 36 1/16 |

Seven D Industries, L.P.
Series 5900 Impact Single Hung
Thermal Specifications

Impact Glazing

| Glass Type | U-Value | SHGC | VT | w/ Grid | |
|-------------------------------------|---------|------|-----|---------|-----|
| | | | | SHGC | VT |
| 3/4" IG -Laminated/Air/Clear | .48 | .61 | .65 | .55 | .58 |
| 3/4" IG – Laminated/90% Argon/Low-E | .31 | .38 | .54 | .34 | .49 |